

NAS1351N6-28 SOCKET HEAD CAP SCREW SPEC

Description:

Fastener Length: 1-3/4", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1-3/4", NAS1351 series screw

NAS1351N6-28 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name: Screw, Cap, Socket Head

NSN: 5305-01-098-7213

NIIN: 010987213

FSC: Screws / 5305

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)

Manufacturer Country: United States

NAS1351N6-28 Specifications

Fastener Length:	1.710 Inches Minimum And 1.750 Inches Maximum
Head Diameter:	0.550 Inches Minimum And 0.562 Inches Maximum
Head Height:	0.368 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Material:	Iron Alloy 660 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.375 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard
Width Across Flats:	0.3125 Inches Minimum And 0.3160 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.627 Inches Minimum And 1.750 Inches Maximum
Thread Quantity Per Inch:	24
Thread Series Designator:	Unrf

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket-head-cap-screws/NAS1351N6-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.