



Military-Fasteners.com

# NAS1352N02-16 SOCKET HEAD SCREW SPEC

## Description:

Fastener Length: 1-", Thread: 2-56, Head Width: 5/64", Thread Length: 5/8"

*NAS1352N02-16 Manufacturer certs (CofC) are provided free on all orders*

Order this part online

## Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-01-351-3516
NIIN:	013513516
FSC:	Screws / 5305
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel
Manufacturer Country:	United States

# NAS1352N02-16 Specifications

<b>Fastener Length:</b>	1.000 Inches Nominal
<b>Hardness Rating:</b>	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
<b>Head Diameter:</b>	0.134 Inches Minimum And 0.140 Inches Maximum
<b>Head Height:</b>	0.083 Inches Minimum And 0.086 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Material:</b>	Iron Alloy 660 Overall
<b>Minimum Yield Strength:</b>	120000 Pounds Per Square Inch
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Internal Drive Style:</b>	Hexagon
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Specification/standard Data:</b>	80205-nas1352 Professional/industrial Association Standard
<b>Width Across Flats:</b>	0.0781 Inches Minimum And 0.0791 Inches Maximum
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.625 Inches Minimum
<b>Thread Quantity Per Inch:</b>	56
<b>Thread Series Designator:</b>	Unrc

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/NAS1352N02-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.