

NAS1635-04-6 SOCKET HEAD CAP SCREW SPEC

Description:

Fastener Length: 3/8", Thread: 4-40, Thread Length: 3/8

NAS1635-04-6 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name: Screw, Machine

NSN: 5305-00-498-1261

NIIN: 004981261

FSC: Screws / 5305

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)

Manufacturer Country: United States

NAS1635-04-6 Specifications

Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Head Style:	Pan
Nominal Thread Diameter:	0.112 Inches
Internal Drive Style:	Cross Recess Type 1
Screw Surface Treatment:	Passivate
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment Document And Classification:	Mil-f-14072 Finish E300 Mil Spec Single Treatment Response
Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.295 Inches Minimum And 0.375 Inches Maximum
Thread Quantity Per Inch:	40
Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket-head-cap-screws/NAS1635-04-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket-head-cap-screws/NAS1635-04-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket-head-cap-screws/NAS1635-04-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/nas-engage="https: