



Military-Fasteners.com

NAS1669-08L11 BLIND RIVET SPEC

Alternate P/N: PLT210-5-11

Description:

Fastener Length: 25/32", Head Width: 1/4", Jo-bolt, NAS1669 series rivet

NAS1669-08L11 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Rivet, Blind
NSN:	5320-00-938-6039
NIIN:	009386039
FSC:	Rivets / 5320
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc
Manufacturer Country:	United States

See page 2 for technical characteristics

NAS1669-08L11 Specifications

Expansion Device:	Serrated Stem-type W
Fastener Length:	0.778 Inches Minimum And 0.808 Inches Maximum
Grip Length:	0.096 Inches Minimum And 0.657 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
Hardness Rating:	39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut
Head Height:	0.096 Inches Maximum
Head Style:	Hexagon
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Ams 5614 Assn Std 2nd Material Response Sleeve Or Amstm A582 Assn Std 3rd Material Response Sleeve
Material:	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
Material:	Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 4130 Nut
Material:	Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve Or Steel Comp 303 Sleeve
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nut
Shank Diameter:	0.163 Inches Minimum And 0.165 Inches Maximum
Shear Strength:	3355 Double Pounds Per Square Inch
Shank Style:	Threaded Self-plugging Shank W/sleeve
Specification/standard Data:	80205-nas1669 Professional/industrial Association Standard
Width Across Flats:	0.244 Inches Minimum And 0.250 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl2 Fed Spec Single Treatment Response Bolt
Surface Treatment:	Cadmium Bolt And Chromate Bolt
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Cadmium Sleeve And Passivate Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind-rivets/NAS1669-08L11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.