



[Military-Fasteners.com](http://Military-Fasteners.com)

## NAS1669-6L7 BLIND RIVET SPEC

### Description:

Fastener Length: 43/64", Head Width: 1/2", Jo-bolt, NAS1669 series rivet

*NAS1669-6L7 Manufacturer certs (CofC) are provided free on all orders*

Order this part online

## Additional Information

Gov. Issued Name:	Rivet, Blind
NSN:	5320-00-814-3267
NIIN:	008143267
FSC:	Rivets / 5320
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc
Manufacturer Country:	United States

*See page 2 for technical characteristics*

# NAS1669-6L7 Specifications

Expansion Device:	Serrated Stem-type W
Fastener Length:	0.652 Inches Minimum And 0.682 Inches Maximum
Grip Length:	0.406 Inches Minimum And 0.469 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
Hardness Rating:	39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut
Head Height:	0.180 Inches Minimum And 0.190 Inches Maximum
Heat Treatment:	Annealed Overall
Head Style:	Hexagon
Material:	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
Material:	Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 4130 Nut
Material:	Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Lubrication:	Dry Film Or Wax
Material Document And Classification:	Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nut
Shank Diameter:	0.373 Inches Minimum And 0.375 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Special Features:	Heat Process Mil-h-6875
Width Across Flats:	0.491 Inches Minimum And 0.500 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416 Ty 1 Cl 3 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Bolt
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Nut
Surface Treatment:	Cadmium Bolt And Chromate Bolt
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Passivate Sleeve And Cadmium Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind-rivets/NAS1669-6L7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.