



- MATERIAL:**
- STRAP - 2024 ALUMINUM ALLOY (UNS A82024), ALCLAD PER AMSQQ-A-250/5, CONDITION T4 OR T42.
CORROSION RESISTANT STEEL 302 (UNS S30200) PER AMS 5516 OR 321 (UNS 32100) PER AMS 5510 OR 304
UNS S30400) PER AMS 5513
- CUSHION - SYNTHETIC RUBBER, CHLOROPRENE TYPE (NEOPRENE) PER AMS3209.
SILICONE RUBBER PER AMS3303
POLYTETRAFLUOROETHYLENE (PTFE) PER AMS3652
FABRIC POLYBENZIMIDAZOLE (PBI) FIBERGLASS POLYTETRAFLUOROETHYLENE (PTFE) IMPREGNATED PER
AMS3677.
- FINISH:**
- CRES - PASSIVATE PER AMS2700, METHOD 1, CLASS 4
ALUMINUM - NONE
PTFE - SODIUM TREATED (DECREASED SLIPPAGE CHARACTERISTICS)
PTFE - NONE (NATURAL)

EXAMPLE OF PART NUMBER:

NAS1677 D 8 - 32 T X = STRAP RETAINING, ALUMINUM ALLOY, .500 HIGH, 2.000 WIDE, PTFE CUSHION,
SODIUM TREATED, .213 TO .223 DIAMETER MOUNTING HOLE.

"X" AFTER CUSHION CODE = .213 TO .223 DIAMETER MOUNTING HOLE, OMIT FOR
.204 HOLE

CUSHION

- K = PTFE NATURAL
- N = SYNTHETIC RUBBER
- S = SILICONE RUBBER
- T = PTFE (SODIUM TREATED)
- Z = FABRIC, PBI/PTFE IMPREGNATED

"B" DIMENSION IN .0625 INCREMENTS. SEE NOTE 2

W = WEDGE SEE NOTE 4
"-" (NO LETTER) = NO WEDGE

"A" DIMENSION IN .0625 INCREMENTS. SEE NOTE 2

MATERIAL: D = ALUMINUM ALLOY
C = CRES

DOCUMENT NUMBER

THIS CATALOG PAGE IS FOR REFERENCE ONLY. REQUEST A
CERTIFIED UMPCO DRAWING FOR ACTUAL SPECIFICATIONS.
ANY CONFLICT BETWEEN THIS DOCUMENT AND THE CERTIFIED
DRAWING, THE CERTIFIED DRAWING WILL TAKE PRECEDENCE.
IF THE DOCUMENT IS CONTROLLED BY ANY OTHER SOURCE
THAN UMPCO, THE CERTIFIED DRAWING MUST BE PURCHASED
THROUGH THAT ORGANIZATION.

UMPCO, INC
CAGE CODE No. 18076

REV
A
07/21/11

NAS1677

STRAP, RETAINING- CUSHIONED, RECTANGULAR, 2 PIECE

PART NUMBER

