



Military-Fasteners.com

NAS1919M04-02 BLIND RIVET SPEC

Description:

NAS1919 series rivet

NAS1919M04-02 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Blind Rivet
NSN:	5320-01-360-9175
NIIN:	013609175
FSC:	Rivets / 5320
Schedule B:	7508.90.0000, Other articles of nickel, nesoi (excluding cloth, grill & netting of nickel wire)
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc
Manufacturer Country:	United States

See page 2 for technical characteristics

NAS1919M04-02 Specifications

Expansion Device:	Serrated Stem-type W
Grip Length:	0.0630 Inches Minimum And 0.1250 Inches Maximum
Head Height:	0.0540 Inches Minimum And 0.0640 Inches Maximum
Head Major Diameter:	0.2380 Inches Minimum And 0.2520 Inches Maximum
Head Style:	Universal
Material:	Iron Alloy 660 Locking Ring Or Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ringnickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeveiron Alloy 660 Stem
Shank Diameter:	0.1240 Inches Minimum And 0.1280 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind-rivets/NAS1919M04-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.