



Military-Fasteners.com

NAS6403U10 BOLT SPEC

Description:

Fastener Length: 61/64", Thread: 10-32, Thread Length: 11/32"

NAS6403U10 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Bolt, Shear
NSN:	5306-00-500-2282
NIIN:	005002282
FSC:	Bolts / 5306
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	013280, Alum Bolts
Manufacturer Country:	United States

See page 2 for technical characteristics

NAS6403U10 Specifications

Fastener Length:	0.933 Inches Minimum And 0.963 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Head Style:	Dished Hexagon
Material:	Titanium Alloy Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas6403 Professional/industrial Association Standard
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.298 Inches Minimum And 0.348 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear-bolts/NAS6403U10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.