



★ FASTENERS

Military-Fasteners.com

P/N NAS8602-1

Description

length: 0.385", grip: 0.062", thread: 8-32, reduced head close, tolerance, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS86021
Minimum Qty (MOQ):	50
NSN:	5305-01-525-0806
Schedule B:	7318.15.2095
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS8602-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.370 Inches Minimum And 0.390 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.226 Inches Nominal
Head Height:	0.039 Inches Nominal
Grip Diameter:	0.162 Inches Minimum And 0.163 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	C17 Acft
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw Close Tolerance
Material:	Steel Comp 4340 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+bolts/NAS8602-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.