

# NJL0281D (NPN) NJL0302D (PNP)

## Complementary ThermalTrak™ Transistors

The ThermalTrak family of devices has been designed to eliminate thermal equilibrium lag time and bias trimming in audio amplifier applications. They can also be used in other applications as transistor die protection devices.

### Features

- Thermally Matched Bias Diode
- Instant Thermal Bias Tracking
- Absolute Thermal Integrity
- High Safe Operating Area
- Pb-Free Packages are Available\*

### Benefits

- Eliminates Thermal Equilibrium Lag Time and Bias Trimming
- Superior Sound Quality Through Improved Dynamic Temperature Response
- Significantly Improved Bias Stability
- Simplified Assembly
  - ♦ Reduced Labor Costs
  - ♦ Reduced Component Count
- High Reliability

### Applications

- High-End Consumer Audio Products
  - ♦ Home Amplifiers
  - ♦ Home Receivers
- Professional Audio Amplifiers
  - ♦ Theater and Stadium Sound Systems
  - ♦ Public Address Systems (PAs)


[www.DataSheet4U.com](http://www.DataSheet4U.com)



**ON Semiconductor®**


<http://onsemi.com>

**BIPOLAR POWER  
TRANSISTORS**  
**15 AMP, 260 VOLT, 180 WATT**




TO-264, 5 LEAD  
CASE 340AA  
STYLE 1

### MARKING DIAGRAM



### SCHEMATIC



NJL0xxxD = Device Code  
xxx = 281 or 302  
G = Pb-Free Package  
A = Assembly Location  
YY = Year  
WW = Work Week

### ORDERING INFORMATION

| Device    | Package             | Shipping        |
|-----------|---------------------|-----------------|
| NJL0281D  | TO-264              | 25 Units / Rail |
| NJL0281DG | TO-264<br>(Pb-Free) | 25 Units / Rail |
| NJL0302D  | TO-264              | 25 Units / Rail |
| NJL0302DG | TO-264<br>(Pb-Free) | 25 Units / Rail |

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## NJL0281D (NPN) NJL0302D (PNP)

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Rating                                                                                | Symbol         | Value        | Unit                     |
|---------------------------------------------------------------------------------------|----------------|--------------|--------------------------|
| Collector-Emitter Voltage                                                             | $V_{CEO}$      | 260          | Vdc                      |
| Collector-Base Voltage                                                                | $V_{CBO}$      | 260          | Vdc                      |
| Emitter-Base Voltage                                                                  | $V_{EBO}$      | 5            | Vdc                      |
| Collector-Emitter Voltage – 1.5 V                                                     | $V_{CEX}$      | 260          | Vdc                      |
| Collector Current<br>– Continuous<br>– Peak (Note 1)                                  | $I_C$          | 15<br>25     | Adc                      |
| Base Current – Continuous                                                             | $I_B$          | 1.5          | Adc                      |
| Total Power Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate Above $25^\circ\text{C}$ | $P_D$          | 180<br>1.43  | W<br>W/ $^\circ\text{C}$ |
| Operating and Storage Junction Temperature Range                                      | $T_J, T_{stg}$ | – 65 to +150 | $^\circ\text{C}$         |
| DC Blocking Voltage                                                                   | $V_R$          | 200          | V                        |
| Average Rectified Forward Current                                                     | $I_{F(AV)}$    | 1.0          | A                        |

### THERMAL CHARACTERISTICS

| Characteristic                       | Symbol          | Max   | Unit               |
|--------------------------------------|-----------------|-------|--------------------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 0.694 | $^\circ\text{C/W}$ |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Pulse Test: Pulse Width = 5 ms, Duty Cycle < 10%.

### ATTRIBUTES


| Characteristic                                      | Value                |
|-----------------------------------------------------|----------------------|
| ESD Protection<br>Human Body Model<br>Machine Model | >8000 V<br>> 400 V   |
| Flammability Rating                                 | UL 94 V-0 @ 0.125 in |

# NJL0281D (NPN) NJL0302D (PNP)


## ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic                                                                                                                                                                       | Symbol         | Min            | Max               | Unit            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------------|-------------------|-----------------|
| <b>OFF CHARACTERISTICS</b>                                                                                                                                                           |                |                |                   |                 |
| Collector-Emitter Sustaining Voltage<br>( $I_C = 100\text{ mAdc}$ , $I_B = 0$ )                                                                                                      | $V_{CEO(sus)}$ | 260            | –                 | Vdc             |
| Collector Cutoff Current<br>( $V_{CB} = 260\text{ Vdc}$ , $I_E = 0$ )                                                                                                                | $I_{CBO}$      | –              | 10                | $\mu\text{Adc}$ |
| Emitter Cutoff Current<br>( $V_{EB} = 5\text{ Vdc}$ , $I_C = 0$ )                                                                                                                    | $I_{EBO}$      | –              | 5                 | $\mu\text{Adc}$ |
| <b>ON CHARACTERISTICS</b>                                                                                                                                                            |                |                |                   |                 |
| DC Current Gain<br>( $I_C = 500\text{ mAdc}$ , $V_{CE} = 5\text{ Vdc}$ )<br>( $I_C = 1\text{ Adc}$ , $V_{CE} = 5\text{ Vdc}$ )<br>( $I_C = 3\text{ Adc}$ , $V_{CE} = 5\text{ Vdc}$ ) | $h_{FE}$       | 75<br>75<br>75 | 150<br>150<br>150 |                 |
| Collector-Emitter Saturation Voltage<br>( $I_C = 5\text{ Adc}$ , $I_B = 0.5\text{ Adc}$ )                                                                                            | $V_{CE(sat)}$  | –              | 1.0               | Vdc             |
| Base-Emitter On Voltage<br>( $I_C = 5\text{ Adc}$ , $V_{CE} = 5\text{ Vdc}$ )                                                                                                        | $V_{CE(on)}$   | –              | 1.2               | Vdc             |
| <b>DYNAMIC CHARACTERISTICS</b>                                                                                                                                                       |                |                |                   |                 |
| Current-Gain – Bandwidth Product<br>( $I_C = 1\text{ Adc}$ , $V_{CE} = 5\text{ Vdc}$ , $f_{test} = 1\text{ MHz}$ )                                                                   | $f_T$          | 30             | –                 | MHz             |
| Output Capacitance<br>( $V_{CB} = 10\text{ Vdc}$ , $I_E = 0$ , $f_{test} = 1\text{ MHz}$ )                                                                                           | $C_{ob}$       | –              | 400               | pF              |
| Maximum Instantaneous Forward Voltage (Note 2)<br>( $I_F = 1.0\text{ A}$ , $T_J = 25^\circ\text{C}$ )<br>( $I_F = 1.0\text{ A}$ , $T_J = 150^\circ\text{C}$ )                        | $V_F$          | 1.1<br>0.93    |                   | V               |
| Maximum Instantaneous Reverse Current (Note 2)<br>(Rated dc Voltage, $T_J = 25^\circ\text{C}$ )<br>(Rated dc Voltage, $T_J = 150^\circ\text{C}$ )                                    | $i_R$          | 10<br>100      |                   | $\mu\text{A}$   |
| Maximum Reverse Recovery Time<br>( $I_F = 1.0\text{ A}$ , $di/dt = 50\text{ A}/\mu\text{s}$ )                                                                                        | $t_{rr}$       | 100            |                   | ns              |

2. Diode Pulse Test: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .




**Figure 1. Power Derating**




**Figure 2. Safe Operating Area**


# **NJL0281D (NPN) NJL0302D (PNP)**




**Figure 3. NJL0281A DC Current Gain**




**Figure 4. NJL0302A DC Current Gain**




**Figure 5. NJL0281A Base-Emitter Voltage**



**Figure 6. NJL0302A Base-Emitter Voltage**




**Figure 7. NJL0281A Saturation Voltage**




**Figure 8. NJL0302A Saturation Voltage**


## NJL0281D (NPN) NJL0302D (PNP)




**Figure 9. NJL0281A Current Gain Bandwidth Product**



**Figure 10. NJL0302A Current Gain Bandwidth Product**



**Figure 11. Typical Reverse Current**




**Figure 12. Typical Forward Voltage**

# NJL0281D (NPN) NJL0302D (PNP)

## PACKAGE DIMENSIONS

TO-264, 5 LEAD  
CASE 340AA-01  
ISSUE O



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.

| DIM | MILLIMETERS |        |        | INCHES |        |        |
|-----|-------------|--------|--------|--------|--------|--------|
|     | MIN         | NOM    | MAX    | MIN    | NOM    | MAX    |
| A   | 25.857      | 25.984 | 26.111 | 1.018  | 1.023  | 1.028  |
| B   | 19.761      | 19.888 | 20.015 | 0.778  | 0.783  | 0.788  |
| C   | 4.928       | 5.055  | 5.182  | 0.194  | 0.199  | 0.204  |
| D   | 1.219       | BSC    |        | 0.0480 | BSC    |        |
| E   | 2.032       | 2.108  | 2.184  | 0.0800 | 0.0830 | 0.0860 |
| F   | 1.981       | BSC    |        | 0.0780 | BSC    |        |
| G   | 3.81        | BSC    |        | 0.150  | BSC    |        |
| H   | 2.667       | 2.718  | 2.769  | 0.1050 | 0.1070 | 0.1090 |
| J   | 0.584       | BSC    |        | 0.0230 | BSC    |        |
| K   | 20.422      | 20.549 | 20.676 | 0.804  | 0.809  | 0.814  |
| L   | 11.28       | REF    |        | 0.444  | REF    |        |
| M   | 0°          | ---    | 7°     | 0°     | ---    | 7°     |
| N   | 4.57        | REF    |        | 0.180  | REF    |        |
| P   | 2.259       | 2.386  | 2.513  | 0.0889 | 0.0939 | 0.0989 |
| Q   | 3.480       | BSC    |        | 0.1370 | BSC    |        |
| R   | 2.54        | REF    |        | 0.100  | REF    |        |
| S   | 0°          | ---    | 8°     | 0°     | ---    | 8°     |
| U   | 6.17        | REF    |        | 0.243  | REF    |        |
| W   | 0°          | ---    | 6°     | 0°     | ---    | 6°     |
| Y   | 2.388       | BSC    |        | 0.0940 | BSC    |        |

### STYLE 1:

1. BASE
2. EMITTER
3. COLLECTOR
4. ANODE
5. CATHODE

ThermalTrak is a trademark of Semiconductor Components Industries, LLC (SCILLC).

**ON Semiconductor** and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative

NJL0281D/D