


Subminiature PCB Telecom Relay

PC312B



FEATURES

- Subminiature design
- PC Terminals on .1 in. grid pattern
- Contact capacity from 1 mA to 5A
- Meets FCC part 68 voltage surge
- Class "B" insulation standard
- Three coil sensitivities available
- Sealed, immersion cleanable



File # E86876

UL/CSA RATINGS

Contact Form	1 Form C SPDT
Rated Load	1A @ 120VAC / 30 VDC
Rated Load (Special)	3A & 5A @ 120VAC / 30VDC
Max. Switching Current	2 Amps
Max. Switching Current (S)	5 Amps
Minimum Load (Gold Plated)	1 mA @ 1 VDC

CONTACT DATA

Material		Ag (Fine Silver), Ag+Au (Fine Silver Gold Clad) AgNi (Silver Nickel), AgCdO (Silver Cadmium Oxide)
Initial Contact Resistance		100 milliohms max @ 0.1A, 6VDC (with Gold Plate)
Service Life	Mechanical	1 X 10 ⁷ Operations
	Electrical	1 X 10 ⁵ Operations

CHARACTERISTICS

Operate Time	5 ms. Max.
Release Time	5 ms. Max.
Insulation Resistance	100 megohms min, at 500VDC, 50%RH
Dielectric Strength	1250 Vrms, 1 min. between coil and contacts 500 Vrms, 1 min. between open contacts: 750 Vrms, 1 min for S version
Surge Resistance	1500 V, between coil and contacts (FCC Part 68)
Shock Resistance	10 g, 11ms, functional; 100 g, destructive
Vibration Resistance	DA 1.5 mm, 10 - 55 Hz
Power Consumption	0.45 W, 0.36 W or 0.2 W
Ambient Temperature Range	-25 to 70 C operating, -30 to 130 storage
Weight	3.5 grams approx.

ORDERING INFORMATION

Example:	PC312B	-12	H	S
Model				
Coil Voltage				
Coil Sensitivity				
Nil: 0.36 W; B: 0.45 W; H: 0.2 W				
Current Rating				
Nil: Standard, 2 Amp; S: Special 5 Amp				

COIL DATA

Coil Voltage	Resistance ohms $\pm 10\%$			Must Operate Voltage Max. (VDC)	Must Release Voltage Min. (VDC)
	Sensitivity Code B 0.45 W	Standard Sensitivity 0.36 W	Sensitivity Code H 0.2 W		
3	20	25	45	2.25	0.3
5	56	70	120	3.75	0.5
6	80	100	180	4.50	0.6
9	180	220	440	6.75	0.9
12	320	400	700	9.00	1.2
18	720	900	1620	13.5	1.8
24	1280	1600	2800	18.00	2.4

Note: Custom coil voltages within the ranges shown are available on special order.

Dimensions in Inches (millimeters)



Drawings are 2X actual size

Side View

End View

Bottom View
PC Board Layout

Wiring Diagram



Notes:

Tolerances $\pm .010$ unless otherwise noted

PICKER
COMPONENTS

3220 Commander Drive, Suite 102, Carrollton, Texas 75006

Sales: Call Toll Free (888) 997-3933 Fax (818) 342-5296 email: pickerwest@sbcglobal.net URL: pickercomponents.com