



## SOT-563 Package

### Description

The PESDLC563T5VU protects sensitive semiconductor components from damage or upset due to electrostatic discharge (ESD) and other voltage induced transient events. They feature large cross-sectional area junctions for conducting high transient currents, offer desirable electrical characteristics for board level protection, such as fast response time, low operating voltage. It gives designer the flexibility to provide five lines I/O protection. All pins are rated to withstand 15kV ESD pulses using the IEC61000-4-2 air discharge method, which can meet the requirement of level 4.

#### Feature

- 100W peak pulse power (t<sub>P</sub> = 8/20µs)
- SOT-563 package
- Protects four bidirectional lines and five unidirectional lines
- Low clamping voltage
- Low capacitance
- Working voltage: 5V
- RoHS compliant transient protection for high speed data lines to IEC61000-4-2(ESD)±15kV(air),±8kV(contact)

### **Mechanical Characteristics**

- Lead finish:100% matte Sn(Tin)
- Mounting position: Any
- Qualified max reflow temperature:260°C
- Device meets MSL 1 requirements
- Pure tin plating: 7 ~ 17 um
- ➢ Pin flatness:≤3mil

## **Electronics Parameter**

Symbol	Parameter			
V <sub>RWM</sub>	Peak Reverse Working Voltage			
I <sub>R</sub>	Reverse Leakage Current @ V <sub>RWM</sub>			
V <sub>BR</sub>	Breakdown Voltage @ I <sub>T</sub>			
Ι <sub>Τ</sub>	Test Current			
IPP	Maximum Reverse Peak Pulse Curren			
Vc	Clamping Voltage @ IPP			
P <sub>PP</sub>	Peak Pulse Power			
CJ	Junction Capacitance			
I <sub>F</sub>	Forward Current			
VF	Forward Voltage @ I <sub>F</sub>			





**SOT-563** 

5

4

6

PESDLC563T5VU

Marking Code : 97+

## Applications

- Communication systems & cellular phones
- Printers
- Notebook and hand hold computers
- PDAs
- Video equipment





## SOT-563 Package

## Electrical characteristics per line@25°C( unless otherwise specified) \*NOTE1

Parameter	Symbol	Conditions	Min.	Тур.	Max.	Units
Reverse Stand-off Voltage	V <sub>RWM</sub>				5	V
Reverse Breakdown Voltage	V <sub>BR</sub>	$I_t = 1mA$	6.1	6.7	7.1	V
Reverse Leakage Current	I <sub>R</sub>	V <sub>RWM</sub> = 5V T=25°C			1	μA
Clamping Voltage	Vc	$I_{PP} = 1A$ $t_P = 8/20\mu S$			8.8	V
Clamping Voltage	Vc	$I_{PP}=3A$ $t_{P}=8/20\mu S$			11.5	V
Junction Capacitance	Cj	$V_R=0V$ f = 1MHz		10	14	pF

# Absolute maximum rating@25°C \*NOTE1

Rating	Symbol	Value	Units
Peak Pulse Power (t <sub>p</sub> =8/20µs)	P <sub>pp</sub>	100	W
Forward Voltage(@1A, 8/20µs)	VF	1.5	V
Operating Temperature	TJ	-55 to +150	°C
Storage Temperature	T <sub>STG</sub>	-55 to +150	°C

Note1: Pin 1, 3, 4, 5 or 6 to Pin 2

## **Typical Characteristics**



Fig.1 Typical Clamping Voltage VS Peak Pulse Current for PESDLC563T5VU





## PESDLC563T5VU

SOT-563 Package



## **Solder Reflow Recommendation**

Peak Temp=257°C, Ramp Rate=0.802deg. °C/sec



## **PCB** Design

For TVS diodes a low-ohmic and low-inductive path to chassis earth is absolutely mandatory in order to achieve good ESD protection. Novices in the area of ESD protection should take following suggestions to heart:

- > Do not use stubs, but place the cathode of the TVS diode directly on the signal trace.
- Do not make false economies and save copper for the ground connection.
- Place via holes to ground as close as possible to the anode of the TVS diode.
- Use as many via holes as possible for the ground connection.
- > Keep the length of via holes in mind! The longer the more inductance they will have.

Rev. =h01





PESDLC563T5VU

**100W ESD Protector** 

SOT-563 Package





COMPLIANT

PESDLC563T5VU

SOT-563 Package

## **Ordering Information:**

Device PN	Packing
PESDLC563T5VU -T <sup>(1)</sup> H <sup>(2)</sup> -WS	Tape&Reel: 3 Kpcs/Reel

Note: (1) Packing code, Tape & Reel Packing

(2) Haloge free product for packing code suffix "H"

## \*\*\*Disclaimer\*\*\*

WILLAS reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. WILLAS or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on WILLAS data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. WILLAS does not assume any liability arising out of the application or use of any product or circuit.

WILLAS products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of WILLAS. Customers using or selling WILLAS components for use in such applications do so at their own risk and shall agree to fully indemnify WILLAS Inc and its subsidiaries harmless against all claims, damages and expenditures.