

PJSD05FN2

SINGLE LINE TVS DIODE FOR ESD PROTECTION PORTABLE ELECTRONICS

VOLTAGE 5 Volts **POWER** 200 Watts



DFN 2L Unit : inch(mm)

FEATURES

- 200 Watts peak pules power($t_p=8/20\mu s$)
- Small package for use in portable electronics
- IEC61000-4-2 8KV contact 15KV Air compliant
- Low clamping voltage and leakage current
- In compliance with EU RoHS 2002/95/EC directives

APPLICATIONS

- Case: DFN 2L plastic
- Terminals : Solderable per MIL-STD-750, Method 2026
- Polarity : Color band cathode
- Marking : BA
- Video I/O ports protection
- Set Top Boxes
- Portable Instrumentation



MAXIMUM RATINGS

ABSOLUTE MAXIMUM RATING

Rating	Symbol	Value	Units
Peak Pulse Power ($t_p=8/20 \mu s$)	P_{PP}	200	W
Maximum Peak Pulse Current	I_{PPM}	18	A
ESD Voltage per HBM MIL-STD-883	V_{ESD}	25	KV
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-50 to +150	°C

ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Conditions	Min.	Typical	Max.	Units
Reverse Stand-Off Voltage	V_{RWM}	-	-	-	5	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR}=1mA$	6.0	-	7.2	V
Reverse Leakage Current	I_R	$V_R=5V$	-	-	1	μA
Clamping Voltage(8/20 μs)	V_C	$I_{PP}=5A$	-	-	11	V
Clamping Voltage(8/20 μs)	V_C	$I_{PP}=15A$	-	-	14	V
Off State Junction Capacitance	C_J	0Vdc Bias=f=1MHz	-	-	160	pF
Off State Junction Capacitance	C_J	5Vdc Bias=f=1MHz	-	-	80	pF

PAN JIT RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE

PJSD05FN2




Fig.1 8/20 μs Peak Pulse Current Waveform




Fig.2 Typical Peak Clamping Voltage




Fig.3 Typical Junction Capacitance




Fig.4 Typical Reverse Characteristics





Fig.5 Typical Forward Characteristics

PJSD05FN2

MOUNTING PAD LAYOUT

DFN 2L

Unit: inch (mm)



ORDER INFORMATION

- Packing information
T/R - 8K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2011

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.