

ML23HS / PL23HS Series: 1.8° - Size 23





• Phases	2
• Steps / Revolution	200
• Step Accuracy	±5%
• Shaft Load (20,000 Hours at 1000 RPM)	
Axial	40 N (9 Lbs.) Push 130 N (30 Lbs.) Pull
Radial	70 N (15.5 Lbs.) At Flat Center
• IP Rating	40
• Approvals	UL Recognized File E465363, RoHS
• Operating Temp.	-20°C to +50°C
• Insulation Class	B, 130°C
• Insulation Resistance	100 MegOhms

M L23HS 0 P 4 100 -E

Motor Technology		Options	
M	High Torque Step Motor	Omit	No Options
P	PowerPlus Step Motor	-E	0.25 inch Diameter Rear Shaft with Encoder Mounting Holes
Basic Motor Length (Max)		Winding	
	0 39mm (1.54 in.)	###	Current rating x 100
	4 45mm (1.77 in.)		
	8 55mm (2.17 in.) 1 Stack		
	A 77mm (3.03 in.) 2 Stack		
	C 112mm (4.41 in.) 3 Stack		
Electrical Connection		Number of Connections	
L	Leads	4	4 Lead-Bipolar
P	Plug-in Connector	6	6 Lead-Unipolar(or Bipolar)

Dimensions: mm (in)



ML23HS - 4 Lead Bi-Polar

Length	Model Number	Connect	Rated Current	Holding Torque		Winding Ohms mH		Detent Torque		Rotor Inertia		Motor Weight	
	Single Shaft	P=Plug L=Leads	Amps (mounted)	Nm Typ.	oz-in TYP.	±10% @20 C	Typ.	mNm oz-in		g cm ² oz-in ²		kg Lbs	
39 mm (1.54 in.)	^ ML23HS0P4100	P	1	0.82	120	6.3	15.9	24	3.4	121.5	0.66	0.42	0.93
	^ ML23HS0P4160	P	1.6	0.83	120	2.6	6.5						
	^ ML23HS0P4220	P	2.2	0.84	120	1.39	3.5						
	^ ML23HS0L4350	L	3.5	0.82	120	0.56	1.3						
45 mm (1.77 in.)	^ ML23HS4P4100	P	1	1.20	170	7.3	22	28	4	155	0.85	0.48	1.1
	^ ML23HS4P4150	P	1.5	1.20	170	3.1	9.2						
	^ ML23HS4P4210	P	2.1	1.20	170	1.62	4.8						
	^ ML23HS4L4340	L	3.4	1.20	170	0.65	1.8						
55 mm (2.17 in.) 1 Stack	^ ML23HS8P4100	P	1	1.50	210	7.6	33	45	6.4	221	1.2	0.6	1.3
	^ ML23HS8P4150	P	1.5	1.50	210	3.1	13.6						
	^ ML23HS8P4220	P	2.2	1.50	210	1.6	6.9						
	^ ML23HS8L4360	L	3.6	1.50	210	0.63	2.6						
	^ ML23HS8L4550	L	5.5	1.50	210	0.28	1.03						
77 mm (3.03 in.) 2 Stack	^ ML23HSAP4100	P	1	2.30	330	8.8	39	75	11	391	2.1	1	2.2
	^ ML23HSAP4150	P	1.5	2.30	330	4.3	18.5						
	^ ML23HSAP4200	P	2	2.30	330	2.3	9.8						
	^ ML23HSAP4300	P	3	2.30	330	1.1	4.5						
	^ ML23HSAL4500	L	5	2.30	330	0.39	1.53						
112 mm (4.41 in.) 3 Stack	^ ML23HSCP4150	P	1.5	3.20	450	5.1	23	120	17	610	3.3	1.5	3.3
	^ ML23HSCP4200	P	2	3.20	450	2.7	11.8						
	^ ML23HSCP4300	P	3	3.20	450	1.29	5.5						
	^ ML23HSCL4500	L	5	3.20	450	0.51	1.85						

^ Preferred model

PL23HS - PowerPlus - 4 Lead Bi-Polar


Length	Model Number	Connect	Rated Current	Holding Torque		Winding Ohms mH		Detent Torque		Rotor Inertia		Motor Weight	
	Single Shaft	P=Plug L=Leads	Amps (mounted)	Nm Typ.	oz-in TYP.	±10% @20 C	Typ.	mNm oz-in		g cm ² oz-in ²		kg Lbs	
55 mm (2.17 in.) 1 Stack	^ PL23HS8P4100	P	1	2.30	330	7.6	26	100	14	260	1.4	0.65	1.4
	^ PL23HS8P4150	P	1.5	2.20	310	3.1	10.7						
	^ PL23HS8P4220	P	2.2	2.30	330	1.6	5.4						
	^ PL23HS8L4360	L	3.6	2.30	330	0.63	2						
	^ PL23HS8L4550	L	5.5	2.20	310	0.28	0.8						
77 mm (3.03 in.) 2 Stack	^ PL23HSAP4100	P	1	3.30	470	8.8	32	150	21	460	2.5	1.1	2.4
	^ PL23HSAP4150	P	1.5	3.40	480	4.3	15.2						
	^ PL23HSAP4200	P	2	3.30	470	2.3	8.1						
	^ PL23HSAP4300	P	3	3.30	470	1.1	3.7						
	^ PL23HSAL4500	L	5	3.30	470	0.39	1.27						

^ Preferred model

Mating Connector With Leads (order separately)

Dimensions: mm (in)

4 Lead Part Number 4634 1402 01891




ML23HS0

ML23HS4


ML23HS8

ML23HS4


ML23HS0P4100




ML23HS4P4100




ML23HS8P4100




ML23HS4P4100




ML23HS0P4160




ML23HS4P4150




ML23HS8P4150




ML23HS4P4150




ML23HS0P4220




ML23HS4P4210




ML23HS8P4220




ML23HS4P4200




ML23HS0L4350




ML23HS4L4340



ML23HS8L4550



ML23HS4L4500



ML23HSC

PowerPlus PL23HS8

PowerPlus PL23HS

