


SMT Power Inductors

High Current Molded Power Inductor - PA4547 & PM4547 Series



- Height:** 1.5mm Max
- Footprint:** 3.8mm x 3.4mm Max
- Current Rating:** up to 7.0A
- Inductance Range:** 0.22uH to 10.0uH
- High current, low DCR, and high efficiency
- High reliability
- Minimized acoustic noise and minimized leakage flux noise

Electrical Specifications @ 25°C - Operating Temperature -55°C to +125°C

Commercial ^{5,6}	Automotive ^{5,6}	Inductance 100KHz, 1.0V uH±20%	Rated Current A	DC Resistance		Saturation Current A
				TYP. mΩ	MAX. mΩ	
PA4547.221NLT		0.22	7.00	14	17	10.8
PA4547.471NLT	PM4547.471NLT	0.47	5.50	23.3	28	8.0
PA4547.561NLT	PM4547.561NLT	0.56	5.00	28	33	7.2
PA4547.681NLT	PM4547.681NLT	0.68	4.50	34	42	6.5
PA4547.102NLT	PM4547.102NLT	1.00	3.60	41	50	5.8
PA4547.152NLT	PM4547.152NLT	1.50	3.40	64	77	4.0
PA4547.222NLT	PM4547.222NLT	2.20	3.20	82	98	3.8
PA4547.332NLT	PM4547.332NLT	3.30	2.50	170	205	3.2
PA4547.472NLT	PM4547.472NLT	4.70	1.90	220	264	2.8
PA4547.562NLT	PM4547.562NLT	5.60	1.70	265	318	2.3
PA4547.682NLT	PM4547.682NLT	6.80	1.50	290	348	2.0
PA4547.822NLT	PM4547.822NLT	8.20	1.30	390	468	1.8
PA4547.103NLT	PM4547.103NLT	10.00	1.20	435	522	1.6

Notes:


- Actual temperature of the component during system operation (ambient plus temperature rise) must be within the standard operating range.
- The saturation current is the current at which the initial inductance drops approximately 30% at the stated ambient temperature. This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effect) to the component.
- The rated current is the DC current required to raise the component temperature by approximately 40 °C. Take note that the components' performance varies depending on the system condition. It is suggested that the component be tested at the system level, to verify the temperature rise of the component during system operation.
- The part temperature (ambient+temp rise) should not exceed 125 °C under worst case operating conditions. Circuit design, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
- Parts shown in bold are standard catalog parts and are available through sample stock and distribution. Parts in lighter font are available but are not necessarily held in sample stock or distribution **and lead times may be longer**. Please contact Pulse for availability.
- The PA4547.XXXNLT and PM4547.XXXNLT are both AEC-Q200 qualified. The PM4547.XXXNLT part numbers are also IATF16949 certified. The mechanical dimensions are 100% tested in production but do not necessarily meet a product capability index (Cpk) 1.33 and therefore the PM4547.XXXNLT may not strictly conform to PPAP.

SMT Power Inductors


High Current Molded Power Inductor - PA4547 & PM4547 Series

Mechanical

PA4547/PM4547



FINAL LAYOUT




SUGGESTED PAD LAYOUT

Series	A	B	C	D	E	L	G	H
PA4547/PM4547	3.5±0.3	3.2±0.2	1.3±0.2	0.7±0.2	1.2±0.2	4.1	1.9	1.45

All Dimensions in mm.

TAPE & REEL INFO



SURFACE MOUNTING TYPE, REEL/TAPE LIST

	REEL SIZE (mm)		TAPE SIZE (mm)			QTY
	A	G	P ₁	W	K ₀	
PA4547/PM4547	Ø330	12.4	8	12	1.8	3000

For More Information

Pulse Worldwide Headquarters

15255 Innovation Drive Ste 100
San Diego, CA 92128
U.S.A.

Pulse Europe

Pulse Electronics GmbH
Am Rottland 12
58540 Meinerzhagen
Germany

Pulse China Headquarters

Pulse Electronics (Shenzhen) CO., LTD
D708, Shenzhen Academy of
Aerospace Technology,
The 10th Keji South Road,
Nanshan District, Shenzhen,
P.R. China 518057

Pulse North China

Room 2704/2705
Super Ocean Finance Ctr.
2067 Yan An Road West
Shanghai 200336
China

Pulse South Asia

3 Fraser Street
0428 DUO Tower
Singapore 189352

Pulse North Asia

1F., No.111 Xiyuan Rd
Zhongli City
Taoyuan City 32057
Taiwan (R.O.C)

Tel: 858 674 8100
Fax: 858 674 8262

Tel: 49 2354 777 100
Fax: 49 2354 777 168

Tel: 86 755 33966678
Fax: 86 755 33966700

Tel: 86 21 62787060
Fax: 86 2162786973

Tel: 65 6287 8998
Fax: 65 6280 0080

Tel: 886 3 4356768
Fax: 886 3 4356820

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2019. Pulse Electronics, Inc. All rights reserved.