

Product Search Data Sheet


# PTGL07AR650H8B52B0

Note: This datasheet may be out of date. <u>Please download the latest datasheet of PTGL07AR650H8B52B0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> https://www.murata.com/en-eu/products/productdetail?partno=PTGL07AR650H8B52B0



#### Appearance & Shape







 Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
Circuit is protected until current is turned off.

3. Restores the original low resistance value automatically once the overload is removed.

4. Non-contact design leads to long life and no noise. Durable and strong against mechanical vibration and shock because it is a solid element.

## Applications

Limited Usage	Consumer Grade
Other Usage	1. Transformers 2. Transistors 3. Fluorescent Lamps

### Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	300

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. Please download the latest datasheet of PTGL07AR650H8B52B0 from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=PTGL07AR650H8B52B0

# PTGL07AR650H8B52B0

## Specifications

Max. Voltage	265V	d: Lead Diameter	0.6mm
Hold Current	68mA	Shape	Lead
Measure Condition of Hold Current	(at +60°C)	Mass	0.58g
Hold Current (2)	84mA		
Measure Condition of Hold Current (2)	(at +25℃)		
Trip Current	162mA		
Measure Condition of Trip Current	(at +25°C)		
Trip Current(2)	190mA		
Measure Condition of Trip Current(2)	(at -10°C)		
Max. Current	1A		
Resistance (25°C)	65Ω		
Resistance Value Tolerance (at 25°C)	±25%		
Power Consumption(typ)	1.3W		
Operating Temperature Range	-10℃ to 60℃		
D: Outer Dimension	8mm		
Thickness	6mm		
F: Lead Space	5mm		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering






PTGL07AR650H8B52B0


Note: This datasheet may be out of date. <u>Please download the latest datasheet of PTGL07AR650H8B52B0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> https://www.murata.com/en-eu/products/productdetail?partno=PTGL07AR650H8B52B0




INNOVATOR IN ELECTRON



Resistance-Temperature Charac.



Protective Threshold Current Range



Operating Time (Typical Curve)

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering