

. .

Note: This datasheet may be out of date.

Please download the latest datasheet of PTGL13AR100H8B72B0 from the official website of Murata

Manufacturing Co., Ltd.

https://www.murata.com/en-eu/products/productdetail?partno=PTGL13AR100H8B72B0

PTGL13AR100H8B72B0












Appearance & Shape







- 1. Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
- 2. Circuit is protected until current is turned off.
- 3. Restores the original low resistance value automatically once the overload is removed.
- 4. Non-contact design leads to long life and no noise.

 Durable and strong against mechanical vibration and shock because it is a solid element.



Limited Usage	Consumer Grade
Other Usage	Transformers Transistors Transistors Transistors



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	150

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. $\underline{ \text{Please download the latest datasheet of PTGL13AR100H8B72B0 from the official website of Murata} \\$

Manufacturing Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=PTGL13AR100H8B72B0

PTGL13AR100H8B72B0



Max. Voltage	265V
Hold Current	200mA
Measure Condition of Hold Current	(at +60°C)
Hold Current (2)	260mA
Measure Condition of Hold Current (2)	(at +25°C)
Trip Current	480mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	560mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	2.2A
Resistance (25°C)	10Ω
Resistance Value Tolerance (at 25°C)	±25%
Power Consumption(typ)	2.7W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	14mm
Thickness	6mm
F: Lead Space	7.5mm

d: Lead Diameter	0.6mm
Shape	Lead
Mass	2.11g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





URL: https://www.murata.com/

Last updated : 2019/04/21

PTGL13AR100H8B72B0








Resistance-Temperature Charac.





Operating Time (Typical Curve)

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/04/21