

Product Search Data Sheet


PTGL13AR3R7H4B71B0

Note: This datasheet may be out of date. <u>Please download the latest datasheet of PTGL13AR3R7H4B71B0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> https://www.murata.com/en-eu/products/productdetail?partno=PTGL13AR3R7H4B71B0



#### Appearance & Shape





(in mm)


od±0.05

# Applications

Limited Usage	Consumer Grade
Other Usage	1. Transformers 2. Transistors 3. Fluorescent Lamps

### Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	300



 Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
Circuit is protected until current is turned off.

3. Restores the original low resistance value automatically once the overload is removed.

4. Non-contact design leads to long life and no noise. Durable and strong against mechanical vibration and shock because it is a solid element.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



## PTGL13AR3R7H4B71B0

Note: This datasheet may be out of date. Please download the latest datasheet of PTGL13AR3R7H4B71B0 from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=PTGL13AR3R7H4B71B0

### Specifications

Max. Voltage	80V	d: Lead Diameter	0.6mm
Hold Current	310mA	Shape	Lead
Measure Condition of Hold Current	(at +60°C)	Mass	1.25g
Hold Current (2)	405mA		
Measure Condition of Hold Current (2)	(at +25°C)		
Trip Current	750mA		
Measure Condition of Trip Current	(at +25°C)		
Trip Current(2)	860mA		
Measure Condition of Trip Current(2)	(at -10°C)		
Max. Current	5.5A		
Resistance (25°C)	3.7Ω		
Resistance Value Tolerance (at 25°C)	±25%		
Power Consumption(typ)	2.3W		
Operating Temperature Range	-10℃ to 60℃		
D: Outer Dimension	13.5mm		
Thickness	4.5mm		
F: Lead Space	7.5mm		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




Product Search Data Sheet

# PTGL13AR3R7H4B71B0


Note: This datasheet may be out of date Please download the latest datasheet of PTGL13AR3R7H4B71B0 from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=PTGL13AR3R7H4B71B0




INNOVATOR IN ELECTRON



Resistance-Temperature Charac.



Protective Threshold Current Range



Operating Time (Typical Curve)

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

