

Product Search Data Sheet


PTGL18AR4R7M6B72B0

Note: This datasheet may be out of date. <u>Please download the latest datasheet of PTGL18AR4R7M6B72B0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> https://www.murata.com/en-eu/products/productdetail?partno=PTGL18AR4R7M6B72B0



Appearance & Shape







 Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
Circuit is protected until current is turned off.

3. Restores the original low resistance value automatically once the overload is removed.

4. Non-contact design leads to long life and no noise. Durable and strong against mechanical vibration and shock because it is a solid element.

Applications

Limited Usage	Consumer Grade
Other Usage	1. Transformers 2. Transistors 3. Fluorescent Lamps

Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	100

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

PTGL18AR4R7M6B72B0

Note: This datasheet may be out of date. Please download the latest datasheet of PTGL18AR4R7M6B72B0 from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=PTGL18AR4R7M6B72B0

Specifications

Max. Voltage	125V	d: Lead Diameter	0.6mm
Hold Current	360mA	Shape	Lead
Measure Condition of Hold Current	(at +60°C)	Mass	3.55g
Hold Current (2)	450mA		
Measure Condition of Hold Current (2)	(at +25℃)		
Trip Current	775mA		
Measure Condition of Trip Current	(at +25℃)		
Trip Current(2)	900mA		
Measure Condition of Trip Current(2)	(at -10°C)		
Max. Current	1.7A		
Resistance (25°C)	4.7Ω		
Resistance Value Tolerance (at 25°C)	±20%		
Power Consumption(typ)	3.1W		
Operating Temperature Range	-10°C to 60°C		
D: Outer Dimension	18.5mm		
Thickness	5.5mm		
F: Lead Space	7.5mm		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




Product Search Data Sheet


PTGL18AR4R7M6B72B0

Note: This datasheet may be out of date. <u>Please download the latest datasheet of PTGL18AR4R7M6B72B0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> https://www.murata.com/en-eu/products/productdetail?partno=PTGL18AR4R7M6B72B0






Resistance-Temperature Charac.



Protective Threshold Current Range



Operating Time (Typical Curve)

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.