

Note: This datasheet may be out of date.

Please download the latest datasheet of PTGL18AR6R8M6B72B0 from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-eu/products/productdetail?partno=PTGL18AR6R8M6B72B0

## PTGL18AR6R8M6B72B0










## Appearance & Shape







## Features

- 1. Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
- 2. Circuit is protected until current is turned off.
- 3. Restores the original low resistance value automatically once the overload is removed.
- 4. Non-contact design leads to long life and no noise. Durable and strong against mechanical vibration and shock because it is a solid element.



Limited Usage	Consumer Grade
Other Usage	Transformers Transistors Fluorescent Lamps



# Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	100

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.  $\underline{ \text{Please download the latest datasheet of PTGL18AR6R8M6B72B0 from the official website of Murata} \\$ 

Manufacturing Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=PTGL18AR6R8M6B72B0

# PTGL18AR6R8M6B72B0



Max. Voltage	125V
Hold Current	300mA
Measure Condition of Hold Current	(at +60°C)
Hold Current (2)	380mA
Measure Condition of Hold Current (2)	(at +25°C)
Trip Current	640mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	750mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	1.4A
Resistance (25°C)	6.8Ω
Resistance Value Tolerance (at 25°C)	±20%
Power Consumption(typ)	3W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	18.5mm
Thickness	5.5mm
F: Lead Space	7.5mm

d: Lead Diameter	0.6mm	
Shape	Lead	
Mass	3.55g	

2 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




URL: https://www.murata.com/


Last updated : 2019/04/21

Manufacturing Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=PTGL18AR6R8M6B72B0


# PTGL18AR6R8M6B72B0







Resistance-Temperature Charac.



Protective Threshold Current Range

Operating Time (Typical Curve)

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/04/21