

DC-DC CONVERTERS


Non-isolated DDR/QDR Memory Bus Termination Module

1

NEW Product



- V_{TT} bus termination output (output tracks the system V_{REF})
- 6 A output current (8 A Peak)
- 3.3 Vdc, 5 Vdc or 12 Vdc input voltage
- DDR and QDR compatible
- ON/OFF inhibit (for V_{TT} standby)
- Under-voltage lockout
- Operating temperature range: -40 °C to +85 °C
- Efficiencies up to 88%
- Output overcurrent protection (non-latching, auto-reset)
- Point-of-Load-Alliance (POLA) compatible
- Available RoHS compliant



2 YEAR WARRANTY

The PTHxx050Y are a new series of non-isolated dc-dc converters designed specifically for bus termination in DDR and QDR memory applications. Operating from either a 3.3 Vdc, 5 Vdc or 12 Vdc input, the modules generate a V_{TT} output that will source or sink up to 6 A of current to accurately track their V_{REF} input. V_{TT} is the required bus termination supply voltage, and V_{REF} is the reference voltage for the memory and chipset bus receiver comparators. V_{REF} is usually set to half the V_{DDQ} power supply voltage. The PTHxx050Y series employs an actively switched synchronous rectifier output to provide state of the art stepdown switching conversion. The products are small in size and are an ideal choice where space, performance and high efficiency are desired.

All specifications are typical at nominal input, $V_{REF} = 1.25$ V, full load at 25 °C unless otherwise stated. C_{in} , C_{o1} and C_{o2} = typical value

SPECIFICATIONS

OUTPUT SPECIFICATIONS

www.DataShe

Output current (over V_{REF} range)	All models Continuous (See Note 1) Repetitive pulse (See Note 2)	± 6 A ± 8 A
Tracking range for V_{REF}	0.55-1.8 V	
Tracking tolerance to V_{REF} ($V_{TT} - V_{REF}$) (over line, load and temperature)	-10 mV to +10mV	
Ripple and noise	20 MHz bandwidth	20 mV pk-pk
Load transient response (See Note 5)	80 μ s settling time Overshoot/undershoot 25 mV typ.	
Output capacitance: Non-ceramic values (See Notes 5 and 6)	PTH03050Y 470 μ F typ., 3,300 μ F max. PTH05050Y 470 μ F typ., 3,300 μ F max. PTH12050Y 940 μ F typ., 3,300 μ F max.	
Ceramic values (See Note 5)	PTH03050Y 200 μ F typ., 300 μ F max. PTH05050Y 200 μ F typ., 300 μ F max. PTH12050Y 400 μ F typ., 600 μ F max.	
(See Note 7)	ESR (non-ceramic)	4 m Ω min

INPUT SPECIFICATIONS

Input current	No load	10 mA
Input voltage range	PTH03050Y 2.95-3.65 Vdc PTH05050Y 4.5-5.5 Vdc PTH12050Y 10.8-13.2 Vdc	
Undervoltage lockout:		
PTH03050Y	Vin increasing 2.45 V typ., 2.80 V max. Vin decreasing 2.20 V min., 2.40 V typ.	
PTH05050Y	Vin increasing 4.30 V typ., 4.45 V max. Vin decreasing 3.40 V min., 3.70 V typ.	
PTH12050Y	Vin increasing 9.5 V typ., 10.4 V max. Vin decreasing 8.80 V min., 9.0 V typ.	

INPUT SPECIFICATIONS CONTD.

Input capacitance (See Note 4)	PTH03050Y and PTH05050Y 470 μ F PTH12050Y 560 μ F	
Remote ON/OFF	Active high	

GENERAL SPECIFICATIONS

Efficiency $I_o = 4$ A	PTH03050Y 88% typ. PTH05050Y 87% typ. PTH12050Y 84% typ.	
Insulation voltage	Non-isolated	
Switching frequency	PTH03050Y 550- 650 kHz PTH05050Y 550-650 kHz PTH12050Y 200-300 kHz	
Approvals and standards	EN60950 UL/cUL60950	
Material flammability	UL94V-0	
Dimensions	(L x W x H)	22.10 x 12.57 x 8.50 mm 0.870 x 0.495 x 0.335 in
Weight	2.9 g (0.10 oz)	
MTBF	Telcordia SR-332	6,000,000 hours

ENVIRONMENTAL SPECIFICATIONS


Thermal performance (See Note 2)	Operating ambient, temperature Non-operating	-40 °C to +85 °C -40 °C to +125 °C
MSL ('Z' suffix only)	JEDEC J-STD-020C Level 3	

PROTECTION

Overcurrent threshold (auto reset)	All models	12 A typ.
------------------------------------	------------	-----------

OUTPUT POWER (MAX.)	INPUT VOLTAGE	V _{TT} RANGE	OUTPUT CURRENT (MIN.)	OUTPUT CURRENT (MAX.)	EFFICIENCY (TYP.)	MODEL NUMBER ^(9,10)
10.8 W	2.95-3.65 Vdc	0.55-1.8Vdc	0 A	±6 A	88%	PTH03050Y
10.8 W	4.5-5.5 Vdc	0.55-1.8Vdc	0 A	±6 A	87%	PTH05050Y
10.8 W	10.8-13.2 Vdc	0.55-1.8Vdc	0 A	±6 A	84%	PTH12050Y

Part Number System with Options



Notes

- Rating is conditional on the module being directly soldered to a 4 layer PCB with 1 oz. copper. See the SOA curves or contact the factory for appropriate derating. The PTH03050Y and PTH05050Y require no derating up to 85 °C operating temperature and natural convection airflow.
- Up to 10 ms pulse period at 10% maximum duty.
- This control pin has an internal pull-up to the input voltage Vin. If it is left open-circuit the module will operate when input power is applied. A small low-leakage (<100 nA) MOSFET is recommended for control. For further information, consult Application Note 178.
- An input capacitor is required for proper operation. The capacitor must be rated for a minimum of 300 mA rms (750 mA rms for 12 V input) of ripple current.
- The typical value of external output capacitance value ensures that V_{TT} meets the specified transient performance requirements for the memory bus terminations. Lower values of capacitance may be possible when the measured peak change in output current is consistently less than 3 A. Test conditions were 15 A/μs load step, -1.5 A to +1.5 A.
- This is the calculated maximum. The minimum ESR limitation will often result in a lower value. Consult Application Note 178 for further details.
- This is the typical ESR for all the electrolytic (non-ceramic) output capacitance. Use 7 mΩ as the minimum when using max ESR values to calculate.
- Tape and reel packaging only available on the surface-mount versions.
- To order Pb-free (RoHS compatible) surface-mount parts replace the mounting option 'S' with 'Z', e.g. PTHxx050YAZ. To order Pb-free (RoHS compatible) through-hole parts replace the mounting option 'H' with 'D', e.g. PTHxx050YAD.
- NOTICE: Some models do not support all options. Please contact your local Artesyn representative or use the on-line model number search tool at <http://www.artesyn.com/powergroup/products.htm> to find a suitable alternative.

International Safety Standard Approvals



UL/cUL CAN/CSA-C22.2 No. 60950
File No. E174104



TÜV Product Service (EN60950) Certificate No. B 04 06 38572 044
CB Report and Certificate to IEC60950, Certificate No. US/8292/UL




Figure 1 - Safe Operating Area
 $V_{in} = 3.3\text{ V}$, $V_{REF} = 1.25\text{ V}$, $I_{out} = 6\text{ A}$ (See Note A)




Figure 2 - Safe Operating Area
 $V_{in} = 12\text{ V}$, $V_{REF} = 1.25\text{ V}$, $I_{out} = 6\text{ A}$ (See Note A)




Figure 3 - Efficiency vs Load Current
 $V_{REF} = 1.25\text{ V}$ (See Note B)




Figure 4 - Standard Application

Notes

- A The SOA curves represent the conditions at which internal components are within the Artesyn derating guidelines.
- B Characteristic data has been developed from actual products tested at 25 °C. This data is considered typical data for the converter.




Figure 5 - Plated Through-Hole Mechanical Drawing

PIN CONNECTIONS	
PIN NO.	FUNCTION
1	Ground
2	V_{REF}
3	V_{in}
4	Inhibit*
5	N/C
6	V_{TT}

*Denotes negative logic:
Open = Normal operation
Ground = Function active




Figure 6 - Surface-Mount Mechanical Drawing