

Indoor DC Power Cables

TelcoFlex® III meets or exceeds the following:

- UL Listed RHH/LS
- FT4 flame test
- VW-1
- ASTM B-33
- 600 Volts
- Physical and electrical tests in accordance with UL standard 44 requirements
- CSA AWM I B 105°C
- IEC 60674 and 60332
- RoHS / REACH compliant



SPECIFICATIONS

Wire Size (AWG)	# Strands	Insulation Minimum Average Wall	Nominal Insulation Diameter	Overall OD (inches)	Weight /feet	Max DC Res. @ 20°C (ohms/m ft)	Description	Part Number
1/0	19	80	0.53	0.606	0.441	0.106	1/0, Non-Hal, KS24194 L3 Type, Gray	PWR-1/0-24194-GY
2/0	19	80	0.575	0.651	0.537	0.084	2/0, Non-Hal, KS24194 L3 Type, Gray	PWR-2/0-24194-GY
2	7	60	0.41	0.482	0.278	0.169	2 AWG, Non-Hal, KS24194 L3 Type, Gray	PWR-2A-24194-GY
4	7	60	0.35	0.414	0.188	0.269	4 AWG, Non-Hal, KS24194 L3 Type, Gray	PWR-4A-24194-GY
6	7	60	0.305	0.37	0.132	0.427	6 AWG, Non-Hal, KS24194 L3 Type, Gray	PWR-6A-24194-GY
8	7	60	0.27	0.327	0.093	0.678	8 AWG, Non-Hal, KS24194 L3 Type, Gray	PWR-8A-24194-GY
10	7	45	0.21	0.272	0.063	1.080	10 AWG, Non-Hal, KS24194 L3 Type, Gray	PWR-10A-24194-GY

Also available in black, blue, green, red and with black tracer.

Available through



Division of RF Industries

(800) 233-1728

(858) 549-6340

www.rfindustries.com

rfi@rfindustries.com

and



Cables Unlimited
Division of RF Industries

(800) 590-9965

(631) 563-6363

www.cables-unlimited.com

quotes@cables-unlimited.com

Manufactured in the USA



RF Industries (NASDAQ: RFIL) 7610 Miramar Rd, San Diego, CA 92126
(858) 549-6340, (800) 233-1728, rfi@rfindustries.com, www.rfindustries.com

319090

Free Datasheet <http://www.datasheet4u.com/>