

Micro Commercial Components

Pb

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Features

- Halogen free available upon request by adding suffix "-HF"
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking:Y2/8550
- Capable of 0.5Watts(Tamb=25°C) of Power Dissipation.
- Collector-current 1.5Å
- Collector-base Voltage 40V
- Operating and storage junction temperature range: -55°C to +150°C

Electrical Characteristics @ 25°C Unless Otherwise Specified


Symbol	Parameter	Min	Max	Units
	CTERISTICS	1	<u>ı </u>	
V _{(BR)CBO}	Collector-Base Breakdown Voltage (lc=-100µAdc, lc=0)	-40		Vdc
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	-25		Vdc
V _{(BR)EBO}	Emitter-Base Breakdown Voltage (t=-100µAdc, tc=0)	-5.0		Vdc
I _{CBO}	Collector Cutoff Current (V _{CB} =-40Vdc,		-0.1	µAdc
Iceo	Collector Cutoff Current (V _{CE} =-20Vdc, J _B =0)		-0.1	µAdc
ЕВО	Emitter Cutoff Current (V _{EB} =-5.0Vdc, _b =0)		-0.1	µAdc
ON CHARAC	TERISTICS			
$h_{\text{FE}(1)}$	DC Current Gain (t=-100mAdc, V _{CE} =-1.0Vdc)	85	400	
$h_{\text{FE}(2)}$	DC Current Gain (t _c =-800mAdc, V _{ce} =-1.0Vdc)	40		
V _{CE(sat)}	Collector-Emitter Saturation Voltage (t_=-800mAdc, t_=-80mAdc)		-0.5	Vdc
$V_{\text{BE(sat)}}$	Base-Emitter Saturation Voltage (L=-800mAdc, L=-80mAdc)		-1.2	Vdc
V_{BEF}	Base- Emitter Positive Favor Voltage (l _b =-1.0Adc)		-1.55	Vdc
SMALL-SIG	NAL CHARACTERISTICS		•	
f _T	Transistor Frequency (_b =-50mAdc, V _{CE} =-10Vdc,)	100		MHz
C _{ob}	Output Capacitance (E=0,V _{CB} =-10Vdc,f=1MHz)		15	рF

CLASSIFICATION OF HEELD

Rank	В	С	D	D3			
Range	85-160	120-200	160-300	300-400			

PXT8550-B PXT8550-C PXT8550-D PXT8550-D3

PNP Silicon Plastic-Encapsulate Transistor





DIM	INCHES		MSINS MM		NOTES
	MIN	MAX	MIN	MAX	1
А	.173	.181	4.39	4.60	
В	.061		1.55		REF.
С	.154	.165	3.91	4.25	
D	.031	.039	0.80	1.00	
E	.092	.100	2.34	2.54	
F	.118		3.00		TYP
G	.013	.019	0.33	0.48	
Н	.015	.021	0.38	0.53	
J	.015	.016	0.38	0.41	
К	.055	.063	1.40	1.60	
IX.	.000		1.40	1.00	1

www.mccsemi.com



Ordering Information :

Device	Packing	
Part Number-TP	Tape&Reel: 1Kpcs/Reel	

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com