

QM2601S-VB Datasheet

N- and P-Channel 20-V (D-S) MOSFETS

PRODUCT SUMMARY



	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)	Q _g (Typ.)
N-Channel	20	0.006 at V _{GS} = 4.5 V	15 ^a	11 nC
		0.010 at V _{GS} = 2.5 V	12 ^a	
P-Channel	-20	0.016 at V _{GS} = -4.5 V	-8.5 ^a	25 nC
		0.020 at V _{GS} = -2.5 V	-7.0 ^a	

FEATURES

- Halogen-free
- TrenchFET[®] Power MOSFETs

APPLICATIONS

- Load Switch
- DC/DC Converter


RoHS
 COMPLIANT


ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted

Parameter	Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage	V _{DS}	20	-20	V
Gate-Source Voltage	V _{GS}	± 12		
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	15	-8.5	A
	T _C = 70 °C	12	-6.8	
	T _A = 25 °C	13 ^{b, c}	-7.0 ^{b, c}	
	T _A = 70 °C	11 ^{b, c}	-5.6 ^{b, c}	
Pulsed Drain Current	I _{DM}	30	-30	
Source Drain Current Diode Current	T _C = 25 °C	5.3	-4.4	
	T _A = 25 °C	3.9 ^{b, c}	-2.9 ^{b, c}	
Maximum Power Dissipation	T _C = 25 °C	3.1	3.2	W
	T _C = 70 °C	2.1	2.2	
	T _A = 25 °C	2.1 ^{b, c}	2.2 ^{b, c}	
	T _A = 70 °C	1.7 ^{b, c}	1.76 ^{b, c}	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-55 to 150		°C

THERMAL RESISTANCE RATINGS

Parameter		Symbol	N-Channel		P-Channel		Unit
			Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^{b, d}	t ≤ 10 s	R _{thJA}	85	110	81	105	°C/W
Maximum Junction-to-Foot (Drain)	Steady State	R _{thJF}	62	80	57	75	

Notes:

 a. T_C = 25 °C.

b. Surface Mounted on 1" x 1" FR4 board.

c. t = 10 s.

d. Maximum under Steady State conditions is 145 °C/W.

SPECIFICATIONS T _J = 25 °C, unless otherwise noted								
Parameter	Symbol	Test Conditions		Min.	Typ.	Max.	Unit	
Static								
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	N-Ch	20			V	
		V _{GS} = 0 V, I _D = - 250 μA	P-Ch	- 20				
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA	N-Ch		22		mV/°C	
		I _D = - 250 μA	P-Ch		- 21			
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J	I _D = 250 μA	N-Ch		- 3.5			
		I _D = - 250 μA	P-Ch		3.5			
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	N-Ch	0.6		1.5	V	
		V _{DS} = V _{GS} , I _D = - 250 μA	P-Ch	- 0.6		- 1.5		
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 12 V	N-Ch			± 100	nA	
			P-Ch			± 100		
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V	N-Ch			1	μA	
		V _{DS} = - 20 V, V _{GS} = 0 V	P-Ch			- 1		
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55 °C	N-Ch			10		
		V _{DS} = - 20 V, V _{GS} = 0 V, T _J = 55 °C	P-Ch			- 10		
On-State Drain Current ^b	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 4.5 V	N-Ch	30			A	
		V _{DS} ≤ - 5 V, V _{GS} = - 4.5 V	P-Ch	- 30				
Drain-Source On-State Resistance ^b	R _{DS(on)}	V _{GS} = 4.5 V, I _D = 5.7 A	N-Ch		0.006		Ω	
		V _{GS} = - 4.5 V, I _D = - 5.1 A	P-Ch		0.016			
		V _{GS} = 2.5 V, I _D = 4.4 A	N-Ch		0.010			
		V _{GS} = - 2.5 V, I _D = - 4.2 A	P-Ch		0.020			
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 5.7 A	N-Ch		17		S	
		V _{DS} = - 10 V, I _D = - 5.1 A	P-Ch		22			
Dynamic ^a								
Input Capacitance	C _{iss}	N-Channel V _{DS} = 10 V, V _{GS} = 0 V, f = 1 MHz	N-Ch		1250		pF	
			P-Ch		1600			
Output Capacitance	C _{oss}	P-Channel V _{DS} = - 10 V, V _{GS} = 0 V, f = 1 MHz	N-Ch		180			
			P-Ch		280			
Reverse Transfer Capacitance	C _{rss}		N-Ch		100			
			P-Ch		65			
Total Gate Charge	Q _g	V _{DS} = 10 V, V _{GS} = 10 V, I _D = 5.7 A	N-Ch		23	35	nC	
		V _{DS} = - 10 V, V _{GS} = - 10 V, I _D = - 5.1 A	P-Ch		44	61		
		N-Channel V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 5.7 A	N-Ch		11	20		
			P-Ch		25	35		
Gate-Source Charge	Q _{gs}	P-Channel V _{DS} = - 10 V, V _{GS} = - 4.5 V, I _D = - 5.1 A	N-Ch		1.8			
			P-Ch		3			
Gate-Drain Charge	Q _{gd}		N-Ch		0.9			
			P-Ch		5.5			
Gate Resistance	R _g	f = 1 MHz	N-Ch		2		Ω	
			P-Ch		6			

Notes:

a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.

SPECIFICATIONS $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise noted							
Parameter	Symbol	Test Conditions		Min.	Typ.	Max.	Unit
Dynamic ^a							
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 10\text{ V}, R_L = 2.2\text{ }\Omega$ $I_D \cong 4.5\text{ A}, V_{GEN} = 4.5\text{ V}, R_g = 1\text{ }\Omega$ P-Channel $V_{DD} = -10\text{ V}, R_L = 2.4\text{ }\Omega$ $I_D \cong -4.1\text{ A}, V_{GEN} = -4.5\text{ V}, R_g = 1\text{ }\Omega$	N-Ch		12	20	ns
			P-Ch		30	45	
Rise Time	t_r		N-Ch		10	15	
			P-Ch		25	40	
Turn-Off Delay Time	$t_{d(off)}$		N-Ch		25	40	
			P-Ch		45	70	
Fall Time	t_f		N-Ch		10	15	
			P-Ch		15	25	
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 10\text{ V}, R_L = 2.2\text{ }\Omega$ $I_D \cong 4.5\text{ A}, V_{GEN} = 10\text{ V}, R_g = 1\text{ }\Omega$ P-Channel $V_{DD} = -10\text{ V}, R_L = 2.4\text{ }\Omega$ $I_D \cong -4.1\text{ A}, V_{GEN} = -10\text{ V}, R_g = 1\text{ }\Omega$	N-Ch		10	15	ns
			P-Ch		10	15	
Rise Time	t_r		N-Ch		10	15	
			P-Ch		10	15	
Turn-Off Delay Time	$t_{d(off)}$		N-Ch		20	30	
			P-Ch		45	70	
Fall Time	t_f		N-Ch		8	15	
			P-Ch		15	25	
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I_S	$T_C = 25\text{ }^{\circ}\text{C}$	N-Ch			1.3	A
			P-Ch			- 1.4	
Pulse Diode Forward Current ^a	I_{SM}		N-Ch			30	
			P-Ch			- 30	
Body Diode Voltage	V_{SD}	$I_S = 4.5\text{ A}, V_{GS} = 0\text{ V}$	N-Ch		0.8	1.2	V
		$I_S = -4.1\text{ A}, V_{GS} = 0\text{ V}$	P-Ch		- 0.8	- 1.2	
Body Diode Reverse Recovery Time	t_{rr}	N-Channel $I_F = 4.5\text{ A}, di/dt = 100\text{ A}/\mu\text{s}, T_J = 25\text{ }^{\circ}\text{C}$ P-Channel $I_F = -4.1\text{ A}, di/dt = -100\text{ A}/\mu\text{s}, T_J = 25\text{ }^{\circ}\text{C}$	N-Ch		15	30	ns
			P-Ch		35	55	
Body Diode Reverse Recovery Charge	Q_{rr}		N-Ch		6	12	nC
			P-Ch		21	35	
Reverse Recovery Fall Time	t_a		N-Ch		7.6		ns
			P-Ch		18		
Reverse Recovery Rise Time	t_b		N-Ch		7.4		
			P-Ch		17		


Notes:

a. Guaranteed by design, not subject to production testing.


b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance




Gate Charge




On-Resistance vs. Junction Temperature


N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage





Single Pulse Power



* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified


Safe Operating Area, Junction-to-Ambient

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




* The power dissipation P_D is based on $T_{J(max)} = 150\text{ °C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Foot


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance




Gate Charge




On-Resistance vs. Junction Temperature


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source



Threshold Voltage





Single Pulse Power



* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified


Safe Operating Area, Junction-to-Ambient

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Foot

SOIC (NARROW): 8-LEAD
JEDEC Part Number: MS-012



DIM	MILLIMETERS		INCHES	
	Min	Max	Min	Max
A	1.35	1.75	0.053	0.069
A ₁	0.10	0.20	0.004	0.008
B	0.35	0.51	0.014	0.020
C	0.19	0.25	0.0075	0.010
D	4.80	5.00	0.189	0.196
E	3.80	4.00	0.150	0.157
e	1.27 BSC		0.050 BSC	
H	5.80	6.20	0.228	0.244
h	0.25	0.50	0.010	0.020
L	0.50	0.93	0.020	0.037
q	0°	8°	0°	8°
S	0.44	0.64	0.018	0.026
ECN: C-06527-Rev. I, 11-Sep-06 DWG: 5498				

RECOMMENDED MINIMUM PADS FOR SO-8



Recommended Minimum Pads
Dimensions in Inches/(mm)

Disclaimer

All products due to improve reliability, function or design or for other reasons, product specifications and data are subject to change without notice.

Taiwan VBsemi Electronics Co., Ltd., branches, agents, employees, and all persons acting on its or their representatives (collectively, the "Taiwan VBsemi"), assumes no responsibility for any errors, inaccuracies or incomplete data contained in the table or any other any disclosure of any information related to the product.(www.VBsemi.com)

Taiwan VBsemi makes no guarantee, representation or warranty on the product for any particular purpose of any goods or continuous production. To the maximum extent permitted by applicable law on Taiwan VBsemi relinquished: (1) any application and all liability arising out of or use of any products; (2) any and all liability, including but not limited to special, consequential damages or incidental ; (3) any and all implied warranties, including a particular purpose, non-infringement and merchantability guarantee.

Statement on certain types of applications are based on knowledge of the product is often used in a typical application of the general product VBsemi Taiwan demand that the Taiwan VBsemi of. Statement on whether the product is suitable for a particular application is non-binding. It is the customer's responsibility to verify specific product features in the products described in the specification is appropriate for use in a particular application. Parameter data sheets and technical specifications can be provided may vary depending on the application and performance over time. All operating parameters, including typical parameters must be made by customer's technical experts validated for each customer application. Product specifications do not expand or modify Taiwan VBsemi purchasing terms and conditions, including but not limited to warranty herein.

Unless expressly stated in writing, Taiwan VBsemi products are not intended for use in medical, life saving, or life sustaining applications or any other application. Wherein VBsemi product failure could lead to personal injury or death, use or sale of products used in Taiwan VBsemi such applications using client did not express their own risk. Contact your authorized Taiwan VBsemi people who are related to product design applications and other terms and conditions in writing.

The information provided in this document and the company's products without a license, express or implied, by estoppel or otherwise, to any intellectual property rights granted to the VBsemi act or document. Product names and trademarks referred to herein are trademarks of their respective representatives will be all.

Material Category Policy

Taiwan VBsemi Electronics Co., Ltd., hereby certify that all of the products are determined to be oHS compliant and meets the definition of restrictions under Directive of the European Parliament 2011/65 / EU, 2011 Nian. 6. 8 Ri Yue restrict the use of certain hazardous substances in electrical and electronic equipment (EEE) - modification, unless otherwise specified as inconsistent.(www.VBsemi.com)

Please note that some documents may still refer to Taiwan VBsemi RoHS Directive 2002/95 / EC. We confirm that all products identified as consistent with the Directive 2002/95 / EC European Directive 2011/65 /.

Taiwan VBsemi Electronics Co., Ltd. hereby certify that all of its products comply identified as halogen-free halogen-free standards required by the JEDEC JS709A. Please note that some Taiwanese VBsemi documents still refer to the definition of IEC 61249-2-21, and we are sure that all products conform to confirm compliance with IEC 61249-2-21 standard level JS709A.