


# RG2A THRU RG2M

## GLASS PASSIVATED FAST SWITCHING RECTIFIER

Reverse Voltage - 50 to 1000 Volts Forward Current - 2.0 Amperes

**PATENTED\***



Dimensions in inches and (millimeters)

\* Brazed-lead assembly is covered by Patent No. 3,930,306

### FEATURES

- ◆ High temperature metallurgically bonded construction
- ◆ Hermetically sealed package
- ◆ Glass passivated cavity-free junction
- ◆ 1.0 Ampere operation at  $T_A=55^\circ\text{C}$  with no thermal runaway
- ◆ Typical  $I_R$  less than  $0.1\mu\text{A}$
- ◆ Capable of meeting environmental standards of MIL-STD-19500
- ◆ Fast switching for high efficiency
- ◆ High temperature soldering guaranteed:  $350^\circ\text{C}/10$  seconds  $0.375''$  (9.5mm) lead length, 5 lbs. (2.3kg) tension



### MECHANICAL DATA

**Case:** JEDEC DO-204AP solid glass body

**Terminals:** Solder plated axial leads, solderable per MIL-STD-750, Method 2026

**Polarity:** Color band denotes cathode end

**Mounting Position:** Any

**Weight:** 0.02 ounce, 0.56 gram

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at  $25^\circ\text{C}$  ambient temperature unless otherwise specified.

	SYMBOLS	RG2A	RG2B	RG2D	RG2G	RG2J	RG2K	RG2M	UNITS
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified current $0.375''$ (9.5mm) lead lengths at $T_A=55^\circ\text{C}$	$I_{(AV)}$	2.0							Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	50.0							Amps
Maximum instantaneous forward voltage at 2.0A	$V_F$	1.3							Volts
Maximum full load reverse current, full cycle average $0.375''$ (9.5mm) lead length at $T_A=25^\circ\text{C}$ $T_A=100^\circ\text{C}$	$I_{R(AV)}$	1.0 100.0							$\mu\text{A}$
Maximum DC reverse current at rated DC blocking voltage	$I_R$	5.0							$\mu\text{A}$
Maximum reverse recovery time (NOTE 1)	$t_{rr}$	150				200	250	500	ns
Typical junction capacitance (NOTE 2)	$C_J$	15.0							pF
Typical thermal resistance (NOTE 3)	$R_{\theta JA}$	55.0							$^\circ\text{C}/\text{W}$
Operating junction and storage temperature range	$T_J, T_{STG}$	-65 to +175							$^\circ\text{C}$

#### NOTES:

(1) Measured with  $I_F=0.5\text{A}$ ,  $I_R=1.0\text{A}$ ,  $I_{rr}=0.25\text{A}$

(2) Measured at 1.0 MHz and applied reverse voltage of 4.0 V<sub>DC</sub>

(3) Thermal resistance from junction to ambient at  $0.375''$  (9.5mm) lead length, P.C.B. mounted

# RATINGS AND CHARACTERISTIC CURVES RG2A AND RG2M

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE

