



SPECIFICATIONS

Model Number	RJ4C
Test Voltage (kV Peak) 60 Hz	18
Rated Operating Voltage (kV Peak)	
DC or 60 Hz	15
2.5 MHz	12
16 MHz	10
32 MHz	7
Continuous Current, Carry (Amps, RMS)	
DC or 60 Hz	50
2.5 MHz	30
16 MHz	17.5
32 MHz	10
Contact Capacitance (pF)	
Between Open Contacts	.5
Open Contacts to Ground	1
Contact Resistance (mΩ)	12
Operate Time (ms. Max.)	18
Release Time (ms. Max.)	9
Pull-in Voltage @ 25° C, 26.5 VDC Coil	14
Dropout Voltage @ -55 to 125° C, 26.5 VDC Coil	1-10
Coil Resistance (Ohms ± 10%) 26.5 VDC Coil	270
Shock, 1/2 Sine 11 ms. (Peak g's)	30
Vibration, Peak g's	
55-500 Hz	10
55-1000 Hz	-
55-2000 Hz	-
Expected Mechanical Life Cycles (X10 ⁶)	1
Weight, Ounces (Grams) Max.	3 (85)



- **RJ4C-26S**
Flange mount. High voltage version of RJ4B. (Flange not shown in photo).

