



SURFACE MOUNT FAST RECOVERY RECTIFIER

RS3A THRU RS3M


VOLTAGE RANGE	50 to 1000 Volts
CURRENT	3.0 Ampere

FEATURES

- Glass Passivated chip junction
- Built-in strain relief
- Fast switching speed for high efficiency
- High temperature soldering guaranteed:
250°C/10 second at terminals

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL 94V-0 rate flame retardant
- Lead: Solder plated, solderable per MIL-STD-202E method208C
- Polarity: Color band denotes cathode end
- Weight: 0.007ounce, 0.25 gram-DO-214AB (SMC)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified.
- Single phase, half wave, 60Hz, resistive or inductive load.
- For capacitive load derate current by 20%.

		SYMBOLS	RS3A	RS3B	RS3D	RS3G	RS3J	RS3K	RS3M	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage		V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage		V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current at T _L =100℃		I _(AV)	3.0							Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC Method)		I _{FSM}	100							Amps
Maximum Instantaneous Forward Voltage at 3.0A		V _F	1.3							Volts
Maximum DC Reverse Current at rated DC blocking voltage at	T _A = 25℃	I _R	10.0							μA
	T _A = 125℃		250							
Typical Reverse Recovery Time Test conditions I _F =0.5A, I _R =1.0A, I _{RR} =0.25A		T _{rr}	150				250	500		ns
Typical Junction Capacitance (NOTE 2)		C _J	60							pF
Typical Thermal Resistance (NOTE 1)		R _{θJA}	50							℃/W
		R _{θJL}	15							
Operating Junction Temperature Range		T _J	-55 to +150							℃
Storage Temperature Range		T _{STG}	-55 to +150							℃

Notes:

1. Thermal resistance from Junction to ambient and from junction to lead mounted on PCB with 0.3×0.3" (8.0 × 8.0mm) copper pad areas.
2. Measured at 1.0MHz and applied reverse voltage of 4.0 Volts



SURFACE MOUNT FAST RECOVERY RECTIFIER

RS3A THRU RS3M

VOLTAGE RANGE


50 to 1000 Volts

CURRENT


3.0 Ampere

RATINGS AND CHARACTERISTIC CURVES RS3A THRU RS3M


F1G.1-FORWARD CURRENT
DERATING CURVE




F1G.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT




F1G.3-TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS



F1G.4-TYPICAL REVERSE
CHARACTERISTICS



F1G.5-TYPICAL JUNCTION CAPACITANCE



F1G.6-TRANSIENT THERMAL IMPEDANCE

