


RT320240B


SHENZHEN RUIE ELECTRONIC CO.,LTD
Address: 深圳市宝安区79区西乡流塘107国道1-3栋7、8楼
Tel: 86-755-27931867, 27931884, 27931806, 27931875
FAX: 86-755-27931864
E-Mail: rt@ruitelcd.com
Postcode: 518102
Http://www.ruitelcd.com




MECHANICAL DATA		
Item	Nominal Dimensions	Unit
Module Size(W×H×T)	139.0×114.5×13.0	mm
Viewing Area(W×H)	103.0×79.0	mm
Dot Pitch(W×H)	0.30×0.30	mm
Dot Size(W×H)	0.27×0.27	mm

ABSOLUTE MAXIMUM RATINGS					
Item	Symbol	Min	Type	Max	Unit
Operating Voltage	VDD	4.5	5.0	5.5	V
Operating Current	IDD	41	40	39	mA
LED Voltage	V _{LED}	4.5	5.0	5.5	V
LED Current	I _{LED}	49	64	81	mA
Operating Temp.	T _{opr}	-20	—	+70	°C
Storage Temp.	T _{sto}	-30	—	+80	°C

ELECTRICAL CHARACTERISTICS					
Item	Symbol	Min	Type	Max	Unit
Input Hight Voltage	V _{IH}	0.8VDD	—	VDD	V
Input Low Voltage	V _{IL}	0	—	0.2VDD	V
Output Hight Voltage	V _{OH}	VDD-0.4	—	VDD	V
Output Low Voltage	V _{OL}	0	—	0.4	V




PIN CONNECTIONS			
PIN	Symbol	Level	Function
1	VSS	—	GND(0V)
2	VDD	—	Supply Voltage for Logic(+5V)
3	V0	—	Power Supply for LCD
4	/WR	L	Command and data write signal
5	/RD	L	Data and status read signal
6	/CS	L	Chip Select signal
7	A0	H/L	Data type select
8	RES	L	Reset Signal (Active LOW)
9	DB0	H/L	Data Bus Line
10	DB1	H/L	
11	DB2	H/L	
12	DB3	H/L	
13	DB4	H/L	
14	DB5	H/L	
15	DB6	H/L	
16	DB7	H/L	
17	NC	—	NO Connect
18	VOUT	—	Negative Voltage to LCD
19	LEDA	—	Backlight Power (+5V)
20	LEDK	—	Backlight Power (0V)



RT320240B

SHENZHEN RUIITE ELECTRONIC CO.,LTD
Address: 深圳市宝安区79区西乡流塘107国道1-3栋7、8楼
Tel: 86-755-27931867, 27931884, 27931806, 27931875
FAX: 86-755-27931864
E-Mail: rt@ruitelcd.com
Postcode: 518102
[Http://www.ruitelcd.com](http://www.ruitelcd.com)



MECHANICAL DATA

Item	Nominal Dimensions	Unit
Module Size(W×H×T)	139.0×114.5×13.0	mm
Viewing Area(W×H)	103.0×79.0	mm
Dot Pitch(W×H)	0.30×0.30	mm
Dot Size(W×H)	0.27×0.27	mm


ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Min	Type	Max	Unit
Operating Voltage	VDD	4.5	5.0	5.5	V
Operating Current	IDD	41	40	39	mA
LED Voltage	V _{LED}	4.5	5.0	5.5	V
LED Current	I _{LED}	49	64	81	mA
Operating Temp.	T _{opr}	-20	—	+70	°C
Storage Temp.	T _{sto}	-30	—	+80	°C

ELECTRICAL CHARACTERISTICS

Item	Symbol	Min	Type	Max	Unit
Input Hight Voltage	V _{IH}	0.8VDD	—	VDD	V
Input Low Voltage	V _{IL}	0	—	0.2VDD	V
Output Hight Voltage	V _{OH}	VDD-0.4	—	VDD	V
Output Low Voltage	V _{OL}	0	—	0.4	V

BLOCK DIAGRAM



PIN CONNECTIONS (No Controller)

PIN	Symbol	Level	Function
1	FRAM	H/L	Frame signal
2	LP	H/L	Data latch signal
3	CP	H/L	Clock pulse input
4	M	H/L	Alternater for LCD driver
5	V0	—	Power Supply for LCD
6	VDD	—	Supply Voltage for Logic(+5V)
7	VSS	—	GND(0V)
8	VEE	—	Negative Voltage to LCD
9	D0	H/L	Data Bus Line
10	D1	H/L	
11	D2	H/L	
12	D3	H/L	H:Display ON; L:Display OFF
13	Disp Off	H/L	
14	NC	—	NO Connect
15	NC	—	NO Connect
16	NC	—	NO Connect
17	NC	—	NO Connect
18	NC	—	NO Connect
19	LEDA	—	Backlight Power (+5V)
20	LEDK	—	Backlight Power (0V)

POWER SUPPLY

