

PLUG-IN RELAY 2CO RELAY 15MM, 230V AC



General technical details:

Supply voltage frequency / for auxiliary and control current circuit / rated value

- minimum
- maximum

Hz 50  
Hz 60

type of voltage

AC

Control supply voltage

- at 50 Hz / at AC / rated value
  - minimum
  - maximum
- at 60 Hz / at AC / rated value
  - minimum
  - maximum

V 230  
V 230  
  
V 230  
V 230

Number of NC contacts

- for auxiliary contacts

0

Number of NO contacts

- for auxiliary contacts

0

Number of change-over switches

- for auxiliary contacts

2

Operating current / of the auxiliary contacts

- at AC-15

• at 230 V	A	2.5
<b>Design of the switching function</b>		changeover switch
• guided		No
<b>Switching behaviour</b>		monostable

#### Mechanical design:

<b>Design of the electrical connection</b>		screw-type terminals
<b>Design of the relay operating mechanism</b>		poled
<b>Product component / jumper socket</b>		No
<b>Width</b>	mm	12.7
<b>Height</b>	mm	12.7
<b>Depth</b>	mm	19.5

#### Certificates/approvals:

General Product Approval

other



GOST



UR

[Declaration of  
Conformity](#)

#### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/LZX:RT424730/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=LZX:RT424730](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:RT424730)

**last change:**

Feb 4, 2013