

S102T01/S102T02 S202T01/S202T02

Low Height Type Solid State Relays

■ Features

1. Low height type (height : 16 mm)
30% less compared with S101S05V
2. Effective ON-state current I_T : MAX. 2Ams ($T_a = 40^\circ\text{C}$)
3. Model Line-ups

	No zero cross circuit	Built-in zero cross circuit
AC100V	S102T01	S102T02
AC200V	S202T01	S202T02


4. Recognized by UL, file No. E94758

Approved by CSA, No. LR63705

■ Applications


1. Programmable controllers
2. Air conditioners
3. Copiers
4. Automatic vending machines

■ Outline Dimensions




Internal Connection Diagram

S102T01/S202T01



- ① Output (Triac T1)
- ② Output (Triac T2)
- ③ Input (+)
- ④ Input (-)

S102T02/S202T02



■ Absolute Maximum ratings

($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Rating		Unit
		S102T01 / S102T02	S202T01 / S202T02	
Input	I_F	50		mA
	V_R	6		V
Output	I_T	2		A_{rms}
	I_{surge}	20		A
	V_{DRM}	400	600	V
	V_{DSM}	400	600	V
	dI_T/dt	40		$\text{A}/\mu\text{s}$
Operating frequency	f	45 to 65		Hz
Operating temperature	T_{opr}	-25 to +100		$^\circ\text{C}$
Storage temperature	T_{stg}	-30 to +125		$^\circ\text{C}$
³ Isolation voltage	V_{iso}	3 000		V_{rms}
Soldering temperature	T_{sol}	260 (For 10 seconds)		$^\circ\text{C}$

¹ Refer to Fig. 1. ² 60Hz sine wave, start at $T_j=25^\circ\text{C}$

³ Isolation voltage test method

1) Use a dielectric withstand voltage tester with zero cross circuit.

2) The applied voltage waveform shall be sine wave.

3) Apply voltage between input and output. (Input and output terminals shall be shorted respectively.)


■ Electro-optical Characteristics

(Ta=25°C)

Parameter		Symbol	Conditions	MIN.	TYPE.	MAX.	Unit
Input	Forward voltage	V _F	I _F = 20mA	-	1.2	1.4	V
	Reverse current	I _R	V _R = 3V	-	-	1 x 10 ⁻⁴	A
Output	Repetitive peak OFF-state current	I _{DRM}	V _D = V _{DRM}	-	-	1 x 10 ⁻⁴	A
	ON-state voltage	V _T	I _T = 2A _{rms} Load resistance, I _F = 20mA	-	-	1.7	V _{rms}
	Holding current	I _H	-	-	-	25	mA
	Critical rate of rise of OFF-state voltage	dV/dt	V _D = 2/3V _{DRM}	30	-	-	V/μs
Transfer characteristics	Critical rate of rise of OFF-state voltage at commutation	(dV/dt) _C	T _j = 125°C, V _D = 400V dI _t /dt = -1.0A/ms	4	-	-	V/μs
	Minimum trigger current	I _{FT}	*4	-	-	8	mA
	Zero cross voltage	V _{OX}	I _F = 8mA	-	-	35	V
	Insulation resistance	R _{ISO}	DC500V, 40 to 60% RH	1 x 10 ¹⁰	-	-	Ω
	Turn-on time	t _{on}	S102T01/S202T01	-	-	1	ms
			S102T02/S202T02	-	-	10	
	Turn-off time	t _{off}	AC50Hz	-	-	10	ms

*4 S102T01/S202T01 V_D=12V,R_L=30 ΩS102T02/S202T02 V_D=6V,R_L=30 Ω

**Fig. 1 Effective On-state current vs.
Ambient Temperature**



- Please refer to the chapter "Precautions for Use". (Page 78 to 93)