

SHINDENGEN

Schottky Rectifiers (SBD)

Dual

S20SC4M

40V 20A

FEATURES

T_j150

P_{RRSM} avalanche guaranteed

Small j_c

High current capacity

APPLICATION

Switching power supply

DC/DC converter


Home Appliances, Office Equipment

Telecommunication

OUTLINE DIMENSIONS

Case : MTO-3P

Unit : mm



RATINGS

Absolute Maximum Ratings (If not specified T_c=25)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T _{stg}		-40 ~ 150	
Operating Junction Temperature	T _j		150	
Maximum Reverse Voltage	V _{RM}		40	V
Repetitive Peak Surge Reverse Voltage	V _{RRSM}	Pulse width 0.5ms, duty 1/40	45	V
Average Rectified Forward Current	I _o	50Hz sine wave, R-load, Rating for each diode I _o /2, T _c =125	20	A
Peak Surge Forward Current	I _{FSM}	50Hz sine wave, Non-repetitive 1 cycle peak value, T _j =125	170	A
Repetitive Peak Surge Reverse Power	P _{RRSM}	Pulse width 10 μs, Rating of per diode, T _j =25	660	W
Mounting Torque	T _{OR}	(Recommended torque 0.5N·m)	0.8	N·m


Electrical Characteristics (If not specified T_c=25)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V _{F2}	I _F =10A, Pulse measurement, Rating of per diode	Max.0.59	V
Reverse Current	I _R	V _R =V _{RM} , Pulse measurement, Rating of per diode	Max.5	mA
Junction Capacitance	C _j	f=1MHz, V _R =10V, Rating of per diode	Typ.340	pF
Thermal Resistance	j _c	junction to case	Max.1.2	/W

S20SC4M


Forward Voltage







S20SC4M



Reverse Current





S20SC4M Reverse Power Dissipation




S20SC4M Forward Power Dissipation





S20SC4M Peak Surge Forward Capability



SBD Repetitive Surge Reverse Power Derating Curve



SBD Repetitive Surge Reverse Power Capability

