





Features

- $V_{DS}=70V, I_D=57A$
- $R_{ds(on)}(typ)=11.5m\Omega @ V_{gs}=10V$
- 100% Avalanche Tested
- 100% R_g Tested
- Lead-Free (RoHS Compliant)


Applications

- DC Motor Control
- DC-DC Converters
- BMS
- SMPS
- Automotive Environment

Internal Circuit and Pin Description

				
Package	TO-220	TO-263	TO-220N	TO-220P
Package Code	R	S	RN	RP

Package Marking



- Company
- Part No. and Package Code
- Assembly Information
- Lot No.

Absolute Maximum Ratings ($T_c=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Value	Units
V_{DSS}	Drain-Source Voltage	70	V
I_D	Continuous Drain Current ($T_c=25^\circ C$)	57	A
	Continuous Drain Current ($T_c=100^\circ C$)	36	A
I_{DM}	Pulsed Drain Current (Note 1)	228	A
V_{GS}	Gate-Source Voltage	± 25	V
E_{AS}	Single Pulsed Avalanche Energy (Note 2)	121	mJ
P_D	Maximum Power Dissipation ($T_c=25^\circ C$)	88	W
	Derating Factor above $25^\circ C$	0.704	W/ $^\circ C$
T_J	Operating Junction Temperature Range	-55 to +150	$^\circ C$
T_{STG}	Storage Temperature Range	-55 to +150	$^\circ C$

Thermal Characteristics

Symbol	Parameter	Value	Units
R _{th j-c}	Thermal Resistance, Junction to case	1.41	°C/W

Electrical Characteristics ($T_c=25^\circ\text{C}$ unless otherwise noted)







Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	70	-	-	V
I _{DSS}	Drain-Source Leakage Current	V _{DS} =66.5V, V _{GS} =0V	-	-	1	μA
I _{GSS}	Gate Leakage Current, Forward	V _{GS} =25V, V _{DS} =0V	-	-	100	nA
	Gate Leakage Current, Reverse	V _{GS} =-25V, V _{DS} =0V	-	-	-100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250μA	2.4	3	3.6	V
R _{D(on)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =40A	9.2	11.5	13.2	mΩ
Q _g	Total Gate Charge	V _{DD} =48V V _{GS} =10V I _D =50A (Note 3)	-	45	-	nC
Q _{gs}	Gate-Source Charge		-	12	-	nC
Q _{gd}	Gate-Drain Charge		-	15	-	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =37.5V, V _{GS} =10V I _D =45A, R _G =4.7Ω T _c =25°C (Note 3)	-	22	-	ns
t _r	Turn-on Rise Time		-	12	-	ns
t _{d(off)}	Turn-off Delay Time		-	25	-	ns
t _f	Turn-off Fall Time		-	32	-	ns
R _g	Gate Resistance	V _{DS} =0V, V _{GS} =0V, f=1MHz	-	1.3	-	Ω
C _{iss}	Input Capacitance	V _{DS} =25V V _{GS} =0V f = 1MHz	-	2209	-	pF
C _{oss}	Output Capacitance		-	198	-	pF
C _{rss}	Reverse Transfer Capacitance		-	156	-	pF







Source-Drain Diode Characteristics ($T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
I _s	Continuous Source Diode Forward Current	-	-	57	A	
I _{SM}	Pulsed Source Diode Forward Current (Note 1)	-	-	228	A	
V _{SD}	Forward On Voltage	V _{GS} =0V, I _s =45A	-	0.9	1	V
t _{rr}	Reverse Recovery Time	V _{GS} =0V, I _s =45A dI _F /dt = 100A/us	-	28	-	ns
			-	51	-	nC



Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. L=0.5mH, V_{DD}=64V, R_G=25Ω, Starting T_J=25°C
3. Pulse Width ≤ 300 us; Duty Cycle≤2%



Typical Characteristics





Gate Charge Test Circuit and Waveforms



Switching Time Test Circuit & Waveforms




Avalanche Test Circuit & Waveforms





Package Outline

TO220




SYMBOL	MIN	NOM	MAX
A	4.47	4.57	4.67
A1	1.27	1.30	1.33
A2	2.35	2.40	2.45
b	0.76	0.80	0.89
b2	1.23	1.27	1.38
c	0.47	0.50	0.53
D	15.60	15.70	15.80
D1	9.10	9.20	9.30
E	9.70	9.90	10.10
E1	-	8.70	-
e	2.54 BSC		
e1	5.08 BSC		
L	12.83	13.00	13.17
L1	3.00	3.10	3.20
P	3.57	3.60	3.63
Q	2.75	2.80	2.85
θ1	5°	7°	9°
θ2	1°	3°	5°
θ3	1°	3°	5°

TO263



UNIT:mm



SYMBOL	MIN	NOM	MAX
A	4.47	4.57	4.67
A1	1.25	1.30	1.35
A2	2.34	2.40	2.46
b	1.22	1.27	1.32
b1	0.75	0.80	0.85
c	0.45	0.50	0.55
E	9.90	10.00	10.10
E1	9.78	9.88	9.98
E2	7.95	8.00	8.05
E3	1.10	1.20	1.30
E4	7.95	8.00	8.05
e	2.54 BSC		
H	15.00	15.20	15.40
H1	10.30	10.40	10.50
L	2.20	2.40	2.60
L1	1.50	1.60	1.70
Θ	5°	7°	9°
Θ_1	1°	3°	5°
Θ_2	5°	7°	9°
Θ_3	11°	13°	15°
Θ_4	0°	2°	5°