

Printheads

Hight Speed Thermal Printhead (8dots / mm)

SE2004-DC90A

High speed, high quality, and high durability are achieved by using step free structure with high performance partial glaze and highly conductive overcoat layer. SE200*-DC90A series are lined up which can accommodate with all types of barcode labeling printers from Direct to Thermal Transfer, normal to high speed (over 300mm/s).

●Applications

Bar code label printers


Ticket printers

General purpose compact printers

●Features

- 1) ROHM new technology "STEP FREE" structure will provide, high corrosion resistance, better resistance against scratching damage, high efficiency.
- 2) Standard glazed components to accommodate thick paper.
- 3) High speed clock to facilitate external heat history control.
- 4) Using a hard conductive film as a protective film on the heating element offers excellent resistance to electrostatic damage.
- 5) Compatible with the 300dpi in mechanical specifications, to facilitate the making of a series of printers.

●External dimensions (Unit : mm)



Note: No heat history control function inside the thermal printhead. External heat history control is required for high speed printing.

Printheads

●Characteristics

Parameter	Symbol	Typical	Unit
Effective printing width		112	mm
Dot pitch		0.125	mm
Total dot number		896	dots
Average resistance value	Rave	550	Ω
Applied voltage	V _H	24	V
Applied power	P _o	0.91	W/dot
Print cycle	SLT	0.42	ms
Maximum number of dots energized simultaneously		896	dots
Maximum clock frequency		10	MHz
Maximum roller diameter		20	mm
Running life / pulse life		50 / 1×10 ⁸	km / pulses
Operating temperature		5 to 45	°C

●Pin configuration

HIROSE

No.	Circuit	No.	Circuit
1	GND	2	VDD
3	DI2	4	CLK(CP)
5	/LAT	6	/STB2
7	NC	8	DI1
9	/STB1	10	NC
11	TM	12	TM
13	SENS3	14	SENS2
15	SENS1	16	BEO
17	NC	18	NC
19	NC	20	NC
21	NC	22	NC
23	NC	24	NC
25	NC	26	NC

JST

No.	Circuit
1	COM
2	COM
3	COM
4	GND
5	GND
6	GND

Printheads

●Timing chart





Fig.1

Printheads

●Equivalent circuit



DI No.	DOT No.
DI 2	896~449
DI 1	448~ 1

/STR No.	DOT No.
/STB2	896~449
/STB1	448~ 1

Fig.2

Printheads

●Data sheet




Fig. 3 Representative density curve




Fig. 4 Maximum energy curve




Fig. 5 Thermistor curve

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.