





Parameter	Min.	Typ.	Max.	Units.
Center Frequency (Fc) ¹	69.8	70.0	70.2	MHz
Insertion Loss at Fc		22.4	25.5	dB
1 dB Bandwidth ²	24.5	24.56		MHz
3 dB Bandwidth	26.0	26.1		MHz
40 dB Bandwidth		31.4	34	MHz
Passband Ripple ³		0.5	1.0	dB p-p
Phase Ripple		3.5	6	deg p-p
Group Delay Ripple		30	35	ns p-p
Absolute Delay		1.4		us
Ultimate Rejection	50	60		dB
Substrate Material	128 Lithium Niobate			
Ambient Temperature		25		° C

Notes:

1. Average of the lower and upper 3 dB band edge frequencies.
2. Relative to level at F_c .
3. Excludes band edge transitions.
4. A smoothing aperture of 250 kHz may be applied to Group Delay Ripple measurement.



PACKAGE OUTLINE




Units: mm

Pin Configuration:

Input: 14
Input Return: 1
Output: 8
Output Return: 7
Ground: 2, 9

MATCHING CIRCUIT



Component values:
(Minimum $Q = 45$)

$Ls1 = 397$ nH

$Ls2 = 338$ nH

Notes

- Recommend use of 2% tolerance components.
- Tuning values shown are for reference only. Optimum values may change depending upon board layout.

ISO 9001
Registered

Rev X1 22-Apr-05
Page 2 of 2