

TECHNICAL DATA
DATA SHEET 4168, REV. B**HERMETIC POWER ULTRAFAST RECTIFIER**

DESCRIPTION: A 600-VOLT, 15 AMP, POWER ULTRAFAST RECTIFIER IN A HERMETIC 2-LEAD TO-257 PACKAGE.

Note:

- Add the letter "C" to the part number prefix – **SHDC** for package with ceramic seals.
- Industry standard 1N6779


MAXIMUM RATINGS

All ratings are @ $T_A = 25^\circ\text{C}$ unless otherwise specified

RATING	SYMBOL	MAX.	UNITS
PEAK INVERSE VOLTAGE	PIV	600	Volts
MAXIMUM DC OUTPUT CURRENT (With Cathode Maintained @ $T_C=100^\circ\text{C}$)	I_O	15	Amps
PEAK SINGLE PULSE FORWARD CURRENT, 8.3 ms (per leg)	I_{FSM}	140	Amps
MAXIMUM THERMAL RESISTANCE	$R_{\theta JC}$	1.6	$^\circ\text{C/W}$
MAXIMUM POWER DISSIPATION	P_D	125	Watts
MAXIMUM OPERATING AND STORAGE TEMPERATURE RANGE	Top/Tstg	-65 to + 150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS

CHARACTERISTIC			
MAXIMUM FORWARD VOLTAGE DROP, Pulsed $T_C = 25^\circ\text{C}$ $I_f = 8$ Amps $I_f = 15$ Amps	V_f	1.4 1.6	Volts
MAXIMUM FORWARD VOLTAGE DROP, Pulsed $T_C = 100^\circ\text{C}$ $I_f = 8$ Amps	V_f	1.3	Volts
MAXIMUM FORWARD VOLTAGE DROP, Pulsed $T_C = -55^\circ\text{C}$ $I_f = 15$ Amps	V_f	1.8	Volts
MAXIMUM REVERSE CURRENT $T_C = 25^\circ\text{C}$ I_r @ 600 PIV	I_r	10	μA
MAXIMUM REVERSE CURRENT $T_C = 100^\circ\text{C}$ I_r @ 600 PIV	I_r	1.0	mA
JUNCTION CAPACITANCE $V_R = 5\text{V}$, $F = 1\text{MHZ}$	C_J	300	pF
MAXIMUM REVERSE RECOVERY TIME $I_F = 0.5\text{A}$, $I_R = 1\text{A}$, $I_{RM} = 0.25\text{A}$	t_{rr}	60	nsec

SENSITRON**DATA SHEET 4168, REV. B****MECHANICAL DIMENSIONS: In Inches / mm****TO-257**

TYPE	PIN 1	PIN 3
ULTRAFAST RECTIFIER IN A 2-LEAD TO-257 PACKAGE	CATHODE	ANODE

DISCLAIMER:

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.