

TCE Type (*complementary device type)	Device Polarity & Material	Application	Maximum Ratings					
			Device Power Dissipatn. P_T W	Collector Current Continuous I_C A	Base Current I_B A	Breakdown Voltages		
						Collector-to-Base BV_{CBO} V	Collector-to-Emitter BV_{CEO} V	Emitter-to-Base BV_{EBO} V
SK3003A	PNP/Ge	Audio Small-Signal Amplification	0.2	-1		-30	-12	-5
SK3004	PNP/Ge	AF Driver, Preamp, Power Output Stage	1	-1		-32	-25	-12
SK3006	PNP/Ge	FM Broadcast Rec., RF Amp/Mix/Osc/Converter	0.08	-0.01		-25	-18	-0.3
SK3007A	PNP/Ge	AF Output Stage, Class A/B	1	-1		-32	-16	-10
SK3008	PNP/Ge	AM Broadcast Band	0.08	-0.01		-34	-15	-0.5
SK3009	PNP/Ge	Gen. AF High-Power	30	-10	-2	-60	-50	-10
SK3012	PNP/Ge	AF Power	170	-30		-60	-45	-30
SK3018	NPN/Si	RF Small-Signal	0.3	0.05		20	12	2.5
SK3020	NPN/Si	Small-Signal, Med -Power	1	1		120 Min		7 Min
SK3021	NPN/Si	Class A Audio Amplification	35	2		500	300	6
SK3024	NPN/Si	Audio Driver/Output Stage	5	0.7	0.2		$V_{CEB} = 90$	4
*SK3025	PNP/Si	Audio Driver/Output Stage	3	-0.7	-0.2		-90	-4
*SK3024								
SK3026	NPN/Si	Audio Output Stage	75	4	2	90	55	7
SK3027	NPN/Si	Audio Output Stage	115	15	7	100	60	7
*SK3173								
SK3028	NPN/Si	Matched Pair SK3026	35	4		60	60	5
SK3029	NPN/Si	Audio Output Stage	115	15	7	100	60	7
SK3035	PNP/Ge	TV Horiz. Output Stage	32	-10		-220		-1.5
SK3036	NPN/Si	Gen. Purpose Power	150	30	15	100	60	7
SK3037	NPN/Si	Gen. Purpose	150	30	15	100	60	7
SK3039	NPN/Si	UHF TV Tuner	0.2	0.05		30	15	3
SK3040	NPN/Si	TV Video Output Stage	1	0.1		200	200	6
SK3044	NPN/Si	Gated AGC, Clamp Amp TV	10	1		300 Min	300 Min	7 Min
SK3045	NPN/Si	TV Video, AF Output, Voltage Regulator	10	1		450	350	7
SK3049	NPN/Si	CB Transmitter Output Stage	10	2		60	60	4



Operating Characteristics					Switching Characteristics (if any) Max. Limits, Resistive Load				RF Functional Data (if any)			Outline No.	TCE Type
Current Gain			Gain- Bandwidth Product	Noise Figure	Delay Time	Rise Time	Storage Time	Fall Time	Power Gain	Test Conditions			
Small Signal	Static	Test Conditions								Power Output	Operating Frequency		
h_{fe}	h_{FE}		f_T MHz	NF	t_d μS	t_r μS	t_s μS	t_f μS	G_p dB	P_{OUT} Test W	F_0 MHz		
20 Min		Vce(V) = -9 Ic(A) = -1										T-008	SK3003A
200 Typ		Vce(V) = -1 Ic(A) = -0.3	0.001									T-004	SK3004
50	...	Vce(V) = -12 Ic(A) = -0.001	260									T-001	SK3006
55-175		Vce(V) = Ic(A) = -0.005	1.5									T-004	SK3007A
50		Vce(V) = -12 Ic(A) = -0.001	45									T-004	SK3008
100		Vce(V) = -2 Ic(A) = -0.5	0.60 Typ									T-043	SK3009
105 Typ	...	Vce(V) = -2 Ic(A) = -5	0.1									T-037	SK3012
90 Typ		Vce(V) = 6 Ic(A) = 0.002	1400 Typ									T-001	SK3018
....	150 Max	Vce(V) = 10 Ic(A) = 0.005	125 Min	6dB								T-005	SK3020
...	100 Max	Vce(V) = 10 Ic(A) = 1				3 Max	4 Max	3 Max				T-040	SK3021
...	50-250	Vce(V) = 4 Ic(A) = 0.15	100 Typ	...								T-005	SK3024
...	250 Max	Vce(V) = 4 Ic(A) = 0.15	100 Typ	...								T-005	SK3025
.....	150 Max	Vce(V) = 4 Ic(A) = 0.5	3									T-040	SK3026
.....	20-70	Vce(V) = 4 Ic(A) = 4										T-043	SK3027
...	25-320	Vce(V) = 2 Ic(A) = 1	8									T-040	SK3028
...	20-70	Vce(V) = 4 Ic(A) = 4										T-043	SK3029
25		Vce(V) = -1.5 Ic(A) = -4	2.5									T-043	SK3035
.....	15-60	Vce(V) = 4 Ic(A) = 10										T-043	SK3036
...	15-60	Vce(V) = 4 Ic(A) = 10										T-043	SK3037
...	25-250	Vce(V) = 5 Ic(A) = 0.002	1400 Min	4.5dB Max					15 Min	...	450	T-001	SK3039
.....	55	Vce(V) = 10 Ic(A) = 0.05	120									T-005	SK3040
.....	40-160	Vce(V) = 10 Ic(A) = 0.2										T-005	SK3044
...	40-160	Vce(V) = 10 Ic(A) = 0.02										T-007	SK3045
...	10-140	Vce(V) = 5 Ic(A) = 0.5	300 Typ									T-007	SK3049