



<http://www.soly-tech.com>

首利實業股份有限公司

SOLYTECH ENTERPRISE CORPORATION

台北縣五股鄉五股工業區五權七路18號3F
3F No.18 Wu Chun 7Rd, Wu Gu
Industry Area, Wu Gu Shiang, Taipei
Tel:886-2-2299-1907 Fax:886-2-2290-1978~7

SPECIFICATION

Model Name	SL-8360BTX									
Watt	350W									
Form Factor	ATX12V Version 2.2 V									
Dimensions	Cage: 150 (L) x 140 (W) x 86 (H) mm									
Fan	Dual 8CM FAN									
Connector	20+4pin M/B x1, 4pin+12V CPU x1, Peripheral x 6, Floppy x 2									
PFC	Passive PFC (Option)									
Input	Voltage	90V~132Vac or 180V~264Vac								
	Frequency	47~63Hz								
	Current	8/4A for 115-230Vac								
	Efficiency	65% at full load , nominal line								
Output	DC O/P	+3.3V	+5V	+12V1	+12V2	-12V	+5Vsb			
	Current	20A	12A	10A	13A	0.3A	2.5A			
	+5V & +3.3V combined load					126W				
	+5V & +3.3V &+12Vcombined load					335W				
Protection	Over voltage protection / Over current protection / Short circuit protection									
MTBF	>50'000hrs at 80% load , 25℃ ambient									
Environment	Operating temperature : 5℃ to 40℃ Storage temperature : -20℃ to 70℃									
Safety	CB, CUL, TUV, CSA, NEMKO, SEMKO, DEMKO, FIMKO, BSMI									
EMI/RFI	FCC Part 15 Class B , CISPR 22 Class B , CE									

