

Medium Pressure Sensor Analog Output

SM6844-015-A-B-5-S

FEATURES

- Analog pressure calibrated and temperature compensated output
- Amplified analog output
- Compensated temperature range: 0 to 85oC
- Absolute pressure configuration
- Insensitive to mounting orientation
- Robust JEDEC SOIC-16 package for automated assembly
- Manufactured according to ISO9001 and ISO/TS 16949 standards
- RoHS & REACH compliant
- Pressure range: 15 PSIA (103 kPa)



DESCRIPTION

The SM6844 Series is an absolute pressure MEMS sensor family offering state-of-the-art pressure transducer technology and CMOS mixed signal processing technology to produce an analog, fully conditioned, pressure and temperature compensated sensor in JEDEC standard SOIC-16 package with a single horizontal porting option.

Combining the pressure sensor with a signal-conditioning ASIC in a single package simplifies the use of advanced silicon micro-machined pressure sensors. The pressure sensor can be mounted directly on a standard printed circuit board and a high level, calibrated pressure signal can be acquired from the analog output. This eliminates the need for additional circuitry, such as a compensation network or microcontroller containing a custom correction algorithm.

The SM6844 is shipped in sticks or tape & reel.

Medical	Industrial	Consumer	
Sleep Apnea	Airflow Measurement	Sports Equipment	
СРАР	Pneumatic Gauges	Appliances	
Ventilators	Pressure Switches		
Gas Flow Instrumentation	Safety Cabinets		
Air Flow Monitors	Life Sciences		
Negative Pressure Wound Therapy	Gas Flow Instrumentation		



ABSOLUTE MAXIMUM RATINGS

All parameters are specified at Vdd = 5 V DC supply voltage at 25°C, unless otherwise noted.

No.	Characteristic	Symbol	Minimum	Typical	Maximum	Units
1	Supply Voltage	V_{DD}	0.0		6.0	V
2	Supply Current	I _{VDD}	0.0	2.0	4.0	mA
3	Operating Temperature ^(a)	Τ _{ΟΡ}	-40		+125	°C
4	Storage Temperature ^(a)	T _{STG}	-40	-	+125	°C

Notes:

a. Tested on a sample basis.

b. Clean, dry gas compatible with wetted materials. Wetted materials include Pyrex glass, silicon, alumina ceramic, epoxy, RTV, gold, aluminum, and nickel.

No.	Product Number	Operating Pressure	Proof Pressure (P _{PROOF}) ^(a)	Burst Pressure (P _{BURST}) ^(a)	
5	SM6844-015-A-B-5-S	0 to 15 PSIA	±45 PSI	±75 PSI	

Notes:

a. Tested on a sample basis.

OPERATING CHARACTERISTICS TABLE

All parameters are specified at Vdd = 5 V DC supply voltage at 25°C, unless otherwise noted.


	Single-Ended						
No.	Characteristic	Symbol	Minimum	Typical	Maximum	Units	
6	Supply Voltage	V_{DD}	4.75	5	5.25	V FS	
7	Full Scale Span	FSP		4		V	
8	Zero Offset Voltage	V _{ZERO}		0.5		V	
9	Compensated Temperature Range	T _{COMP}	-0		+85	°C	
10	Accuracy ^(c)	ACC	-1		+1	%FS	


Notes:

c. The accuracy specification applies over all operating conditions. This specification includes the combination of linearity, repeatability, and hysteresis errors over pressure & temperature.




SOIC-16 (B) Single-Horizontal Package Dimensions






Notes:

- • All dimensions in units of [mm].
- • Moisture Sensitivity Level (MSL): Level 3.
- • Wetted materials: Silicon, glass, copper, silicone, epoxy, mold compound.
- • Tolerance on all dimensions ±0.13 mm unless otherwise specified.





SM6844 + Family Applications Circuit



"C" needs to be in close proximity of the device

Package Labeling					
Pin No.	Pin Function				
1	Vout (Amplified Analog Output)				
2	NC				
3	VDD				
4	NC				
5	NC				
6	NC				
7	NC				
8	NC				
9	NC				
10	NC				
11	NC				
12	GND				
13	NC				
14	NC				
15	NC				
16	NC				

NOTES:

• Do not connect to NC pins



Ordering Information

Order Code	Part Marking	Negative Pressure Range	Positive Pressure Range	Pressure Type	Tube Configuration	Shipping Method
SM6844-015-A-B-5-T	SM6844	0 PSI	15 PSI	Absolute	Single Horizontal	Sticks or Tape & Reel

Part Number Legend



Silicon Microstructures Product Series

.




 $\frac{\mathbf{\Lambda}}{\mathbf{1}}$



<u>5</u> ↑



Shipping Configuration S - Sticks/Tubes T - T & R



| Unit of Pressure C : cmH₂O M : mBar K : kPa None : PSI



| Port Configuration B: Horizontal C: Vertical H: Hole







QUALIFICATION STANDARDS

REACH Compliant RoHS Compliant PFOS/PFOA Compliant For qualification specifications, please contact Sales at sales@si-micro.com









Silicon Microstructures Warranty and Disclaimer:

Silicon Microstructures, Inc. reserves the right to make changes without further notice to any products herein and to amend the contents of this data sheet at any time and at its sole discretion.

Information in this document is provided solely to enable software and system implementers to use Silicon Microstructures, Inc. products and/or services. No express or implied copyright licenses are granted hereunder to design or fabricate any silicon-based microstructures based on the information in this document.

Silicon Microstructures, Inc. makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Silicon Microstructures, Inc. assume any liability arising out of the application or use of any product or silicon-based microstructure, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Silicon Microstructure's data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals", must be validated for each customer application by customer's technical experts. Silicon Microstructures, Inc. does not convey any license under its patent rights nor the rights of others. Silicon Microstructures, Inc. makes no representation that the circuits are free of patent infringement. Silicon Microstructures, Inc. products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Silicon Microstructures, Inc. product could create a situation where personal injury or death may occur. Should Buyer purchase or use Silicon Microstructures, Inc. and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Silicon Microstructures, Inc. was negligent regarding the design or manufacture of the part.

Silicon Microstructures, Inc. warrants goods of its manufacture as being free of defective materials and faulty workmanship. Silicon Microstructures, Inc. standard product warranty applies unless agreed to otherwise by Silicon Microstructures, Inc. in writing; please refer to your order acknowledgement or contact Silicon Microstructures, Inc. directly for specific warranty details. If warranted goods are returned to Silicon Microstructures, Inc. during the period of coverage, Silicon Microstructures, Inc. will repair or replace, at its option, without charge those items it finds defective. The foregoing is buyer's sole remedy and is in lieu of all warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Silicon Microstructures, Inc. be liable for consequential, special, or indirect damages.

While Silicon Microstructures, Inc. provides application assistance personally, through its literature and the Silicon Microstructures, Inc. website, it is up to the customer to determine the suitability of the product for its specific application. The information supplied by Silicon Microstructures, Inc. is believed to be accurate and reliable as of this printing. However, Silicon Microstructures, Inc. assumes no responsibility for its use. Silicon Microstructures, Inc. assumes no responsibility for any inaccuracies and/or errors in this publication and reserves the right to make changes without further notice to any products or specifications herein

Silicon Microstructures, Inc.TM and the Silicon Microstructures, Inc. logo are trademarks of Silicon Microstructures, Inc. All other service or product names are the property of their respective owners.

© Silicon Microstructures, Inc. 2001-2016. All rights reserved.