

DUAL RETRIGGERABLE MONOSTABLE MULTIVIBRATOR

- **HIGH SPEED**
 $t_{PD} = 25 \text{ ns (TYP)}$ at $V_{CC} = 5V$
- **LOW POWER DISSIPATION**
 STANDBY STATE $I_{CC} = 4 \mu A \text{ (MAX.)}$ AT $T_A = 25^\circ C$
 ACTIVE STATE $I_{CC} = 700 \mu A \text{ (MAX.)}$ AT $V_{CC} = 5V$
- **HIGH NOISE IMMUNITY**
 $V_{NIH} = V_{NIL} = 28 \% V_{CC} \text{ (MIN.)}$
- **OUTPUT DRIVE CAPABILITY**
 10 LSTTL LOADS
- **SYMMETRICAL OUTPUT IMPEDANCE**
 $I_{OH} = I_{OL} = 4 \text{ mA (MIN.)}$
- **BALANCED PROPAGATION DELAYS**
 $t_{PLH} = t_{PHL}$
- **WIDE OPERATING VOLTAGE RANGE**
 $V_{CC} \text{ (OPR)} = 2 V \text{ TO } 6 V$
- **WIDE OUTPUT PULSE WIDTH RANGE**
 $t_{WOUT} = 120 \text{ ns} \sim 60 \text{ s OVER AT } V_{CC} = 4.5 V$
- **PIN AND FUNCTION COMPATIBLE WITH**
 54/74LS423

DESCRIPTION

The M54/74HC423/423A are high speed CMOS MONOSTABLE multivibrators fabricated with silicon gate C²MOS technology.

They achieve the high speed operation similar to equivalent LSTTL while maintaining the CMOS low power dissipation. There are two trigger inputs, \overline{A} INPUT (negative edge) and B INPUT (positive edge). These inputs are valid for rising/falling signals, ($t_r - t_f - 1 \text{ sec}$). After triggering the output maintains the MONOSTABLE state for the time period determined by the external resistor R_x and capacitor C_x .


Two different pulse width constant are available:
 $K \cong 0.46$ for HC423 $K \cong 1$ for HC423A.

Taking \overline{CLR} low breaks this MONOSTABLE STATE. If the next trigger pulse occurs during the MONOSTABLE period it makes the MONOSTABLE period longer. Limit for values of C_x and R_x :



C_x : NO LIMIT

R_x : $V_{CC} < 3.0 V$ 5 K Ω to 1 M Ω
 $V_{CC} \geq 3.0 V$ 1 K Ω to 1 M Ω


All inputs are equipped with protection circuits against static discharge and transient excess voltage.




PIN CONNECTIONS (top view)



SYSTEM DIAGRAM



TIMING CHART



FUNCTIONAL DESCRIPTION (continued)

RE-TRIGGERED OPERATION

When a second trigger pulse follows the first its effect will depend on the state of the multivibrator. If the capacitor C_x is being charged the voltage level of R/C external falls to V_{refl} again and Q remains high i.e. the retrigger pulse arrives in a time shorter than the period $R_x \cdot C_x$ seconds, the capacitor charging time constant. If the second trigger pulse is very close to the initial trigger pulse it is ineffective ; i.e. the second trigger must arrive in the capacitor discharge cycle to be ineffective; Hence the

minimum time for a second trigger to be effective depends on V_{cc} and C_x .

RESET OPERATION

CL is normally high. If CL is low, the trigger is not effective because Q output goes low and trigger control flip-flop is reset.


Also transistor Op is turned on and C_x is charged quickly to V_{cc} . This means if CL input goes low, the IC becomes waiting state both in operating and non operating state.

TRUTH TABLE

INPUTS			OUTPUTS		NOTE
\bar{A}	B	\bar{CL}	Q	\bar{Q}	
	H	H			OUTPUT ENABLE
X	L	H	L	H	INHIBIT
H	X	H	L	H	INHIBIT
L		H			OUTPUT ENABLE
X	X	L	L	H	INHIBIT

X: Don't Care Z: High Impedance


INPUT AND OUTPUT EQUIVALENT CIRCUIT



PIN DESCRIPTION

PIN No	SYMBOL	NAME AND FUNCTION
1, 9	1A, 2A	Trigger Inputs (Negative Edge Triggered)
2, 10	1B, 2B	Trigger Inputs (Positive Edge Triggered)
3, 11	1CLR, 2CLR	Direct Reset (Active LOW)
4, 12	1Q, 2Q	Outputs (Active LOW)
7	2REXT/CEXT	External Resistor Capacitor Connection
13, 5	1Q, 2Q	Outputs (Active HIGH)
14, 6	1CEXT, 2CEXT	External Capacitor Connection
15	1REXT/CEXT	External Resistor Capacitor Connection
8	GND	Ground (0V)
16	VCC	Positive Supply Voltage

IEC LOGIC SYMBOL



ABSOLUTE MAXIMUM RATING

Symbol	Parameter	Value	Unit
V _{CC}	Supply Voltage	-0.5 to +7	V
V _I	DC Input Voltage	-0.5 to V _{CC} + 0.5	V
V _O	DC Output Voltage	-0.5 to V _{CC} + 0.5	V
I _{IK}	DC Input Diode Current	± 20	mA
I _{OK}	DC Output Diode Current	± 20	mA
I _O	DC Output Source Sink Current Per Output Pin	± 25	mA
I _{CC} or I _{GND}	DC V _{CC} or Ground Current	± 50	mA
P _D	Power Dissipation	500 (*)	mW
T _{stg}	Storage Temperature	-65 to +150	°C
T _L	Lead Temperature (10 sec)	300	°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these condition is not implied.

(*) 500 mW: ± 65 °C derate to 300 mW by 10mW/°C: 65 °C to 85 °C

M54/M74HC423/423A

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Value	Unit
V _{CC}	Supply Voltage	2 to 6	V
V _I	Input Voltage	0 to V _{CC}	V
V _O	Output Voltage	0 to V _{CC}	V
T _{op}	Operating Temperature: M54HC Series M74HC Series	-55 to +125 -40 to +85	°C °C
t _r , t _f	Input Rise and Fall Time	0 to 1000 0 to 500 0 to 400	ns
C _X	External Capacitor	NO LIMITATION	
R _X	External Resistor	V _{CC} < 2 V V _{CC} ≥ 3 V	5K to 1M (*) 1K to 1M (*)
			Ω

(*) The maximum allowable values of C_x and R_x are a function of leakage of capacitor C_x, the leakage of device and leakage due to the board layout and surface resistance. Susceptibility to externally induced noise may occur for R_x > 1MΩ

DC SPECIFICATIONS

Symbol	Parameter	Test Conditions				Value						Unit		
		V _{CC} (V)			T _A = 25 °C 54HC and 74HC			-40 to 85 °C 74HC		-55 to 125 °C 54HC				
					Min.	Typ.	Max.	Min.	Max.	Min.	Max.			
V _{IH}	High Level Input Voltage	2.0			1.5			1.5		1.5		V		
		4.5			3.15			3.15		3.15				
		6.0			4.2			4.2		4.2				
V _{IL}	Low Level Input Voltage	2.0					0.5		0.5		0.5	V		
		4.5					1.35		1.35		1.35			
		6.0					1.8		1.8		1.8			
V _{OH}	High Level Output Voltage	2.0	V _I = V _{IH} or V _{IL}	I _O =-20 μA	1.9	2.0		1.9		1.9		V		
		4.5			4.4	4.5		4.4		4.4				
		6.0			5.9	6.0		5.9		5.9				
		4.5		I _O =-4.0 mA		4.18	4.31		4.13		4.10			
		6.0		I _O =-5.2 mA		5.68	5.8		5.63		5.60			
V _{OL}	Low Level Output Voltage	2.0	V _I = V _{IH} or V _{IL}	I _O = 20 μA		0.0	0.1		0.1		0.1	V		
		4.5				0.0	0.1		0.1		0.1			
		6.0				0.0	0.1		0.1		0.1			
		4.5		I _O = 4.0 mA			0.17	0.26		0.33			0.40	
		6.0		I _O = 5.2 mA			0.18	0.26		0.33			0.40	
I _I	Input Leakage Current	6.0	V _I = V _{CC} or GND				±0.1		±1		±1	μA		
I _I	R/C Terminal Off State Current	6.0	V _I = V _{CC} or GND				±0.1		±1		±1	μA		
I _{CC}	Quiescent Supply Current	6.0	V _I = V _{CC} or GND				4		40		80	μA		
I _{CC}	Active State Supply Current (1)	2.0	V _I = V _{CC} or GND Pin 7 or 15 V _{IN} = V _{CC} /2			45	200		260		325	μA		
		4.5				400	500		650		810	μA		
		6.0				0.7	1.0		1.3		1.6	mA		


(1): Per Circuit

AC ELECTRICAL CHARACTERISTICS ($C_L = 50 \text{ pF}$, Input $t_r = t_f = 6 \text{ ns}$)


Symbol	Parameter	Test Conditions		Value						Unit	
		V _{CC} (V)		T _A = 25 °C 54HC and 74HC			-40 to 85 °C 74HC		-55 to 125 °C 54HC		
				Min.	Typ.	Max.	Min.	Max.	Min.		Max.
t _{TLH} t _{THL}	Output Transition Time	2.0			30	75		95			ns
		4.5			8	15		19			
		6.0			7	13		16			
t _{PLH} t _{PHL}	Propagation Delay Time (\overline{A} , B - Q, \overline{Q})	2.0			102	210		265			ns
		4.5			29	42		53			
		6.0			22	36		45			
t _{PLH} t _{PHL}	Propagation Delay Time (CLR - Q, \overline{Q})	2.0			68	160		200			ns
		4.5			20	32		40			
		6.0			16	27		34			
t _{WOUT}	Output Pulse Width (for HC423)	2.0	C _X = 100 pF R _X = 10 KΩ		1.3						μs
		4.5			1.1						
		6.0			1						
		2.0	C _X = 0.1 μF R _X = 100 KΩ		4.8						ms
		4.5			4.6						
		6.0			4.5						
t _{WOUT}	Output Pulse Width (for HC423A)	2.0	C _X = 100 pF R _X = 10 KΩ		1.7						μs
		4.5			1.4						
		6.0			1.3						
		2.0	C _X = 0.1 μF R _X = 100 KΩ		10						ms
		4.5			9.5						
		6.0			9.5						
Δt _{WOUT}	Output Pulse Width Error Between Circuits in Same Package				±1						%
t _{W(H)} t _{W(L)}	Minimum Pulse Width	2.0				75		95			ns
		4.5				15		19			
		6.0				13		16			
t _{W(L)}	Minimum Pulse Width	2.0				75		95			ns
		4.5				15		19			
		6.0				13		16			
t _{rr}	Minimum Retrigger Time	2.0	C _X = 100 pF R _X = 1 KΩ		325						ns
		4.5			108						
		6.0			78						
		2.0	C _X = 0.1 μF R _X = 100 KΩ		5						μs
		4.5			1.4						
		6.0			1.2						
C _{IN}	Input Capacitance				5	10		10		10	pF
C _{PD} (*)	Power Dissipation Capacitance				160						pF

(*) C_{PD} is defined as the value of the IC's internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit). Average operating current can be obtained by the following equation. $I_{CC(opr)} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC'}$ Duty/100 + $I_C/2$ (per monostable) ($I_{CC'}$: Active Supply Current) (Duty: %)


Output Pulse Width Constant Characteristics
(for HC423)




Output Pulse Width Constant Characteristics
(for HC423A)



Output Pulse Width Characteristics (for HC423)




Output Pulse Width Characteristics (for HC423A)




Plastic DIP16 (0.25) MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
a1	0.51			0.020		
B	0.77		1.65	0.030		0.065
b		0.5			0.020	
b1		0.25			0.010	
D			20			0.787
E		8.5			0.335	
e		2.54			0.100	
e3		17.78			0.700	
F			7.1			0.280
I			5.1			0.201
L		3.3			0.130	
Z			1.27			0.050



Ceramic DIP16/1 MECHANICAL DATA


DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A			20			0.787
B			7			0.276
D		3.3			0.130	
E	0.38			0.015		
e3		17.78			0.700	
F	2.29		2.79	0.090		0.110
G	0.4		0.55	0.016		0.022
H	1.17		1.52	0.046		0.060
L	0.22		0.31	0.009		0.012
M	0.51		1.27	0.020		0.050
N			10.3			0.406
P	7.8		8.05	0.307		0.317
Q			5.08			0.200



P053D

SO16 (Narrow) MECHANICAL DATA


DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A			1.75			0.068
a1	0.1		0.2	0.004		0.007
a2			1.65			0.064
b	0.35		0.46	0.013		0.018
b1	0.19		0.25	0.007		0.010
C		0.5			0.019	
c1	45° (typ.)					
D	9.8		10	0.385		0.393
E	5.8		6.2	0.228		0.244
e		1.27			0.050	
e3		8.89			0.350	
F	3.8		4.0	0.149		0.157
G	4.6		5.3	0.181		0.208
L	0.5		1.27	0.019		0.050
M			0.62			0.024
S	8° (max.)					



P013H

PLCC20 MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	9.78		10.03	0.385		0.395
B	8.89		9.04	0.350		0.356
D	4.2		4.57	0.165		0.180
d1		2.54			0.100	
d2		0.56			0.022	
E	7.37		8.38	0.290		0.330
e		1.27			0.050	
e3		5.08			0.200	
F		0.38			0.015	
G			0.101			0.004
M		1.27			0.050	
M1		1.14			0.045	



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A