

Rotary Switch


6-position Vertical Type

SRRN Series

www.DataSheet4U.com



Lead wiring compatible switch.



Typical Specifications

Items		Specifications
Rating(max.)(min.) (Resistive load)		0.15A 12V DC/50μA 3V DC
Contact resistance (Initial/After operating life)		50mΩ max./100mΩ max.
Rotational torque		70 ± 30mN·m
Operating life	Without load	10,000cycles
	With load	10,000cycles(0.15A 12V DC)

Product Line

Number of wafers	Poles	Positions	Changeover angle	Changeover timing	Actuator configuration	Actuator length (mm)	Minimum order unit(pcs.)	Product No.			
1	2	5	30 ± 3°	Non shorting	Round	20	600	SRRN151800			
					Flat	15		SRRN152000			
		6			18-tooth serration	20		SRRN161100			
	3	4			Round			SRRN142100			
	4	3			18-tooth serration	15			SRRN134300		

Notes

1. Products other than those listed in the above chart are also available. Please contact us for details.
2. All the axis are cutting shafts.
3. Please place purchase orders per minimum order unit(integer).

Detector

Push

Slide

Rotary

Encoders

Power


Dual-in-line
Package Type

TACT Switch™

Custom-
Products


Dimensions

Unit:mm



Terminal Configuration

Unit:mm



Standard Circuit Diagram(Standard Poles Per Step)

Number of poles	2		3		4	
Circuit diagram						
	Dummy terminals	5-positions 6-positions	4-positions	3-positions		

Note

The ☒ mark in the above table indicate a stopper with the shaft turned fully counterclockwise when viewed from direction A of the diagrams.

Refer to P.171 for shaft configurations.
Refer to P.173 for attached parts.

List of Varieties

Series			SRBD	SRBQ		SRRM	SRBV	SRBM		SRRN					
				Insertion	Reflow type			Rotary	Pulse						
Photo															
Outline specifications	Step angle		36 °	40 ± 3 °		30 ± 3 °			18 ± 3 °	30 ± 3 °					
	Number of poles		1			1 2 3 4	1	1 2	2 3 4						
Dimensions (mm)		W	10	11.4		————	16.2	12.5		————					
		D		12.4			10								
		H	1.7		3.5		7.5		11.5						
Operating temperature range			-25 to +85		-10 to +60		-40 to +85			-10 to +60					
Rating(max)/(min) (Resistive load)			1mA 5V DC 50μA 3V DC		0.1A 16V DC 50μA 3V DC	0.25A 30V DC 50μA 3V DC	0.3A 16V DC 50μA 3V DC	0.1A 16V DC 50μA 3V DC		0.15A 12V DC 50μA 3V DC					
Electrical performance	Initial contact resistance		100MΩ min. 100V DC			100MΩ min. 500V DC	100MΩ min. 100V DC			100MΩ min. 500V DC					
	Insulation resistance		100V AC for 1minute			500V AC for 1minute	100V AC for 1minute			500V AC for 1minute					
	Voltage proof		3N for 1minute	5N for 1minute		10N for 1minute	5N for 1minute								
Mechanical performance	Actuator strength	Rotational direction	————			1N·m	0.6N·m	0.5N·m	——	1N·m					
		Push direction	50N	20N		100N									
	Wobble of actuator		Load at the tip of shaft SRRM : 5N SRBV, SRBQ : 1N				The below table shows for SRBQ (Unit : mm)			The below table shows for SRBV (Unit : mm)			Measuring position from mounting surface	Shaft wobble (max.value)	Applicable mounting dimension
			(Unit : mm)			Distance from mounting surface to the tip of shaft		Shaft wobble (max.value)	(Unit : mm)			Measuring position from mounting surface		Shaft wobble (max. value)	Applicable mounting dimension
			Measuring position from mounting surface	Shaft wobble (max. value)	Applicable mounting dimension	below 5		0.5 max.	Measuring position from mounting surface		Shaft wobble (max. value)	Applicable mounting dimension	10mm	0.17 mm	15 mm
			10	0.17	15	above 5 and below 10		0.9 max.	10	0.2	15	15mm	0.25 mm	20 mm	
15			0.25	20	above 10 and below 15		1.2 max.	15	0.3	20	Load at the tip of shaft : 5N				
Durability	Operating life without load		10,000cycles 250mΩ max.	10,000cycles 100mΩ max.	10,000cycles 40mΩ max.	10,000cycles 100mΩ max.			30,000cycles 100mΩ max.	10,000cycles 70mΩ max.					
	Operating life with load Load : (at rated load)		10,000cycles 250mΩ max.	10,000cycles 100mΩ max.	10,000cycles 60mΩ max.	10,000cycles 150mΩ max.			10,000cycles 100mΩ max.						
Environmental performance	Cold		-40 ± 2 for 500h		-20 ± 2 for 96h										
	Dry heat		85 ± 2 for 500h		85 ± 2 for 96h										
	Damp heat		60 ± 2 , 90 to 95%RH for 500h		40 ± 2 , 90 to 95%RH for 96h										
Soldering	Manual soldering		————	350 ± 10 3 ⁺ 1s	350 ± 5 3s max.	350 ± 10 , 3 ⁺ 1s									
	Dip soldering		————	260 ± 5 5 ± 1s	——	260 ± 5 10 ± 1s			260 ± 3 5s max.	260 ± 5 10 ± 1s					
	Reflow soldering		Please see P.172			—————									
Page			158	160		167	165	162		169					

Detector

Push

Slide

Rotary

Encoders

Power

Dual-in-line
Package Type

TACT Switch™

Custom-
Products


- Rotary Switches Shaft Style171
- Rotary Switches Soldering Conditions172
- Rotary Switches Attached Parts173
- Rotary Switches Cautions174

Shaft Configurations


18-tooth Serration Shaft

The shaft shows the position in which it is turned fully counterclockwise.

Cutting Shaft



Die Casting Shaft



Unit:mm


Shaft length L	A	B	C
15	6	1	7
20	10	2	11

Unit:mm


Shaft length L	l
15	8
20	12

Details About Serration

- (1) The mold dimensions of standard serration and the dimensions of test jigs are as shown in the figure at left.
- (2) Position of the serration bottom
When the shaft is turned fully counterclockwise, the position of the serration bottom is on the AA line.
- (3) Slitting angle
The slitting angle(position) is not specified.




Round Shaft




Round Shaft with Groove

The shaft shows the position in which it is turned fully counterclockwise.




Shaft flatten angle




Flat Shaft

The shaft shows the position in which it is turned fully counterclockwise.

Cutting Shaft



Die Casting Shaft



Unit:mm

Shaft length L	l
15	7
20	12

Shaft flatten angle



Note


SRBM Series are based on (printed terminal direction). SRRM, SRRN, SRBV Series are based on (panel lug).

Attached Parts

The following parts are included with the product.


SRRM, SRBV

Unit:mm



SRBM, SRRN

Unit:mm



Detector

Push

Slide

Rotary

Encoders

Power

Dual-in-line
Package Type

TACT Switch™

Custom-
Products