

**ON Semiconductor®**

www.onsemi.com

STK531U369A-E

Inverter IPM for 3-phase Motor Drive

Overview

This “Inverter IPM” is highly integrated device containing all High Voltage (HV) control from HV-DC to 3-phase outputs in a single SIP module (Single-In line Package). Output stage uses IGBT/FRD technology and implements Under Voltage Protection (UVP) and Over Current Protection (OCP) with a Fault Detection output flag. Internal Boost diodes are provided for high side gate boost drive.

Function

- Single control power supply due to Internal bootstrap circuit for high side pre-driver circuit
- All control input and status output are at low voltage levels directly compatible with microcontrollers
- Built-in cross conduction prevention
- Externally accessible embedded thermistor for substrate temperature measurement
- The level of the over current protection is adjustable with the external resistor, “RSD”

Certification

- UL Recognized (File number : E339285)

Specifications

Absolute Maximum Ratings at $T_c = 25^\circ\text{C}$

Parameter	Symbol	Remarks	Ratings	Unit
Supply voltage	V_{CC}	P to N, surge < 500V *1	450	V
Collector-emitter voltage	V_{CE}	P to U, V, W or U, V, W, to N	600	V
Output current	I_o	P, N, U, V, W terminal current	± 10	A
		P, N, U, V, W terminal current at $T_c = 100^\circ\text{C}$	± 5	A
Output peak current	I_{op}	P, N, U, V, W terminal current, $PW = 1\text{ms}$	± 20	A
Pre-driver voltage	$VD_{1,2,3,4}$	VB1 to U, VB2 to V, VB3 to W, V_{DD} to V_{SS} *2	20	V
Input signal voltage	V_{IN}	HIN1, 2, 3, LIN1, 2, 3	-0.3 to V_{DD}	V
FAULT terminal voltage	V_{FAULT}	FAULT terminal	-0.3 to V_{DD}	V
Maximum power dissipation	P_d	IGBT per 1 channel	31.2	W
Junction temperature	T_j	IGBT, FRD	150	$^\circ\text{C}$
Storage temperature	T_{stg}		-40 to +125	$^\circ\text{C}$
Operating case temperature	T_c	IPM case temperature	-20 to +100	$^\circ\text{C}$
Tightening torque		A screw part *3	0.9	Nm
Isolation voltage	Vis	50Hz sine wave AC 1 minute *4	2000	VRMS

Reference voltage is “ V_{SS} ” terminal voltage unless otherwise specified.

*1 : Surge voltage developed by the switching operation due to the wiring inductance between P and N terminal.

*2 : $VD_1=VB_1$ to U, $VD_2=VB_2$ to V, $VD_3=VB_3$ to W, $VD_4=V_{DD}$ to V_{SS} terminal voltage.

*3 : Flatness of the heat-sink should be lower than 0.15mm.

*4 : Test conditions : AC2500V, 1 second.

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

ORDERING INFORMATION

See detailed ordering and shipping information on page 13 of this data sheet.

STK531U369A-E

Electrical Characteristics at Tc = 25°C, VD1, VD2, VD3, VD4 = 15V

Parameter	Symbol	Conditions		Test circuit	MIN	TYP	MAX	Unit
Power output section								
Collector-emitter cut-off current	I _{CE}	V _{CE} = 600V		Fig.1	-	-	0.1	mA
Bootstrap diode reverse current	I _{R(BD)}	V _{R(BD)} = 600V			-	-	0.1	mA
Collector to emitter saturation voltage	V _{CE(SAT)}	I _c = 10A T _j = 25°C	Upper side	Fig.2	-	1.9	2.4	V
			Lower side *1		-	2.2	2.7	
		I _c = 5A T _j = 100°C	Upper side		-	1.5	-	
			Lower side *1		-	1.7	-	
Diode forward voltage	V _F	I _F = 10A T _j = 25°C	Upper side	Fig.3	-	1.8	2.1	V
			Lower side *1		-	2.1	2.4	
		I _F = 5A T _j = 100°C	Upper side		-	1.4	-	
			Lower side *1		-	1.6	-	
Junction to case thermal resistance	θ _{j-c(T)}	IGBT		-	-	-	4.0	°C/W
	θ _{j-c(D)}	FWD			-	-	6.0	
Control (Pre-driver) section								
Pre-driver current consumption	I _D	V _{D1, 2, 3} = 15V		Fig.4	-	0.08	0.4	mA
		V _{D4} = 15V			-	1.6	4.0	
High level Input voltage	V _{in H}	H _{IN1} , H _{IN2} , H _{IN3} , L _{IN1} , L _{IN2} , L _{IN3} to V _{SS}			2.5	-	-	V
Low level Input voltage	V _{in L}				-	-	0.8	V
Input threshold voltage hysteresis *2	V _{inth(hys)}				0.5	0.8	-	V
Logic 1 input leakage current	I _{IN+}	V _{IN} = +3.3V			-	100	143	μA
Logic 0 input leakage current	I _{IN-}	V _{IN} = 0V			-	-	2	μA
FAULT terminal sink current	I _{oSD}	FAULT : ON / V _{FAULT} = 0.1V			-	2	-	mA
FAULT clear time	FLTCLR	Fault output latch time			18	-	80	ms
V _{CC} and V _S undervoltage positive going threshold	V _{CCUV+} V _{SUV+}				10.5	11.1	11.7	V
V _{CC} and V _S undervoltage negative going threshold	V _{CCUV-} V _{SUV-}				10.3	10.9	11.5	V
V _{CC} and V _S undervoltage hysteresis	V _{CCUVH} V _{SUVH-}				0.14	0.2	-	V
Over current protection level	ISD	PW = 100μs, RSD = 0Ω		Fig.5	18.1	-	22.9	A
Electric current output signal level	ISO	I _o = 10A		-	0.31	0.33	0.35	V

Reference voltage is "VSS" terminal voltage unless otherwise specified.

*1 : The lower side's $V_{CE(SAT)}$ and V_F include a loss by the shunt resistance

*2 : Input threshold voltage hysteresis indicates a reference value based on the design value of built-in pre-driver IC

Electrical Characteristics at Tc = 25°C, VD1, VD2, VD3, VD4 = 15V, VCC = 300V, L = 3.9mH

Parameter	Symbol	Conditions	Test circuit	MIN	TYP	MAX	Unit	
Switching time	tON	Io = 10A	Fig.6	0.3	0.5	1.2	μs	
	tOFF			-	0.8	1.5		
Turn-on switching loss	Eon	Io = 5A		-	200	-	μJ	
Turn-off switching loss	Eoff			-	130	-	μJ	
Total switching loss	Etot			-	330	-	μJ	
Turn-on switching loss	Eon	Io = 5A, Tc = 100°C		-	240	-	μJ	
Turn-off switching loss	Eoff			-	130	-	μJ	
Total switching loss	Etot			-	370	-	μJ	
Diode reverse recovery energy	Erec	IF = 5A, P = 400V, Tc = 100°C			-	17	-	μJ
Diode reverse recovery time	trr				-	62	-	ns
Reverse bias safe operating area	RBSOA	Io = 20A, VCE = 450V		Full square				
Short circuit safe operating area	SCSOA	VCE = 400V, Tc = 100°C		4	-	-	μs	


Reference voltage is "VSS" terminal voltage unless otherwise specified.

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Notes:

- The pre-drive power supply low voltage protection has approximately 0.2V of hysteresis and operates as follows.
Upper side : The gate is turned off and will return to regular operation when recovering to the normal voltage, but the latch will continue till the input signal will turn 'high'.
Lower side : The gate is turned off and will automatically reset when recovering to normal voltage. It does not depend on input signal voltage.
- The pre-drive low voltage protection is the feature to protect devices when the pre-driver supply voltage falls due to an operating malfunction.

Equivalent Block Diagram



Module Pin-Out Description

Pin	Name	Description
1	VB3	High Side Floating Supply Voltage 3
2	W, VS3	Output 3 - High Side Floating Supply Offset Voltage
3	–	Without Pin
4	–	Without Pin
5	VB2	High Side Floating Supply voltage 2
6	V, VS2	Output 2 - High Side Floating Supply Offset Voltage
7	–	Without Pin
8	–	Without Pin
9	VB1	High Side Floating Supply voltage 1
10	U, VS1	Output 1 - High Side Floating Supply Offset Voltage
11	–	Without Pin
12	–	Without Pin
13	P	Positive Bus Input Voltage
14	–	Without Pin
15	–	Without Pin
16	N	Negative Bus Input Voltage
17	HIN1	Logic Input High Side Gate Driver - Phase U
18	HIN2	Logic Input High Side Gate Driver - Phase V
19	HIN3	Logic Input High Side Gate Driver - Phase W
20	LIN1	Logic Input Low Side Gate Driver - Phase U
21	LIN2	Logic Input Low Side Gate Driver - Phase V
22	LIN3	Logic Input Low Side Gate Driver - Phase W
23	FAULT	Fault output
24	ISO	Current monitor output
25	VDD	+15V Main Supply
26	VSS	Negative Main Supply
27	ISD	Over current detection and setting
28	RCIN	Fault clear time setting output
29	TH	Thermistor output

(The tested phase : U+ shows the upper side of the U phase and U- shows the lower side of the U phase.)

(The tested phase : U+ shows the upper side of the U phase and U- shows the lower side of the U phase.)

- $I_{CE} / I_{R(BD)}$

	U(BD)	V(BD)	W(BD)
M	9	5	1
N	26	26	26



- $V_{CE(SAT)}$ (Test by pulse)

Fig.2

- VF (Test by pulse)

Fig.3

- ID

Fig.4

■ ISD





Fig.5

■ Switching time (The circuit is a representative example of the lower side U phase.)





Fig.6

Input / Output Timing Chart





Fig. 7

Notes

- *1 : Diagram shows the prevention of shoot-through via control logic. More dead time to account for switching delay needs to be added externally.
- *2 : When V_{DD} decreases all gate output signals will go low and cut off all of 6 IGBT outputs. When V_{DD} rises the operation will resume immediately.
- *3 : When the upper side gate voltage at VB1, VB2 and VB3 drops only, the corresponding upper side output is turned off. The outputs return to normal operation immediately after the upper side gate voltage rises.
- *4 : In case of over current detection, all IGBT's are turned off and the FAULT output is asserted. Normal operation resumes in 18 to 80ms after the over current condition is removed.

Logic level table



INPUT			OUTPUT			
HIN	LIN	OCF	Upper IGBT	Lower IGBT	U,V,W	FAULT
H	L	OFF	ON	OFF	P	OFF
L	H	OFF	OFF	ON	N	OFF
L	L	OFF	OFF	OFF	High Impedance	OFF
H	H	OFF	OFF	OFF	High Impedance	OFF
X	X	ON	OFF	OFF	High Impedance	ON

Fig. 8

Sample Application Circuit




Fig.9

Recommended Operating Condition

Item	Symbol	Conditions	MIN	TYP	MAX	Unit
Supply voltage	V _{CC}	P to N	0	280	450	V
Pre-driver supply voltage	VD1,2,3	VB1 to U, VB2 to V, VB3 to W	12.5	15	17.5	V
	VD4	V _{DD} to V _{SS} *1	13.5	15	16.5	
PWM frequency	f _{PWM}		1	-	20	kHz
Dead time	DT	Turn-off to Turn-on	2	-	-	μs
Allowable input pulse width	PWIN	ON and OFF	1	-	-	μs
Tightening torque		'M3' type screw	0.6	-	0.9	Nm

*1 : Pre-drive power supply (VD4=15±1.5V) must have the capacity of I_o=20mA (DC), 0.5A (Peak).

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

Usage Precaution

1. This IPM includes bootstrap diode and resistors. Therefore, by adding a capacitor "CB", a high side drive voltage is generated; each phase requires an individual bootstrap capacitor. The recommended value of CB is in the range of 1 to 47μF, however this value needs to be verified prior to production. If selecting the capacitance more than 47μF (±20%), connect a resistor (about 20Ω) in series between each 3-phase upper side power supply terminals (VB1, 2, 3) and each bootstrap capacitor. When not using the bootstrap circuit, each upper side pre-drive power supply requires an external independent power supply.
2. It is essential that wiring length between terminals in the snubber circuit be kept as short as possible to reduce the effect of surge voltages. Recommended value of "CS" is in the range of 0.1 to 10μF.
3. "ISO" (pin24) is terminal for current monitor. High current may flow into that course when short-circuiting the "ISO" terminal and "V_{SS}" terminal. Please do not connect them.
4. "FAULT" (pin23) is open DRAIN output terminal (Active Low). Pull up resistor is recommended more than 6.8kΩ.
5. Inside the IPM, a thermistor used as the temperature monitor for internal substrate is connected between V_{SS} terminal and TH terminal therefore, an external pull up resistor connected between the TH terminal and an external power supply should be used. The temperature monitor example application is as follows, please refer the Fig.10, and Fig.11 below.
6. Pull down resistor of 33kΩ is provided internally at the signal input terminals. An external resistor of 2.2k to 3.3kΩ should be added to reduce the influence of external wiring noise.
7. The over current protection feature is not intended to protect in exceptional fault condition. An external fuse is recommended for safety.
8. The level of the over current protection might be changed from IPM design value when "ISD" terminal and "V_{SS}" terminal are shorted at external. Be confirm with actual application("N" terminal and "V_{SS}" terminal are shorted at internal).
9. The level of the over current protection is adjustable with the external resistor "RSD" between "ISD" terminal and "V_{SS}" terminal.
10. When input pulse width is less than 1.0μs, an output may not react to the pulse. (Both ON signal and OFF signal)

This data shows the example of the application circuit, does not guarantee a design as the mass production set.

The characteristic of thermistor

Parameter	Symbol	Condition	MIN	TYP	MAX	Unit
Resistance	R_{25}	$T_c = 25^{\circ}\text{C}$	99	100	101	k Ω
	R_{100}	$T_c = 100^{\circ}\text{C}$	5.18	5.38	5.60	k Ω
B-Constant (25 to 50 $^{\circ}\text{C}$)	B		4208	4250	4293	K
Temperature Range			-40	-	+125	$^{\circ}\text{C}$




Fig.10 Variation of thermistor resistance with temperature




Fig.11 Variation of thermistor terminal voltage with temperature
(39k Ω pull-up resistor, 5V)

CB capacitor value calculation for bootstrap circuit

Calculate conditions

Parameter	Symbol	Value	Unit
Upper side power supply.	VBS	15	V
Total gate charge of output power IGBT at 15V.	QG	89	nC
Upper limit power supply low voltage protection.	UVLO	12	V
Upper side power dissipation.	IDmax	400	μA
ON time required for CB voltage to fall from 15V to UVLO	TONmax	-	s

Capacitance calculation formula

Thus, the following formula are true

$$VBS \times CB - QG - IDMAX \times TONMAX = UVLO \times CB$$

therefore,

$$CB = (QG + IDMAX \times TONMAX) / (VBS - UVLO)$$

The relationship between TONMAX and CB becomes as follows. CB is recommended to be approximately 3 times the value calculated above. The recommended value of CB is in the range of 1 to 47μF, however, this value needs to be verified prior to production.




Fig. 12 Tonmax - CB characteristic

Package Dimensions


unit : mm

The tolerances of length are $\pm 0.5\text{mm}$ unless otherwise specified.

SIP29 44x26.5

CASE 127CH

ISSUE O



ORDERING INFORMATION

Device	Package	Shipping (Qty / Packing)
STK531U369A-E	SIP29 44x26.5 (Pb-Free)	11 / Tube

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.