Ordering number : ENN6085

Diffused Junction Type Silicon Diode






Varactor Diode for FM Receiver Electronic Tuning Use

Features


- · Low voltage (6.5V).
- Twin type varactor diode with good large-signal characteristics for FM receiver electronic tuning use.
- Very small package permits SVC234-applied sets to be compact and slim.
- Since available also in tape reel package, automatic insertion is supported.

Electrical Connection



Package Dimensions

unit : mm 1169A



Specifications

Absolute Maximum Ratings at Tc=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Reverse Voltage	٧R		16	V
Junction Temperature	Tj		125	°C
Storage Temperature	Tstg		−55 to +125	°C

Electrical Characteristics at Tc=25°C

Parameter	Symbol	Conditions	Ratings		Unit
i didilietei		Conditions	min	max	Offic
Breakdown Voltage	V(BR)R	I _R =10μA	16		V
Reverse Voltage	٧R	V _R =10V		50	nA
Interterminal Capacitance *	C _{1V}	V _R =1.0V, f=1MHz	62.02	68.79	pF
	C _{4.5} V	V _R =4.5V, f=1MHz	21.45	28.27	pF
	C _{6.5} V	V _R =6.5V, f=1MHz	13.42	16.03	pF
Quality Factor	Q	V _R =3.0V, f=100MHz	60		
Capacitance Ratio	CR	C _{1.0V} / C _{6.5V}	4.05	4.90	
Matching Tolerance	ΔCm	V_{R} =1.0, 4.5, 6.5V, f=1MHz ($C_{max} - C_{min}$) / C_{min}		0.03	

 \bigstar : Capacitance value per each diode.

Marking : SV


- Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.
- SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.

et4U.com


SVC234

Address and Capacitance Value [pF]

Address	C1.0V	Address	C3.0V	Address	C4.5V	Address	C6.5V
84	62.02 to 63.88	59	33.45 to 34.45	41	21.45 to 22.09	22	13.42 to 13.82
85	63.56 to 65.48	60	34.28 to 35.32	42	21.98 to 22.64	23	13.76 to 14.17
86	65.16 to 67.11	61	35.14 to 36.20	43	22.53 to 23.21	24	14.09 to 14.52
87	66.78 to 68.79	62	36.02 to 37.10	44	23.09 to 23.78	25	14.44 to 14.88
		63	36.92 to 38.02	45	23.67 to 24.38	26	14.81 to 15.26
		64	37.85 to 38.98	46	24.27 to 25.00	27	15.18 to 15.64
		65	38.79 to 39.96	47	24.87 to 25.61	28	15.56 to 16.03
				48	25.50 to 26.26		
				49	26.13 to 26.92		
				50	26.78 to 27.59		
				51	27.45 to 28.27		



www.DataSheet4U.com



- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of April, 2001. Specifications and information herein are subject to change without notice.

www.DataSheet4U.com