

SP4T RF Switch, 10 - 1000 MHz


**SW-124-PIN
V3**

Features

- Low Loss: 0.6 dB Typical
- High Isolation: 60 dB Typical
- Integral TTL Driver
- Hermetic Package
- 50 Ohm Nominal Impedance
- MIL-STD-883 Screening Available

Description

Functional Block Diagram



Dimensions in () are in mm
 Unless Otherwise Noted: .XXX = ±0.010 (.XX = ±0.25)
 .XX = ±0.02 (X = ±0.5)
 WEIGHT (APPROX): 0.28 OUNCES 8 GRAMS

Ordering Information

Part Number	Package
SW-124-PIN	DI-2

Note: Reference Application Note M513 for reel size information.

Note: Die quantity varies.

Truth Table

TTL Control Inputs "1" = TTL Logic High				Condition of Switch RF Common to each RF Port			
1	2	3	4	RF1	RF2	RF3	RF4
1	0	0	0	On	Off	Off	Off
0	1	0	0	Off	On	Off	Off
0	0	1	0	Off	Off	On	Off
0	0	0	1	Off	Off	Off	On

* Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

**SP4T RF Switch,
10 - 1000 MHz**
**SW-124-PIN
V3**
Electrical Specifications: $T_A = -55^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ ¹

Parameter	Test Conditions	Frequency	Units	Min	Typ	Max
Insertion Loss	—	10 - 1000 MHz 10 - 500 MHz	dB dB	— —	— —	1.4 1.0
VSWR	—	10 - 1000 MHz 10 - 500 MHz	Ratio Ratio	— —	— —	1.5:1 1.2:1
Isolation	—	10 - 1000 MHz 10 - 500 MHz 10 - 100 MHz	dB dB dB	40 50 60	— — —	— — —
Ton Toff Transients	In-band	— — —	μS μS mV	— — —	2.0 1.0 40	— — —
1 dB Compression	Input Power	—	dBm	—	+13	—
IP ₂	For two tone input power up to +5 dBm	—	dBm	—	+60	—
IP ₃	For two tone input power up to +5 dBm	—	dBm	—	+30	—
Bias Power	+9 to +15 VDC @ 50 mA Max -5 VDC $\pm$ 5% @ 25 mA Max	—	mW	—	450	—


1. All specifications apply when operated with bias voltages of +12 VDC and -5 VDC ($\pm$ 5%) and 50 ohm impedance at all RF ports.

**SP4T RF Switch,
10 - 1000 MHz**


**SW-124-PIN
V3**

Typical Performance Curves

Insertion Loss



Isolation



VSWR

