




N- and P-Channel for Level Shift Load Switch


PRODUCT SUMMARY

	V_{DS} (V)	$R_{DS(on)}$ (Ω)	I_D (A)	Q_g (Typ.)
N-Channel	20	0.225 at $V_{GS} = 4.5$ V	1.5 ^a	1.1 nC
		0.270 at $V_{GS} = 2.5$ V	1.5 ^a	
		0.345 at $V_{GS} = 1.8$ V	1.5 ^a	
		0.960 at $V_{GS} = 1.5$ V	0.5	
P-Channel	- 12	0.057 at $V_{GS} = - 4.5$ V	- 4.5 ^a	5 nC
		0.077 at $V_{GS} = - 2.5$ V	- 4.5 ^a	
		0.115 at $V_{GS} = - 1.8$ V	- 4.5 ^a	
		0.200 at $V_{GS} = - 1.5$ V	- 1.5	

PowerPAK® SC-70-6 Dual



Marking Code



Ordering Information: SiA777EDJ-T1-GE3 (Lead (Pb)-free and Halogen-free)

FEATURES


- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFETs
- Typical ESD Protection: N-Channel 2800 V P-Channel 1900 V
- 100 % R_g Tested
- Compliant to RoHS Directive 2002/95/EC

APPLICATIONS

- Load Switch with Level Shift for Portable Devices
 - N-Channel for Level Shift Drive
 - P-Channel for Main Switch



RoHS
COMPLIANT
HALOGEN
FREE



ABSOLUTE MAXIMUM RATINGS $T_A = 25^\circ\text{C}$, unless otherwise noted

Parameter		Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage		V _{DS}	20	- 12	V
Gate-Source Voltage		V _{GS}	± 6	± 8	
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	I _D	1.5 ^a	- 4.5 ^a	A
	T _C = 70 °C		1.5 ^a	- 4.5 ^a	
	T _A = 25 °C		1.5 ^{a, b, c}	- 4.5 ^{a, b, c}	
	T _A = 70 °C		1.5 ^{a, b, c}	- 3.9 ^{b, c}	
Pulsed Drain Current		I _{DM}	4	- 15	
Source Drain Current Diode Current	T _C = 25 °C	I _S	1.5 ^a	- 4.5 ^a	
	T _A = 25 °C		1.6 ^{b, c}	- 1.6 ^{b, c}	
Maximum Power Dissipation	T _C = 25 °C	P _D	5	7.8	W
	T _C = 70 °C		3.2	5	
	T _A = 25 °C		1.9 ^{b, c}	1.9 ^{b, c}	
	T _A = 70 °C		1.2 ^{b, c}	1.2 ^{b, c}	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	- 55 to 150		°C
Soldering Recommendations (Peak Temperature) ^{d, e}			260		

THERMAL RESISTANCE RATINGS

Parameter	Symbol	N-Channel		P-Channel		Unit
		Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^{b, f}	R_{thJA}	52	65	52	65	$^\circ\text{C}/\text{W}$
Maximum Junction-to-Case (Drain)	R_{thJC}	20	25	12.5	16	

Notes:

a. Package limited.

b. Surface mounted on 1" x 1" FR4 board.

c. $t = 5$ s.d. See solder profile (www.vishay.com/ppg?73257). The PowerPAK SC-70 is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.

e. Rework Conditions: manual soldering with a soldering iron is not recommended for leadless components.

f. Maximum under steady state conditions for channel 1 and channel 2 is 110 $^\circ\text{C}/\text{W}$.

SPECIFICATIONS T _J = 25 °C, unless otherwise noted								
Parameter	Symbol	Test Conditions		Min.	Typ.	Max.	Unit	
Static								
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	N-Ch	20			V	
		V _{GS} = 0 V, I _D = - 250 μA	P-Ch	- 12				
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA	N-Ch		21		mV/°C	
		I _D = - 250 μA	P-Ch		- 3			
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J	I _D = 250 μA	N-Ch		- 2.3			
		I _D = - 250 μA	P-Ch		2.3			
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	N-Ch	0.4		1.0	V	
		V _{DS} = V _{GS} , I _D = - 250 μA	P-Ch	- 0.4		- 1		
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 3 V	N-Ch			± 1	μA	
		V _{DS} = 0 V, V _{GS} = ± 4.5 V	P-Ch			± 0.5		
		V _{DS} = 0 V, V _{GS} = ± 6 V	N-Ch			± 1	mA	
		V _{DS} = 0 V, V _{GS} = ± 8 V	P-Ch			± 3		
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V	N-Ch			1	μA	
		V _{DS} = - 12 V, V _{GS} = 0 V	P-Ch			- 1		
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55 °C	N-Ch			10		
		V _{DS} = - 12 V, V _{GS} = 0 V, T _J = 55 °C	P-Ch			- 10		
On-State Drain Current ^b	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 4.5 V	N-Ch	4			A	
		V _{DS} ≤ - 5 V, V _{GS} = - 4.5 V	P-Ch	- 10				
Drain-Source On-State Resistance ^b	R _{DS(on)}	V _{GS} = 4.5 V, I _D = 1.6 A	N-Ch		0.183	0.225	Ω	
		V _{GS} = - 4.5 V, I _D = - 3.8 A	P-Ch		0.047	0.057		
		V _{GS} = 2.5 V, I _D = 1.5 A	N-Ch		0.220	0.270		
		V _{GS} = - 2.5 V, I _D = - 3.3 A	P-Ch		0.063	0.077		
		V _{GS} = 1.8 V, I _D = 1.3 A	N-Ch		0.275	0.345		
		V _{GS} = - 1.8 V, I _D = 2.6 A	P-Ch		0.095	0.115		
		V _{GS} = 1.5 V, I _D = 0.3 A	N-Ch		0.320	0.960		
		V _{GS} = - 1.5 V, I _D = 1 A	P-Ch		0.125	0.200		
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 1.6 A	N-Ch		3.5		S	
		V _{DS} = - 10 V, I _D = - 3.8 A	P-Ch		11			
Dynamic ^a								
Total Gate Charge	Q _g	V _{DS} = 10 V, V _{GS} = 5 V, I _D = 1.7 A	N-Ch		1.3	2.2	nC	
		V _{DS} = - 6 V, V _{GS} = - 8 V, I _D = - 4.9 A	P-Ch		7.5	12		
		N-Channel V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 1.7 A	N-Ch		1.1	1.7		
			P-Ch		5	8		
Gate-Source Charge	Q _{gs}	P-Channel V _{DS} = - 6 V, V _{GS} = - 4.5 V, I _D = - 4.9 A	N-Ch		0.2			
			P-Ch		0.6			
Gate-Drain Charge	Q _{gd}		N-Ch		0.1			
			P-Ch		1.8			
Gate Resistance	R _g	f = 1 MHz	N-Ch	40	200	400	Ω	
			P-Ch	2	10	20		

Notes:

a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.









SPECIFICATIONS $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise noted							
Parameter	Symbol	Test Conditions		Min.	Typ.	Max.	Unit
Dynamic ^a							
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 10\text{ V}$, $R_L = 7.7\text{ }\Omega$ $I_D \cong 1.3\text{ A}$, $V_{GEN} = 4.5\text{ V}$, $R_g = 1\text{ }\Omega$	N-Ch		20	30	ns
			P-Ch		20	30	
Rise Time	t_r		N-Ch		12	20	
			P-Ch		20	30	
Turn-Off Delay Time	$t_{d(off)}$	N-Ch		70	105		
		P-Ch		32	50		
Fall Time	t_f	N-Ch		20	30		
		P-Ch		16	25		
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I_S	$T_C = 25\text{ }^{\circ}\text{C}$	N-Ch			1.5	A
			P-Ch			- 4.5	
Pulse Diode Forward Current ^a	I_{SM}		N-Ch			4	
			P-Ch			- 15	
Body Diode Voltage	V_{SD}	$I_S = 1.3\text{ A}$, $V_{GS} = 0\text{ V}$	N-Ch		0.9	1.2	V
		$I_S = - 3.9\text{ A}$, $V_{GS} = 0\text{ V}$	P-Ch		- 0.8	- 1.2	
Body Diode Reverse Recovery Time	t_{rr}	N-Channel $I_F = 1.3\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$, $T_J = 25\text{ }^{\circ}\text{C}$	N-Ch		50	75	ns
			P-Ch		45	70	
Body Diode Reverse Recovery Charge	Q_{rr}		N-Ch		30	45	nC
			P-Ch		25	40	
Reverse Recovery Fall Time	t_a	P-Channel $I_F = - 3.9\text{ A}$, $di/dt = - 100\text{ A}/\mu\text{s}$, $T_J = 25\text{ }^{\circ}\text{C}$	N-Ch		15		ns
			P-Ch		15		
Reverse Recovery Rise Time	t_b		N-Ch		35		
			P-Ch		30		







Notes:

a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.



Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted

Gate Current vs. Gate-to-Source Voltage

Gate Current vs. Gate-to-Source Voltage

Output Characteristics

Transfer Characteristics

On-Resistance vs. Drain Current

Gate Charge




N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, unless otherwise noted

Normalized On-Resistance vs. Junction Temperature

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Single Pulse Power, Junction-to-Ambient

Threshold Voltage

Safe Operating Area, Junction-to-Ambient







SiA777EDJ







Vishay Siliconix




**N-CHANNEL TYPICAL CHARACTERISTICS** $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted

* The power dissipation P_D is based on $T_{J(max)} = 150\text{ }^{\circ}\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.




N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Case

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Gate Current vs. Gate-Source Voltage****Gate Current vs. Gate-Source Voltage****Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current and Gate Voltage****Capacitance**


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified**Safe Operating Area, Junction-to-Ambient**

* The power dissipation P_D is based on $T_{J(max)} = 150\text{ }^{\circ}\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Case

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg265371.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.