



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: SAW Filter 1220 MHz

TST Parts No.:TA0194A

Customer Parts No.:_____

Company:_____

Division:_____

Approved by :_____

Date:_____

Checked by:_____ Andy Lee

Approval by:_____ Francis Chen

Date:_____ 2005/2/18



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 1220 MHz SMD 3.8X3.8mm

MODEL NO.: TA0194A

REV. NO.5

A. MAXIMUM RATING:

1. Operating Temperature: -40°C ~ +85°C

2. Storage Temperature: -40°C ~ +85°C

B. Characteristics :


Balanced to Balanced operation

Terminating source impedance : $Z_s = 200 \Omega$

Terminating load impedance : $Z_L = 200 \Omega$


Characteristics	Value			Note
	Min.	Typ.	Max.	
Center frequency F_c MHz	-	1220	-	-
Insertion loss(1216~1224 MHz) I.L. dB	-	3.7	4.8	-
Ripple (1216~1224MHz) dB	-	0.8	1.5	-
Attenuation:(Reference level from 0 dB)				
1)500.. F_c -93 MHz dB	50	60	-	-
2) F_c -93... F_c -85 MHz dB	46	53	-	-
3) F_c -85... F_c -68 MHz dB	46	53	-	-
5) F_c -88 MHz dB	50	55	-	-
6) F_c -72 MHz dB	48	65	-	-
7) F_c -44 MHz dB	50	54	-	-
8) F_c -36 MHz dB	46	62	-	-
9) F_c +70...2000 MHz dB	50	61	-	-
Group delay ripple(p-p) (1216~1224MHz) nS	-	40	-	

C. Measurement Circuit:




D. Frequency Characteristics :


1. Sdd21 Response




2. Sdd21 Response (Inband)



3. Sdd21 Response (wideband)




E. Outline Drawing:



pin 1, 2 : Balance input, Balanced input return
pin 5, 6 : Balanced output, Blanced output return
pin 3,4,7,8 : To be Ground
□ : Date code
Unit: mm

F. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION

