

# TCR4DG series

## 420 mA CMOS Low Drop-Out Regulator with inrush current protection circuit


The TCR4DG series are CMOS general-purpose single-output voltage regulators with an on/off control input, featuring low dropout voltage, low output noise voltage and low inrush current.

These voltage regulators are available in fixed output voltages between 1.0 V and 4.5 V and capable of driving up to 420 mA.

They feature over-current protection, over-temperature protection, Inrush current protection circuit and Auto-discharge function.

The TCR4DG series are offered in the ultra small plastic mold package WCSP4E (0.645 mm x 0.645 mm; t 0.43 mm (max)). It has a low dropout voltage of 193 mV (3.3 V output,  $I_{OUT} = 420$  mA) with low output noise voltage of 38  $\mu V_{rms}$  (2.5 V output) and a load transient response of only  $\Delta V_{OUT} = \pm 115$  mV (  $I_{OUT} = 1$  mA  $\Leftrightarrow$  420 mA,  $C_{OUT} = 1.0$   $\mu F$  ).

As small ceramic input and output capacitors can be used with the TCR4DG series, these devices are ideal for portable applications that require high-density board assembly such as cellular phones.



Weight: 0.34 mg ( typ.)

### Features

- Low Drop-Out voltage  
 $V_{DO} = 193$  mV (typ.) at 3.3 V-output,  $I_{OUT} = 420$  mA
- Low output noise voltage  
 $V_{NO} = 38$   $\mu V_{rms}$  (typ.) at 2.5 V-output,  $I_{OUT} = 10$  mA,  $10$  Hz  $\leq f \leq 100$  kHz
- Fast load transient response ( $\Delta V_{OUT} = \pm 115$  mV (typ.) at  $I_{OUT} = 1 \Leftrightarrow 420$  mA,  $C_{OUT} = 1.0$   $\mu F$  )
- High ripple rejection ( R.R = 70 dB (typ.) at 2.5 V-output,  $I_{OUT} = 10$  mA,  $f = 1$  kHz )
- Over-current protection
- Over-temperature protection
- Inrush current protection circuit
- Auto-discharge function
- Pull down connection between CONTROL and GND
- Ceramic capacitors can be used (  $C_{IN} = 1.0$   $\mu F$ ,  $C_{OUT} = 1.0$   $\mu F$  )
- Ultra small package WCSP4E (0.645 mm x 0.645 mm ; t 0.43 mm (max))

Start of commercial production  
2017-04

## Absolute Maximum Ratings (Ta = 25°C)

| Characteristics             | Symbol           | Rating      | Unit |
|-----------------------------|------------------|-------------|------|
| Input voltage               | V <sub>IN</sub>  | 6.0         | V    |
| Control voltage             | V <sub>CT</sub>  | -0.3 to 6.0 | V    |
| Output current              | I <sub>OUT</sub> | 420         | mA   |
| Power dissipation           | P <sub>D</sub>   | 800 (Note1) | mW   |
| Operation temperature range | T <sub>opr</sub> | -40 to 85   | °C   |
| Junction temperature        | T <sub>j</sub>   | 150         | °C   |
| Storage temperature range   | T <sub>stg</sub> | -55 to 150  | °C   |

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note1: Rating at mounting on a board


Board material: Glass epoxy(FR4)

Board dimension: 40 mm x 40 mm (both sides of board), t = 1.6 mm

Metal pattern ratio: a surface approximately 50%, the reverse side approximately 50%

Through hole: diameter 0.5 mm x 24

## Pin Assignment (Top view)



|   | 1               | 2                |
|---|-----------------|------------------|
| A | V <sub>IN</sub> | V <sub>OUT</sub> |
| B | CONTROL         | GND              |


## List of Products Number, Output voltage and Marking

| Product No. | Output voltage<br>(V)(typ.) | Marking | Product No. | Output voltage<br>(V)(typ.) | Marking |
|-------------|-----------------------------|---------|-------------|-----------------------------|---------|
| TCR4DG10    | 1.0                         | A       | TCR4DG25    | 2.5                         | T       |
| TCR4DG105   | 1.05                        | B       | TCR4DG27    | 2.7                         | U       |
| TCR4DG11    | 1.1                         | C       | TCR4DG275   | 2.75                        | V       |
| TCR4DG115   | 1.15                        | D       | TCR4DG28    | 2.8                         | W       |
| TCR4DG12    | 1.2                         | E       | TCR4DG285   | 2.85                        | X       |
| TCR4DG125   | 1.25                        | F       | TCR4DG29    | 2.9                         | Y       |
| TCR4DG13    | 1.3                         | H       | TCR4DG30    | 3.0                         | 0       |
| TCR4DG135   | 1.35                        | J       | TCR4DG31    | 3.1                         | 1       |
| TCR4DG15    | 1.5                         | K       | TCR4DG32    | 3.2                         | 2       |
| TCR4DG175   | 1.75                        | L       | TCR4DG325   | 3.25                        | 3       |
| TCR4DG18    | 1.8                         | M       | TCR4DG33    | 3.3                         | 4       |
| TCR4DG185   | 1.85                        | N       | TCR4DG35    | 3.5                         | 5       |
| TCR4DG19    | 1.9                         | P       | TCR4DG36    | 3.6                         | 6       |
| TCR4DG23    | 2.3                         | R       | TCR4DG42    | 4.2                         | 7       |
| TCR4DG245   | 2.45                        | S       | TCR4DG45    | 4.5                         | 8       |

Note: Please ask your local retailer about the devices with other output voltages.

## Top Marking (top view)

Example: TCR4DG10 (1.0 V output)



## Electrical Characteristics

(Unless otherwise specified,  $V_{IN} = V_{OUT} + 1\text{ V}$ ,  $I_{OUT} = 50\text{ mA}$ ,  $C_{IN} = 1.0\text{ }\mu\text{F}$ ,  $C_{OUT} = 1.0\text{ }\mu\text{F}$ ,  $T_j = 25^\circ\text{C}$ )

| Characteristics         | Symbol                | Test Condition                                                                                                                                              |                          | Min                                | Typ. | Max  | Unit              |
|-------------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------|------|------|-------------------|
| Output voltage accuracy | V <sub>OUT</sub>      | I <sub>OUT</sub> = 50 mA (Note 2)                                                                                                                           | V <sub>OUT</sub> < 1.8 V | -18                                | —    | +18  | mV                |
|                         |                       |                                                                                                                                                             | 1.8 V ≤ V <sub>OUT</sub> | -1.0                               | —    | +1.0 | %                 |
| Input voltage           | V <sub>IN</sub>       | I <sub>OUT</sub> = 1 mA (Note 3)                                                                                                                            |                          | V <sub>OUT</sub> + V <sub>DO</sub> | —    | 5.5  | V                 |
| Line regulation         | Reg·line              | V <sub>OUT</sub> + 0.5 V ≤ V <sub>IN</sub> ≤ 5.5 V, I <sub>OUT</sub> = 1 mA                                                                                 |                          | —                                  | 1    | 15   | mV                |
| Load regulation         | Reg·load              | 1 mA ≤ I <sub>OUT</sub> ≤ 420 mA                                                                                                                            |                          | —                                  | 6    | 35   | mV                |
| Quiescent current       | I <sub>B</sub>        | I <sub>OUT</sub> = 0 mA                                                                                                                                     | V <sub>OUT</sub> = 1.0 V | —                                  | 65   | —    | μA                |
|                         |                       |                                                                                                                                                             | V <sub>OUT</sub> = 1.8 V | —                                  | 65   | —    |                   |
|                         |                       |                                                                                                                                                             | V <sub>OUT</sub> = 2.5 V | —                                  | 68   | —    |                   |
|                         |                       |                                                                                                                                                             | V <sub>OUT</sub> = 4.5 V | —                                  | 78   | 125  |                   |
| Stand-by current        | I <sub>B</sub> (OFF)  | V <sub>CT</sub> = 0 V                                                                                                                                       |                          | —                                  | 0.1  | 1    | μA                |
| Drop-out voltage        | V <sub>DO</sub>       | I <sub>OUT</sub> = 420 mA (Note 4)                                                                                                                          |                          | —                                  | 193  | 263  | mV                |
| Temperature coefficient | T <sub>CVO</sub>      | -40°C ≤ T <sub>opr</sub> ≤ 85°C                                                                                                                             |                          | —                                  | 75   | —    | ppm/°C            |
| Output noise voltage    | V <sub>NO</sub>       | V <sub>IN</sub> = V <sub>OUT</sub> + 1 V, I <sub>OUT</sub> = 10 mA, 10 Hz ≤ f ≤ 100 kHz, T <sub>a</sub> = 25°C (Note 5)                                     |                          | —                                  | 38   | —    | μV <sub>rms</sub> |
| Ripple rejection ratio  | R.R.                  | V <sub>IN</sub> = V <sub>OUT</sub> + 1 V, I <sub>OUT</sub> = 10 mA, f = 1 kHz, V <sub>Ripple</sub> = 500 mV <sub>p-p</sub> , T <sub>a</sub> = 25°C (Note 5) |                          | —                                  | 70   | —    | dB                |
| Load transient response | ΔV <sub>OUT</sub>     | I <sub>OUT</sub> = 1 ⇔ 420 mA, C <sub>OUT</sub> = 1.0 μF                                                                                                    |                          | —                                  | ±115 | —    | mV                |
| Control voltage (ON)    | V <sub>CT</sub> (ON)  | —                                                                                                                                                           |                          | 1.0                                | —    | 5.5  | V                 |
| Control voltage (OFF)   | V <sub>CT</sub> (OFF) | —                                                                                                                                                           |                          | 0                                  | —    | 0.4  | V                 |

Note 2: Stable state with fixed  $I_{OUT}$  condition.

Note 3: Please refer to Dropout Voltage table (Page 4), and use it within the limits of absolute maximum rating  $T_{opr}$  and  $T_j$ .

Note 4: The 3.3 V output product. Dropout voltage is the voltage difference between the  $V_{IN}$  and  $V_{OUT}$  at which  $V_{OUT}$  drops to 2% below its nominal value.

Note 5: The 2.5 V output product.


## Drop-out voltage

( $I_{OUT} = 420\text{ mA}$ ,  $C_{IN} = 1.0\text{ }\mu\text{F}$ ,  $C_{OUT} = 1.0\text{ }\mu\text{F}$ ,  $T_j = 25^\circ\text{C}$ )

| Output voltages                               | Symbol   | Min | Typ. | Max | Unit |
|-----------------------------------------------|----------|-----|------|-----|------|
| 1.0 V, 1.05 V                                 | $V_{DO}$ | —   | 767  | 991 | mV   |
| 1.1 V, 1.15V                                  |          | —   | 711  | 851 |      |
| 1.2 V, 1.25V                                  |          | —   | 627  | 781 |      |
| 1.3 V                                         |          | —   | 571  | 711 |      |
| 1.35 V                                        |          | —   | 515  | 683 |      |
| 1.4 V                                         |          | —   | 487  | 669 |      |
| $1.5\text{ V} \leq V_{OUT} < 1.8\text{ V}$    |          | —   | 431  | 571 |      |
| $1.8\text{ V} \leq V_{OUT} < 2.1\text{ V}$    |          | —   | 319  | 473 |      |
| $2.1\text{ V} \leq V_{OUT} < 2.5\text{ V}$    |          | —   | 277  | 403 |      |
| $2.5\text{ V} \leq V_{OUT} < 2.8\text{ V}$    |          | —   | 235  | 347 |      |
| $2.8\text{ V} \leq V_{OUT} < 3.2\text{ V}$    |          | —   | 221  | 291 |      |
| $3.2\text{ V} \leq V_{OUT} < 3.6\text{ V}$    |          | —   | 193  | 263 |      |
| $3.6\text{ V} \leq V_{OUT} \leq 4.5\text{ V}$ |          | —   | 151  | 221 |      |

Application Note

1. Recommended Application Circuit




The figure above shows the recommended configuration for using a Low-Dropout regulator. Insert a capacitor at VOUT and VIN pins for stable input/output operation. (Ceramic capacitors can be used).

2. Power Dissipation

Board-mounted power dissipation ratings for TCR4DG series are available in the Absolute Maximum Ratings table. Power dissipation is measured on the board condition shown below.

[The Board Condition]  
Board material: Glass epoxy(FR4)  
Board dimension: 40mm x 40mm (both sides of board), t= 1.6mm  
Metal pattern ratio: a surface approximately 50%, the reverse side approximately 50%  
Through hole hall: diameter 0.5mm x 24







**Attention in Use**



- **Output Capacitors**  
Ceramic capacitors can be used for these devices. However, because of the type of the capacitors, there might be unexpected thermal features. Please consider application condition for selecting capacitors. And Toshiba recommend the ESR of ceramic capacitor is under 10  $\Omega$ .
- **Mounting**  
The long distance between IC and output capacitor might affect phase assurance by impedance in wire and inductor. For stable power supply, output capacitor need to mount near IC as much as possible. Also VIN and GND pattern need to be large and make the wire impedance small as possible.
- **Permissible Loss**  
Please have enough design patterns for expected maximum permissible loss. And under consideration of surrounding temperature, input voltage, and output current etc, we recommend proper dissipation ratings for maximum permissible loss; in general maximum dissipation rating is 70 to 80 percent.
- **Over current Protection and Thermal shut down function**  
Over current protection and Thermal shut down function are designed in these products, but these are not designed to constantly ensure the suppression of the device within operation limits. Depending on the condition during actual usage, it could affect the electrical characteristic specification and reliability. Also note that if output pins and GND pins are not completely shorted out, these products might be break down.  
When using these products, please read through and understand the concept of dissipation for absolute maximum ratings from the above mention or our 'Semiconductor Reliability Handbook'. Then use these products under absolute maximum ratings in any condition. Furthermore, Toshiba recommend inserting failsafe system into the design.

## Representative Typical Characteristics





### Quiescent Current vs. Input Voltage





### Quiescent Current vs. Ambient Temperature





## Ripple Rejection Ratio vs. Frequency



## Output Voltage vs. Output Current






Note: The above characteristics curves are presented for reference only and not guaranteed by production test, unless otherwise noted.

Package Dimensions

WCSP4E

Unit: mm



Weight: 0.34 mg ( typ.)

**RESTRICTIONS ON PRODUCT USE**

- Toshiba Corporation, and its subsidiaries and affiliates (collectively "TOSHIBA"), reserve the right to make changes to the information in this document, and related hardware, software and systems (collectively "Product") without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**