



Description

The TD3021 consists of a single input AlGaAs LED optically coupled to a Random Phase triac driver chip. The TD3021 provides high input-to-output isolation and is designed to drive high-powered triacs. Typical uses include interfacing logic level control signals to equipment powered from 110V_{AC} lines and higher.

The TD3021 comes standard in a miniature 6 pin DIP package making it ideal for high-density board applications.


Features

- Random Phase Switching
- 400V Blocking Voltage
- Trigger Current (15mA MAX)
- High Isolation Voltage (5000V_{RMS})
- High dV/dt (1kV/μS MIN)
- Long Life / High Reliability
- RoHS / Pb-Free / REACH Compliant

Applications

- Home Appliances
- Motor / Drive Controls
- Solid State Relays
- Solenoid / Valve Controls
- Temperature Controls
- Dimmer Controls

Schematic Diagram



Agency Approvals

UL/C-UL: File # E201932
VDE: File # 40035191 (EN 60747-5-2)

Absolute Maximum Ratings

The values indicated are absolute stress ratings. Functional operation of the device is not implied at these or any conditions in excess of those defined in electrical characteristics section of this document. Exposure to absolute Maximum Ratings may cause permanent damage to the device and may adversely affect reliability.

Storage Temperature-55 to +125°C
Operating Temperature-40 to +100°C
Continuous Input Current.....50mA
Transient Input Current.....400mA
Reverse Input Control Voltage5V
Input Power Dissipation.....40mW
Output Power Dissipation330mW
Solder Temperature – Wave (10sec).....260°C
Solder Temperature – IR Reflow (10sec).....260°C

Ordering Information

Part Number	Description
TD3021	6 pin DIP, (60/Tube)
TD3021-H	0.40" (10.16mm) Lead Spacing (VDE0884)
TD3021-S	6 pin SMD, (60/Tube)
TD3021-STR	6 pin SMD, Tape and Reel (1000/Reel)


NOTE: Suffixes listed above are not included in marking on device for part number identification






Electrical Characteristics, $T_A = 25^\circ\text{C}$ (unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Input Specifications						
LED Forward Voltage	V_F	-	1.4	1.8	V	$I_F = 10\text{mA}$
LED Reverse Voltage	BV_R	5	-	-	V	$I_R = 10\mu\text{A}$
Reverse Leakage Current	I_{nRleak}	-	-	10	μA	$V_R = 5\mu\text{A}$
Trigger Current ¹	I_{InOn}	-	-	15	mA	Main Terminal Voltage = 3V
Output Specifications						
Blocking Voltage	V_{DRM}	400	-	-	V	$I_O = 1\mu\text{A}$
Peak Blocking Current	I_{DRM1}	-	10	100	nA	$V_{DRM} = 400$
Continuous Load Current	I_O	-	-	100	mA	$I_F = 15\text{mA}$
On-State Voltage	V_{ON}	-	2	3	V	$I_F = 15\text{mA}$, $I_{TM} = 100\text{mA}$
Leakage Current	I_{DRM2}	-	0.2	1	μA	$I_F = 0\text{mA}$, $V_{DRM} = 400\text{V}$
Holding Current	I_{HOLD}	-	250	-	μA	-
Critical Rate of Rise ²	dV/dt	1,000	1,500	-	$\text{V}/\mu\text{S}$	-
Isolation Specifications						
Isolation Voltage	V_{ISO}	5,000	-	-	V_{RMS}	$RH \leq 50\%$, $t=1\text{min}$
Input-Output Resistance	R_{I-O}	-	10^{12}	-	Ω	$V_{I-O} = 500V_{DC}$

Note 1: Resistive load. For inductive loads, higher drive current is recommended

Note 2: This is for static dV/dt . Test Circuit Below

TD3021 Static dV/dt Test Circuit:


TD3021 Performance & Characteristics Plots, $T_A = 25^\circ\text{C}$ (unless otherwise specified)
Figure 1: Maximum Load Current vs. Temperature

Figure 2: Typical Blocking Voltage Distribution (N = 100, $T_A = 25^\circ\text{C}$)

Figure 3: On-State Characteristics

Figure 4: Leakage Current (I_{OLEAK}) vs. Temperature ($^\circ\text{C}$)

Figure 5: Turn On Current (I_T) vs. Temperature ($^\circ\text{C}$)


TD3021 Solder Temperature Profile Recommendations

(1) Infrared Reflow:

Refer to the following figure as an example of an optimal temperature profile for single occurrence infrared reflow. Soldering process should not exceed temperature or time limits expressed herein. Surface temperature of device package should not exceed 250°C:




Figure 1

Process Step	Description	Parameter
A	Preheat Start Temperature (°C)	150°C
B	Preheat Finish Temperature (°C)	180°C
C	Preheat Time (s)	90 - 120s
D	Melting Temperature (°C)	230°C
E	Time above Melting Temperature (s)	30s
F	Peak Temperature, at Terminal (°C)	260°C
G	Dwell Time at Peak Temperature (s)	10s
H	Cool-down (°C/s)	<6°C/s

(2) Wave Solder:




Maximum Temperature: 260°C (at terminal)
Maximum Time: 10s
Pre-heating: 100 - 150°C (30 - 90s)
Single Occurrence

(3) Hand Solder:

Maximum Temperature: 350°C (at tip of soldering iron)
Maximum Time: 3s
Single Occurrence




TD3021 Package Dimensions

6 PIN DIP Package

Note: All dimensions in millimeters with inches ["] in parenthesis ()






TD3021 Package Dimensions

6 PIN WIDE Lead Space Package (-H)

Note: All dimensions in millimeters [mm] with inches in parenthesis ()



TD3021 Package Dimensions

6 PIN SMD Surface Mount Package (-S)


Note: All dimensions in millimeters with inches ["] in parenthesis ()


TD3021 Package Dimensions

6 PIN SMD Tape & Reel (-STR)


Note: All dimensions in millimeters


W	B	B1	P	P1	K	E	T	D	D1
16.00 ±0.1	10.50 ±0.1	10.30 ±0.1	12.00 ±0.1	4.00 ±0.1	5.00 ±0.1	1.75 ±0.1	0.40 ±0.1	1.50 ±0.1	1.50 ±0.1



L	M	N	O	Q	R	S
330.00	100.00	16.40 ±0.2	2.00 ±0.1	13.00 ±0.2	2.00	10.00

TD3021 Package Marking



TD3021 Package Weights

Device	Single Unit	Full Tube (60pcs)	Full Pouch (10 tubes)	Full Reel (1000pcs)
TD3021	0.41	43	450	-
TD3021-S	0.40	42	440	-
TD3021-H	0.42	44	460	
TD3021-STR	0.40	-	-	880

Note: All weights above are in GRAMS, and include packaging materials where applicable

DISCLAIMER

Solid State Optronics (SSO) makes no warranties or representations with regards to the completeness and accuracy of this document. SSO reserves the right to make changes to product description, specifications at any time without further notices.

SSO shall not assume any liability arising out of the application or use of any product or circuit described herein. Neither circuit patent licenses nor indemnity are expressed or implied.

Except as specified in SSO's Standard Terms & Conditions, SSO disclaims liability for consequential or other damage, and we make no other warranty, expressed or implied, including merchantability and fitness for particular use.

LIFE SUPPORT POLICY

SSO does not authorize use of its devices in life support applications wherein failure or malfunction of a device may lead to personal injury or death. Users of SSO devices in life support applications assume all risks of such use and agree to indemnify SSO against any and all damages resulting from such use. Life support devices are defined as devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when used properly in accordance with instructions for use can be reasonably expected to result in significant injury to the user, or (d) a critical component of a life support device or system whose failure can be reasonably expected to cause failure of the life support device or system, or to affect its safety or effectiveness.