

VI TELEFILTER**SAW Filter Specification****TFS 119A****1/5****Measurement condition**

Ambient temperature: 23 °C
 Input power level: 0 dBm
 Terminating impedances
 for input: 750 Ohm // -3.9 pF
 for output: 750 Ohm // -3.9 pF
 External coil: 279 nH

Characteristics

Remark:

Reference level for the relative attenuation a_{rel} of the TFS 119A is the insertion loss. The insertion loss a_e is defined as the insertion loss at the nominal frequency f_N . The centre frequency f_C is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed on 119.6 MHz without tolerance. The specified values have to be reached in operating temperature range.

D a t a		typ. Value		tolerance/limit	
Insertion loss	a_e	1.85	dB	1.25...3.25	dB
(Reference level)					
Nominal frequency	f_N	-		119,600	MHz
Centre frequency	f_C	119,605	MHz	-	
1 dB bandwidth	BW	162	MHz	-	
Relative attenuation	a_{rel}				
$f_N \pm 0,8 \text{ MHz} \dots f_N \pm 1,8 \text{ MHz}$		45	dB	min. 20	dB
$f_N \pm 1,8 \text{ MHz} \dots f_N \pm 6 \text{ MHz}$		43...48	dB	min. 30	dB
$f_N \pm 6 \text{ MHz} \dots f_N \pm 100 \text{ MHz}$		27...89	dB	min. 10	dB
VSWR					
@ f_N		1,5 : 1		max. 1,8 : 1	
Group delay	GD				
@ f_N		4,2	µs	max. 8,2	µs
Input power		-		max. 13	dBm
Operating temperature range				- 5 °C ... + 80 °C	
Temperature coefficient of frequency	TC	ca. - 0,036	ppm/K ²		
Frequency inversion temperature		+ 35 °C			

Generated:**Checked / approved:**

VI TELEFILTER
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@telefilter.com

Vectron International, Inc.
 267 Lowell Road
 Hudson, NH 03051 / USA
 Tel: (603) 598-0070 Fax: (603) 598-0075
 E-Mail: vti@vtinh.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

2/5

VI TELEFILTER**SAW Filter Specification****TFS 119A****3/5****Stability Characteristics**

After the following tests the filter shall meet the whole specification:


1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Damp heat: 25 °C to 55°C / 95% r.H. / 10 cycles
(cycle) DIN IEC 68 - 2 - 30 Db
4. Resistance to solder heat (reflow): max. 2 times reflow process;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;

Packing

Tape & Reel: IEC 286 - 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;
max. pieces of filters per reel: 3000
Reel of empty components at start: min 300 mm
Reel of empty components at start including leader: min 500 mm
Trailer min 300 mm

Tape (all dimensions in mm)


W	: 24	± 0,3
Po	: 4	± 0,1
Do	: 1,5	+ 0,1
E	: 1,75	± 0,1
F	: 7,5	± 0,1
G (min)	: 0,6	
P2	: 2	± 0,1
P1	: 8	± 0,1
D1(min)	: 1,5	
Ao	: 5,6	± 0,1
Bo	: 11,8	± 0,1
CT	: 21,5	± 0,1



www.DataSheet4U.com

Reel (all dimensions in mm):

A	:	330
W1	:	24,4 +2
W2 (max)	:	30,4
N (min)	:	60
C	:	13 +0,5/-0,2



The minimum bending radius is 45 mm. The mounting surface of the filters faces the bottom side of the embossed carrier tape. The marking of the filters is able to read if the view is directed on the upper side of the carrier tape with the sprocket holes on the right side of the tape.

VI TELEFILTER
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

Vectron International, Inc.
267 Lowell Road
Hudson, NH 03051 / USA
Tel: (603) 598-0070 Fax: (603) 598-0075
E-Mail: vti@vtinh.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**SAW Filter Specification****TFS 119A****4/5****Air reflow temperature conditions**

1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	


Chip-mount air reflow profile

Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

VI TELEFILTER**SAW Filter Specification****TFS 119A****5/5****History**

Version	Reason of Changes	Name	Date
1.2	Add preliminary values for termination impedance Add history Modify monthly date code into weekly date code Corrected tape and reel information	Dr. Wall	09.05.2000
1.3	Add final termination conditions Add typical filter data Add limits for insertion loss	Dr. Wall	16.06.2000
1.4	Add maximum input power Add relative attenuation value for $F_N \pm 6 \text{ MHz} \dots F_N \pm 100 \text{ MHz}$ Add group delay Notice 1 dB bandwidth instead of 3 dB bandwidth Increase window for insertion loss to two dB	Dr. Wall	28.06.2000
1.5	Change filter name to TFS119A Add external coil Change input power level to 13 dBm Remove typical filter values Remove termination impedances	Dr. Wall	19.07.2000
1.6	Add termination impedances and coupling coil value Define insertion loss window Add typical values for filter data Add maximum value for group delay Correct filter marking	Dr. Wall	14.09.2000