# RP-ULTRA<sup>™</sup> PoE/PoE+ Transformers

SMD Single Port 10/100BASE-TX PoE/PoE+ Isolation Modules

















## **Product Features:**


- RP-ULTRA<sup>™</sup>
- IEEE802.3af/at Compliant
- UL/EN60950 Recognized
- 100% Electrical Testing
- 1500Vrms Hi-Pot
- Patented Open Frame Construction

		Temp.			Return Loss (min)		Insertion		
Part Number	Circuit	PoE	Range	1-30MHz	40MHz	50MHz	60-80MHz	Loss (max)	RoHS <sup>1</sup>
TG110-RP55N5LF	А	PoE	0 to 70°C	-18dB	-16dB	-13dB	-12dB	-1.1dB	Pb-Free
TG110-RP55N5RL	А	PoE	0 to 70°C	-18dB	-16dB	-13dB	-12dB	-1.1dB	RoHS (7a)
TG110-RPE5N5LF	Α	PoE	-40 to +85°C	-18dB	-16dB	-13dB	-12dB	-1.1dB	Pb-Free
TG110-RPE5N5RL	А	PoE	-40 to +85°C	-18dB	-16dB	-13dB	-12dB	-1.1dB	RoHS (7a)
TG110-HPE7N5LF	В	PoE+	-40 to +85°C	-18dB	-14dB	-12dB	-10dB	-1.1dB	Pb-Free

#### Notes:


- 1. Pb-Free parts are RoHS 6/6 compliant. RoHS (7a) parts contain lead per exemption 7a which is set to expire in July 2016.
- 2. Parts with RL suffix are not recommended for new designs.
- 3. Contact the factory or your representative for individual datasheets or additional information.







# HALO ULTRA PoE 10/100BASE-TX Ethernet Transformers

## Mechanical








Dimensions: inch [mm] Co-Planarity: 0.004 [0.10]

US Patent Numbers: 5,656,985 6,297,721 B1 6,297,720 B1 6,320,489 B1 6,344,785 B1 6,662.431 B1



Recommended Solder Pad Layout

2880 Lakeside Drive #116
Santa Clara, CA 95054
(650) 903-3800
www.haloelectronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC isolation modules, and integrated Ethernet connectors. HALO's high quality and competitively priced leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories.