

TOSHIBA LED LAMP InGaAlP RED/GREEN LIGHT EMISSION

TLRMHGH48M(F)

○ BI-COLOR HIGH LUMINOSITY INDICATOR

- Lead(Pb) free(Sn-Ag-Cu)
- High Luminous Intensity.
- 5mm package
- InGaAlP Red/Green LED, the cathode is common to two colors.
- All plastic mold type.
- Milky white, diffusion lens.


Absolute Maximum Ratings (Ta = 25°C)

CHARACTERISTICS	SYMBOL	RATING	UNIT
FORWARD CURRENT	I_F	50 (Note)	mA
REVERSE VOLTAGE	V_R	4	V
POWER DISSIPATION	T_{opr}	-40~100	°C
OPERATING TEMPERATURE	T_{stg}	-40~120	°C

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.
Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note1: Maximum rating of "forward current – atmospheric temperature (i.e. I_F -Ta graph in the next page)" is for each component.

In case two components lightening, total current should be within the rating.



Weight: 0.37 g (typ.)





PRECAUTIONS

Please be careful of the followings



- Soldering temperature : 260 max Soldering time : 3 s max (Soldering portion of lead : below the lead stopper of the device)
- If the lead is formed, the lead should be formed up to below the lead stopper of the device without Formed stress to the resin. Soldering should be performed after lead forming.
- The visible LED lamp also emits some IR light.
If a photodetector is located near the LED lamp, please ensure that it will not be affected by the IR light.

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTICS		SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
FORWARD VOLTAGE	Red	V_F	$I_F = 20\text{mA}$	—	1.95	2.4	V
	Green			—	2.05	2.4	
REVERSE CURRENT	Red	I_R	$V_R = 4\text{V}$	—	—	50	uA
	Green			—	—	50	
LUMINOUS INTENSITY	Red	I_V	$I_F = 20\text{mA}$	272	450	—	mcd
	Green			153	220	—	
SPECTRAL LINE HALF WIDTH	Red	$\Delta\lambda$	$I_F = 20\text{mA}$	—	13	—	nm
	Green			—	13	—	
DOMINANT WAVELENGTH	Red	λ_d	$I_F = 20\text{mA}$	—	626	—	nm
	Green			—	571	—	



Radiation pattern



RESTRICTIONS ON PRODUCT USE

20070701-EN

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patents or other rights of TOSHIBA or the third parties.
- GaAs(Gallium Arsenide) is used in this product. The dust or vapor is harmful to the human body. Do not break, cut, crush or dissolve chemically.
- Please contact your sales representative for product-by-product details in this document regarding RoHS compatibility. Please use these products in this document in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses occurring as a result of noncompliance with applicable laws and regulations.